

COYOTE® Defender 2

Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

Description

The **COYOTE® Defender 2** is a condensed version of its predecessor as it is tailored to accommodate the [COYOTE® Dome Closure CRB System for OPGW](#). In comparison to the original [Defender](#), the Defender 2 reduces overall weight by 1/3 without sacrificing the level of ballistic protection as the 7 gauge steel thickness remains the same.

Product Spotlight

Features

- Two hinged doors with one door that mounts against the structure and the cover door that swings open for easy access.
- Can be mounted direct to the structure via 5/8" through bolts, DA bolts, or 1-1/4" wide band material.
- Defender 2 can also be mounted to the FIBERLIGN® Cable Storage 2 at cable storage locations.

Documentation

Application Procedures

[SP-3244 \(COYOTE Defender 2\)](#)

Catalog Pages

[COYOTE® Defender 2](#)

Part Tables

Catalog Number	Cable Storage and Ballistic Protection**
80061195	FIBERLIGN® CABLE Storage 2 for OPGW, 60" Loop
80061194	COYOTE® DEFENDER 2 for 6.5" x 17" and 6.5" x 22" Domes

**COYOTE Dome Kits include a Mounting Adapter that can vertically mount the dome directly to wood poles or band to metal poles. The modular design of the mounting adapter can be mounted to the FIBERLIGN® CABLE Storage 2 and COYOTE Defender 2 as well.