

GUY-GRIP® Dead-end

Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

Description

GUY-GRIP Dead-ends are intended for use on single wood poles associated with distribution construction. They are made of the same material as to which they are applied.

Features

- Rated at 100% of the strand's published rated breaking strength.
- Intended for single use but can be reinstalled twice within 90 days.

Documentation

Application Procedures

[SP-2045 \(GUY-GRIP® Dead-End\)](#)

[SP-3253 \(GUY-GRIP Dead-End - Multiple Down Guys\)](#)

Catalog Pages

[GUY-GRIP Dead-End - Catalog](#)

Part Tables

For use on: Extra High Strength, High Strength, Siemens Martin, Utilities Grade

B-Coat

Catalog Number	Strand			Units per carton	Wt./Lbs. per carton	Length (Inches)	Color Code
	Size (Inches)	Construction	Mean Diameter (Inches)				
GDE-1102	3/16	7W 7W	.186 .195	100	30	20	Red
GDE-1103	7/32	7W	.216	50	19	24	Green
GDE-1104	1/4	3W 7W	.259 .240	50	24	25	Yellow
GDE-1105	9/32	7W	.279	50	26	28	Blue
GDE-1106	5/16	3W 7W 7W	.312 .312 .327	50	39	31	Black
GDE-1107	3/8	3W 7W	.356 .360	50	51	35	Orange
GDE-1108	7/16	7W	.435	25	40	38	Green

C-Coat

Catalog Number	Strand			Units per carton	Wt./Lbs. per carton	Length (Inches)	Color Code
	Size (Inches)	Construction	Mean Diameter (Inches)				
GDE-2102	3/16	7W 7W	.186 .195	100	30	20	Red
GDE-2103	7/32	7W	.216	50	19	24	Green
GDE-2104	1/4	3W 7W	.259 .240	50	24	25	Yellow
GDE-2105	9/32	7W	.279	50	26	28	Blue
GDE-2106	5/16	3W 7W 7W	.312 .312 .327	50	39	31	Black
GDE-2107	3/8	3W 7W	.356 .360	50	51	35	Orange
GDE-2108	7/16	7W	.435	25	40	38	Green

For use on: Bezinal Strand

Catalog Number	Strand			Units per carton	Weight (Lbs) per carton	Length (Inches)	Color Code
	Size (Inches)	Construction	Mean Diameter (Inches)				
BDE-9102	3/16	7W 7W	.186 .195	100	30	20	Red
BDE-9104	1/4	3W 7W	.259 .240	50	24	25	Yellow
BDE-9106	5/16	3W 7W 7W	.312 .312 .327	50	39	31	Black
BDE-9107	3/8	3W 7W	.356 .360	50	51	35	Orange
BDE-9108	7/16	7W	.435	25	41	38	Green

For use on: Aluminum Clad Steel Strand

Catalog Number	Mean Diameter (Inches)	Nominal Strand Size	Units per carton	Wt./lbs. per carton	Length (Inches)	Color Code
AWDE-4102	.174	3 # 12	100	21	18	Orange
AWDE-4108	.220 .220	4M 3 # 10	50	20	21	Green
AWDE-4110	.247 .242	3 # 9 6M	50	20	24	Yellow
AWDE-4113	.277 .272	3 # 8 8M	50	22	24	Blue
AWDE-4116	.311 .306 .306	3 # 7 10M 5/16" - 7 # 10	50	29	26	Black
AWDE-4118	.330	11.5M	50	30	26	Green
AWDE-4119	.349 .343 .343	3 # 6 12.5M 11/32" - 7 # 9	50	41	29	Yellow
AWDE-4120	.363	14M	50	53	31	Blue
AWDE-4122	.392 .385 .386	3 # 5 3/8" - 7 # 8 16M	50	55	32	Orange
AWDE-4124	.417	18M	25	37	34	Black
AWDE-4125	.433	7/16" - 7 # 7	25	40	36	Green
AWDE-4126	.444	20M	10	22	37	Yellow
AWDE-4128	.486	1/2" - 7 # 6	10	23	39	Blue
AWDE-4130	.519	25M	10	31	43	Red
AWDE-4131	.546	7 # 5	10	32	44	Yellow

For use on: Aluminized Strand

Catalog Number	Strand			Units per carton	Wt./lbs. per carton	Length (Inches)	Color Code
	Size (Inches)	Construction	Mean Diameter (Inches)				
AZDE-7100	3/16	7W 7W	.186 .195	100	25	18	Red
AZDE-7102	1/4	3W 7W	.259 .240	50	22	23	Yellow
AZDE-7103	9/32	7W	.279	50	27	24	Blue
AZDE-7104	5/16	3W 7W 7W	.312 .312 .327	50	37	27	Black
AZDE-7106	3/8	3W 7W	.356 .360	50	63	32	Orange
AZDE-7107	7/16	7W	.435	25	45	34	Green

For use on: Copperweld Strand

Catalog Number	Mean Diameter (Inches)	Nominal Strand Size	Units	Wt./lbs	Length (Inches)	Color Code
CDE-8100	.164	2.2M	100	19	17	Orange
CDE-8102	.174	3 # 12	100	24	17	Red
CDE-8106	.209	4M	100	32	18	White
CDE-3101	.220	3 # 10	100	44	20	Green
CDE-3103	.247 .237	3 # 9 6M	50	24	21	Yellow
CDE-3104	.258	6M3	50	25	22	White
CDE-3106	.276 .277	8M 3 # 8	50	26	23	Blue
CDE-3109	.303 .306 .311	10M 7 # 10 - 5/16" 3 # 7	50	34	25	Red
CDE-3112	.343 .345 .349	7 # 9 - 11/32" 12.5M 3 # 6	50	46	27	Green
CDE-3113	.360	14M	50	64	30	Blue
CDE-3115	.385 .386 .392	7 # 8 - 3/8" 16M 3 # 5	50	65	31	White
CDE-3117	.414	18M	25	46	34	Orange
CDE-3118	.438 .433	20M 7 # 7 - 7/16"	25	47	35	Yellow
CDE-3121	.486	7 # 6 - 1/2"	25	65	39	Blue
CDE-3123	.525	25M	10	37	43	Green
CDE-3124	.546	7 # 5 - 9/16"	10	38	44	Yellow

For use on: Type 302 and Type 430 Strand

Type 302

Catalog Number	Strand			Units	Wt./ Lbs.	Length (Inches)	Color Code	Percent of Strands Rated Breaking Strength
	Size (Inches)	Construction	Mean Diameter (Inches)	Per Carton				
SDE-5101	7/32	3W 7W	.224 .216	100	30	22	Blue	100%
SDE-5102	1/4	3W 7W	.259 .249	50	25	26	Yellow	100%
SDE-5103	9/32	7W	.279	50	26	27	Black	90%
SDE-5104	5/16	3W 7W	.312 .312	50	41	31	Orange	93%
SDE-5105	3/8	3W 7W	.356 .360	50	66	37	Green	83%

For use on: Type 316 Strand

Type 316

Catalog Number	Strand			Units	Wt./ Lbs.	Length (Inches)	Color Code	Percent of Strands Rated Breaking Strength
	Size (Inches)	Construction	Mean Diameter (Inches)	Per Carton				
SDE-6101	7/32	3W 7W	.224 .216	100	30	22	Blue	100%
SDE-6102	1/4	3W 7W	.259 .249	50	25	26	Yellow	100%
SDE-6103	9/32	7W	.279	50	26	27	Black	90%
SDE-6504*	5/16	3W 7W	.312 .312	50	41	31	Orange	93%
SDE-6105	3/8	3W 7W	.356 .360	50	66	37	Green	87%
SDE-6107	1/2	7W	.500	10	52	53	Blue	85%