

FIBERLIGN® Dead-end Set



Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

Documentation

See Pages 5-3 [Communication Catalogue](#)

Part Tables

Assembly Part Number	Cable Diameter Range (mm)	Colour Code
OPGWTS-0900*	9.00 - 9.49	Pink
OPGWTS-0950*	9.50 - 9.99	Orange
OPGWTS-1000*	10.00 - 10.39	Red
OPGWTS-1040*	10.40 - 10.79	Black
OPGWTS-1080*	10.80 - 11.29	Green
OPGWTS-1130*	11.30 - 11.69	Brown
OPGWTS-1170*	11.70 - 12.09	Purple
OPGWTS-1210*	12.10 - 12.59	Yellow
OPGWTS-1260*	12.60 - 12.99	Blue
OPGWTS-1300*	13.00 - 13.39	White
OPGWTS-1340*	13.40 - 13.89	Orange
OPGWTS-1390*	13.90 - 14.29	Red
OPGWTS-1430*	14.30 - 14.60	Black
OPGWTS-1461*	14.61 - 15.10	Green
OPGWTS-1511*	15.11 - 15.50	Brown
OPGWTS-1551*	15.51 - 15.99	Purple
OPGWTS-1600*	16.00 - 16.40	Yellow
OPGWTS-1641*	16.41 - 16.99	Blue
OPGWTS-1700*	17.00 - 17.20	White
OPGWTS-1721*	17.21 - 17.70	Orange
OPGWTS-1771*	17.71 - 18.00	Red
OPGWTS-1801*	18.01 - 18.50	Black
OPGWTS-1851*-2E	18.51 - 19.00	Brown
OPGWTS-1901*-2E	19.01 - 19.40	Purple
OPGWTS-1941*-2E	19.41 - 19.80	Purple
OPGWTS-1981*-2E	19.81 - 20.20	Yellow
OPGWTS-2021*-2E	20.21 - 20.70	Yellow
OPGWTS-2071*-2E	20.71 - 21.10	Blue
OPGWTS-2111*-2E	21.11 - 21.50	Blue
OPGWTS-2151*-2E	21.51 - 22.00	Orange
OPGWTS-2201*-2E	22.01 - 22.40	Orange
OPGWTS-22.41*-2E	22.41 - 22.80	Red
OPGWTS-2281*-2E	22.81 - 23.20	Red
OPGWTS-2321*-2E	23.21 - 23.80	Black

Note: -2E denotes 2 x earth bonding leads for high fault current OPGW.

* Substitute L for left hand Lay conductors

* Substitute R for Right Hand Lay conductors

OPGWTS - Assembly contents
Wedge Type Dead-end Assembly
70 kN Shackle
Earth bonding lead with lugs

