

House Service Connector



Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

Description

The new D-K96A is a fully overmoulded waterproof connection designed with solid internal chambers. It also includes a new shearhead indicator system. It is used to make electrical connection from an insulated supply cable to an insulated consumer cable.

Features

- Bi-metal corrosion resistance accepting both copper and aluminium cables.
- Completely overmoulded design.
- Multiple rib sealing system to ensure integrity of seal on all cable sizes - including fully ribbed ABC.
- Central solid barrier dividing each chamber.
- Fully insulated and water proof.
- Overmoulded shearhead bolt.
- Fits the existing main connection box (MCB).
- Consumers cable can be disconnected and reconnected.
- Tested to AS/NZS4396.
- Connectors is marked with cable sizes and strip requirements.
- Consumers and mains sides are clearly differentiated with markings and bolt colour.

Documentation

[Trade Catalogue](#) see p.10 - p.17

Part Tables

Part Number	Supply Cable Range mm²	Supply Connection Type	Supply Bolt Colour	Customer Cable Range mm²	Customer Connection Type	Customer Bolt Colour
D-K96A	6 - 35	Ins Piercing	Black	4 - 35	Strip Cable	White