

Compression Sleeves (Full Tension)

Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm



Description

Full Tension - AAC, AAAC and ACSR

Features

- PLPFT fittings have been designed to suit AAC and AAAC distribution lines up to 66kV to give full tension under load to AS1154
- The FTA sleeves are suitable for ACSR but as a limited tension fitting carrying a maximum of 50% of the conductor UTS
- Pre-packed with jointing compound, individually packed in sealed plastic bags
- Uses hexagonal dies

Documentation

[Trade Catalogue](#) see p.24 - p.25

Part Tables

Part Number	Conductor Code	Conductor Type	Conductor Stranding	A/F Die Size (mm)
PLPFT36A	Leo	AAC	7/2.50	14
	Chlorine	AAAC	7/2.50	
	Almond*	ACSR	6/1/2.50	
	Angling	ACSR	6/1/2.50	
PLPFT44A	Libra	AAC	7/3.00	18
	Fluorine	AAAC	7/3.00	
	Apricot*	ACSR	6/1/2.75	
	Apple*	ACSR	6/1/3.00	
PLPFT50A	Archery*	ACSR	6/1/3.00	18
	Mars	AAC	7/3.75	
	Helium	AAAC	7/3.75	
	Banana*	ACSR	6/1/3.75	
	Cherry*	ACSR	6/4.75/7/1.60	
CMFT61A	Bowls*	ACSR	6/4.75/7/1.60	22
	Baseball*	ACSR	6/1/3.75	
	Mercury	AAC	7/4.50	
	Hydrogen	AAAC	7/4.50	
CMFT68A	Moon	AAC	7/4.75	22
	Iodine	AAAC	7/4.75	
CMFT68A	Neptune	AAC	19/3.25	22
	Krypton	AAAC	19/3.25	

*50% U.T.S. for ACSR conductors