

PSCCS

Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm



Description

Plastic Substation Cable Clamp Single

The Single Hole type cable clamps fasten a wide range of single and multi conductor low, medium and high voltage cables. Designed to provide superior mechanical strength, ideal for installations where cables are subject to short circuits.

Features

- Made of glass fibre reinforced polyamide (PA)
- Resistant to oils, UV, ozone, salts, moisture, acids and even radioactive emissions
- Self-extinguishing V-0 (UL94), halogen-free, low smoke
- Temperature range from -40°C to 120°C
- Black coloured
- Available pre-mounted
- Stainless steel fasteners included

Testing:

By UL, KEMA, Eaton and Centrilab (reports available upon request).

Documentation

[Trade Catalogue](#) see p.26 - p.27

Part Tables

Part Number	Dimensions (mm)									Mechanical Strength
	DØ	L	B	l	d	H1	H2	h	a	
PSCCS26-38	26-38	92	60	60	12	33-49	7	18	7	30,000Nm
PSCCS36-52	36-52	105	60	75	12	39-55	15	23	8	20,000Nm
PSCCS50-75	50-75	126	60	95	12	46-71	22	30	9	20,00Nm
PSCCS75-100	75-100	200	80	150	12	70-95	32	45	10	68,000Nm