

EZ-WRAP® Spool Tie

Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

Description

The **EZ-WRAP Spool Tie** is intended for use on aluminum based conductors with diameters from .190" to .968".

Features

- An EZ-WRAP Spool Tie Assembly consists of one metal tie component plus tie tube
- The elastomeric tie tube is designed for abrasion protection with bare conductors

Documentation

Application Procedures

[SP-2762 \(EZ-WRAP® Spool Tie\)](#)

Catalog Pages

[EZ-WRAP® Spool Tie - Catalog](#)

Part Tables

Catalog Number	Diameter Range (Inches)		Nominal Conductor Size		Units	Wt./Lbs.	Applied Length (Inches)	Color Code
	Min.	Max.	Bare Conductor	Plastic Jacketed Conductor	Per Carton			
EZSP-4372	.245	.277	#4 (6/1, 7/1) #4 (7W Alum. Alloy)	#6 (7W, 2/64s) #6 (Solid, 3/64s) #6 (6/1, 2/64s)	100	16	19	Orange
EZSP-4374	.316	.357	#2 (6/1, 7/1) #2 (7W Alum. Alloy) #1 (6/1)	#4 (7W, 3/64s) #4 (6/1, 7/1, 3/64s)	100	16	24	Red
EZSP-4375	.358	.405	1/0 (7W All Alum.) 1/0 (6/1) 1/0,7(W Alum. Alloy)	#3 (7W, 4/64s) #2 (7W, 3/64s) #4 (7W, 5/64s)	100	17	26	Yellow
EZSP-4376	.406	.459	2/0 (7W All Alum.) 2/0 (6/1) 2/0 (7W Alum. Alloy)	#2 (6/1, 3/64s) #2 (7W, 4/64s) #1 (7W, 4/64s)	100	21	28	Blue
EZSP-4377	.460	.520	3/0 (7W All Alum.) 3/0 (6/1) 3/0 (7W Alum. Alloy)	#4 (7W, 8/64s) #1 (6/1, 4/64s) #1 (7W-19W, 5/64s) 1/0 (7W, 4/64s)	100	21	31	Orange
EZSP-4378	.521	.588	4/0 (7W All Alum.) 4/0 (6/1) 4/0 (7W Alum. Alloy)	1/0 (6/1, 4/64s) 1/0 (7W, 5/64s) 2/0 (7W, 4/64s) 1/0 (6/1, 5/64s)	100	27	32	Red
EZSP-4379	.589	.665	266.8 (37W All Alum.) 266.8 (18/1) 336.4 (19W All Alum.)	3/0 (7W-19W, 4/64s) 3/0 (6/1, 4/64s) 4/0 (7W 19W, 4/64s) 3/0 (6/1, 5/64s)	100	28	23	Purple
EZSP-4380	.666	.755	336.4 (18/1) 397.5 (19W All Alum.) 400 (19W, 37W All Alum.)	4/0 (7W, 5/64s) 3/0 (6/1, 6/64s) 4/0 (6/1, 5/64s) 266.8 (19W, 5/64s)	100	30	25	Brown
EZSP-4381	.756	.858	477 (19W, 37W All Alum.) 477 (18/1, 24/7), 26/7	266.8 (18/1, 5/64s) 336.4 (19W, 4/64s) 336.4 (37W, 6/64s)	100	35	26	Red
EZSP-4382	.859	.968	556.5 (26/7) 636 (18/1) 700 (37W, 61W All Alum.)	350 (37W, 6/64s) 336.4 (19W, 8/64s) 450 (37W, 5/64s) 477(37W, 5/64s)	100	40	28	Blue
EZ-MS-10279	.969	1.096	636 (24/7, 26/7, 54/7) 795 (37W, 61W) 795 (36/1, 24/7, 54/7)	500 (37W, 5/64s) 477 (37W, 8/64s) 500 (37W, 8/64s)	100	66	38	Green

Videos

Product Gallery