

# Tangent Side Tie: Plastic

**Weight:** 0.00kg

**Dimensions:** 0.00cm x 0.00cm x 0.00cm

## Description

**Plastic Tangent Side Ties** are intended for use on “tangent” construction with jacketed conductors and side mounted tie top insulators on armless construction. Line or sag angles of up to 15° are recommended.

## Features

- Suitable for use with any plastic covered conductor such as Tree Wire or Spacer Cable
- Two versions available: Standard "PVC" and "Semi-Con" for higher voltage applications

## Documentation

### Application Procedures

[SP-2120 \(Plastic Side Tie\)](#)

## Catalog Pages

[Tangent Plastic Side Tie - Catalog](#)

## Part Tables

### C-Neck

PVC Plastic Ties Catalog Number	Semi-Con Plastic Ties Catalog Number	OD Range (in.)		Nominal Conductor Size	Units per carton	Approx. Wt./Lbs.	Approx. Applied Length (in.)	Insulator Color ID Mark (PVC/SC)	Conductor Color Code (PVC/SC)
		Min.	Max.						
SSC-2150	SSC-2150SC	0.296	0.400	#4, 6/1, 2/64s	100	22	17	Black/None	White
SSC-2151	SSC-2151SC	0.401	0.540	#2, 6/1, 3/64s #4, 7W, 8/64s	100	22	16	Black/None	Green
SSC-2152	SSC-2152SC	0.541	0.730	1/0, 6/1, 10/64s 3/0, 6/1, 4/64s	100	23	16	Black/None	Blue
SSC-2153	SSC-2153SC	0.731	0.920	4/0, 6/1, 10/64s 336.4, 18/1, 6/64s	100	25	18	Black/None	Orange
SSC-2154	SSC-2154SC	0.921	1.100	336.4, 18/1, 10/64s 447, 19W, 8/64s	100	27	19	Black/None	Red
SSC-2155	SSC-2155SC	1.101	1.300	477, 37W, 10/64s 397.5, 19W, 12/64s	100	15	21	Black/None	Black/None

## F-Neck

PVC Plastic Ties Catalog Number	Semi-Con Plastic Ties Catalog Number	OD Range (in.)		Nominal Conductor Size	Units per carton	Approx. Wt./Lbs.	Approx. Applied Length (in.)	Insulator Color ID Mark (PVC/SC)	Conductor Color Code (PVC/SC)
		Min.	Max.						
SSF-2250	SSF-2250SC	0.296	0.400	#4, 6/1, 2/64s	50	12	18	Yellow	White
SSF-2251	SSF-2251SC	0.401	0.540	#2, 6/1, 3/64s #4, 7W, 8/64s	50	12	17	Yellow	Green
SSF-2252	SSF-2252SC	0.541	0.730	1/0, 6/1, 10/64s 3/0, 6/1, 4/64s	50	13	17	Yellow	Blue
SSF-2253	SSF-2253SC	0.731	0.920	4/0, 6/1, 10/64s 336.4, 18/1, 6/64s	50	14	19	Yellow	Orange
SSF-2254	SSF-2254SC	0.921	1.100	336.4, 18/1, 10/64s 447, 19W, 8/64s	50	15	20	Yellow	Red
SSF-2255	SSF-2255SC	1.101	1.300	477, 37W, 10/64s 397.5, 19W, 12/64s	50	17	22	Yellow	Black/None

## Product Gallery