

Slack Span Dead-end

Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

Description

Slack Span Dead-end is intended for use on aluminum based conductors with diameter ranges from .229" to 1.216". It is specifically designed to terminate primary, secondary and neutral conductors. Each Slack Span Dead-end covers a range of conductor diameters.

Features

- Tools are not required to install Slack Span Dead-ends, except for hot stick applications.
- Specifically designed to be installed on pin, line post or spool insulators when used in limited tension construction.
- The loop of the Dead-end is covered with an elastomer to provide protection against abrasion and damage to the glaze of the insulator.
- Designed to grip the conductor uniformly to prevent distortion.
- Offers a unique design that eliminates bolts, nuts, washers and other component parts.

Documentation

Application Procedures

[SP-2604 \(Slack Span Dead-end\)](#)

Catalog Pages

[Slack Span Dead-end - Catalog](#)

Part Tables

C-Neck & F-Neck

Catalog Number	Conductor		Per Carton Units	Length (Inches)	Color Code
	Range (Inches)	Nominal Size			
SSDE-9122	.229-.257	#4 AWG	25	16	Orange
SSDE-9124	.290-.325	#2 AWG	25	18	Red
SSDE-9125	.326-.364	#1 AWG	25	19	Green
SSDE-9126	.365-.409	1/0 AWG	25	20	Yellow
SSDE-9127	.410-.460	2/0 AWG	25	18	Blue
SSDE-9128	.461-.516	3/0 AWG	25	18	Orange
SSDE-9129	.517-.577	4/0 AWG	25	19	Red
SSDE-9130	.578-.665	266.8 kcmil	25	21	Black
SSDE-9131	.666-.783	336.4 kcmil	25	21	Green
SSDE-9132	.784-.883	477 kcmil	25	22	Orange
SSDE-9133	.884-1.025	636 kcmil	25	25	Brown
SSDE-9134	1.026-1.216	795 kcmil	25	26	Orange

J-Neck

Catalog Number	Conductor		Per Carton Units	Length (Inches)	Color Code
	Range (Inches)	Nominal Size			
SSDE-9142	.229-.357	#4 AWG	25	18	Orange
SSDE-9144	.290-.325	#2 AWG	25	19	Red
SSDE-9145	.326-.364	#1 AWG	25	20	Green
SSDE-9146	.365-.409	1/0 AWG	25	21	Yellow
SSDE-9147	.410-.460	2/0 AWG	25	19	Blue
SSDE-9148	.461-.516	3/0 AWG	25	20	Orange
SSDE-9149	.517-.577	4/0 AWG	25	21	Red
SSDE-9150	.578-.665	266.8 kcmil	25	22	Black
SSDE-9151	.666-.783	336.4 kcmil	25	23	Green
SSDE-9152	.784-.883	477 kcmil	25	24	Orange
SSDE-9153	.884-1.025	636 kcmil	25	27	Brown
SSDE-9154	1.026-1.216	795 kcmil	25	28	Orange