

Thimble Clevis

Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

Description

Thimble Clevises are used in conjunction with PREFORMED Dead-ends on suspension-type or Dead-end insulators. The thimble is intended to provide a smooth internal contour to prevent stress concentration within the loop of a PREFORMED Dead-end. The Clevis includes a steel pin which links it through the eye of an insulator and secures it with a humpbacked cotter key.

Features

- If removal or replacement of an insulator, or similar maintenance, is required, only the cotter key and steel pin need to be removed to release the clevis.

Documentation

Catalog Pages

[Thimble Clevis - Catalog](#)

Part Tables

Catalog Number	Dimensions (Inches)										
	A	B	C Dia	D	E	F	G	H	I	J	K
TC-5A	1-1/8	1-1/4	11/16	3	1-3/4	15/16	1-13/32	1/2	2-3/16	2-15/16	5/8
ATC-20M	1-1/2	1	11/16	4-11/32	2-13/16	1-1/2	2-3/32	3/4	3-3/8	3-1/16	5/8
TC-5F	1-1/8	1-1/4	11/16	3	1-5/8	15/16	1-13/32	1/2	2-3/16	2-15/16	5/8
TC-17	13/16	3/4	11/16	2-5/16	1-3/8	3/4	1-1/8	3/8	1-7/8	1-5/8	5/8
TC-6F	1-1/4	1-1/2	13/16	3-1/2	2-1/16	1-1/16	1-23/32	17/32	2-3/4	2-7/16	3/4
TC-7F	1.4	1-1/2	1-1/16	4-1/4	3-1/2	2-1/4	2	3/4	25	4	1

Catalog Number	Wt. Per Unit	Units Per Carton	RHS	Material
TC-5A	0.75 lb	25	12,000	Aluminum
ATC-20M	1.8 lb	25	20,000	Aluminum
TC-5F	1.6 lb	25	26,900	Iron
TC-17	1 lb	25	15,000	Iron
TC-6F	2.4 lb	25	42,400	Iron
TC-7F	7.3 lb	Bulk Package	60,000	Iron

