



**PREFORMED** LINE PRODUCTS

The connection you can count on.



## INSULATED CONDUCTOR FITTINGS CATALOGUE

SCAN QR CODE  
TO DOWNLOAD THIS CATALOGUE



## INSULATED CONDUCTOR FITTINGS FOR LOW & HIGH VOLTAGE ABC, CC & CCT CATALOGUE

SCAN QR CODE  
FOR OTHER PLP CATALOGUES



- ❑ Communications
- ❑ Distribution
- ❑ Insulator
- ❑ Substation
- ❑ Transformer
- ❑ Transmission

## PREFORMED LINE PRODUCTS

Preformed Line Products Australia Pty Ltd (PLP) has been supplying product to Australian power utilities for over 50 years. Many of the original products are still found in the electricity network today, highlighting the exceptionally high quality standards that are expected and supplied.

The company has three major operating divisions, PLP which manufactures and carries a range of products for the power distribution, power transmission, substation and communications markets. Rack Technologies which has a range of cabinets and enclosures for the data communication, electronics, electrical and security markets and BlueSky Energy which offers solar power products and sustainable energy systems.

PLP's Australian operation boasts in-house manufacturing, engineering, testing, sales and administration. The modern manufacturing facility in the Sydney suburb of Glendenning includes wire forming, forging, casting, plastic moulding and extrusion, sheet metal work, powder coating and assembly. The manufacturing facility is supported by a modern toolroom which includes the latest CNC vertical machining centre, linked directly to the engineering office.

## ABC SYSTEMS

PLP manufactures insulated fittings for LVABC, HVABC and CCT to suit aluminium and copper systems for the power distribution sector. Additional to the PLP ABC product range and through a partnership with Michaud Group in France, PLP provides a comprehensive range of insulation piercing connectors (IPC). Michaud's dedication to product quality and technical performance makes them a market leader in the manufacture of IPCs worldwide.

### Features of all Michaud IPC are:

- Insulated type suit both aluminium and copper cables – bi-metallic.
- Contacts are compatible with conductor type and application.
- Plastic components are UV stabilised glass reinforced polymer.
- All stainless steel fasteners.
- Torque controlled shear off bolts.
- Connectors are completely air and water tight to prevent corrosion.
- Multiple membrane sealing end caps don't rely on the use of grease.
- Di-electric strength in water over 6kV.
- Fasteners thread is shielded from cable area, to eliminate cable damage whilst tightening.
- Permanently engraved with batch codes and traceability information.
- Conforms to all applicable requirements of AS/NZS4396.

PLP Australia manufactures products that cover the functions of termination, suspension, connection and protection along with a wide range of line hardware fittings and accessories. This Insulated Conductor Fittings Catalogue covers LVABC, HVABC and CCT products and an extensive range of these fittings are stocked at PLP's Glendenning warehouse.

If you have a particular requirement, please do not hesitate to contact PLP on (02) 8805 0000.



# CATALOGUE CONTENT

“ *Preformed Line Products, the connection you can count on.* ”

|                         | PAGE |
|-------------------------|------|
| <b>INDEX</b>            |      |
| CATALOGUE INDEX.....    | 4-6  |
| ALPHABETICAL INDEX..... | 50   |
| PART NUMBER INDEX.....  | 51   |

## LOW VOLTAGE FITTINGS

|  |     |
|--|-----|
| INSULATED PIERCING CONNECTORS.....                           | 8-9 |
| FLEXIBLE END CAPS.....                                       | 10  |
| HOUSE SERVICE CONNECTOR.....                                 | 11  |
| MAINS CONNECTION BOX (K SERIES).....                         | 11  |
| BARE MAINS TO SERVICE CONNECTIONS<br>(R SERIES).....         | 12  |
| PRE-INSULATED COMPRESSION SLEEVES.....                       | 13  |
| PRE-INSULATED COMPRESSION LUGS.....                          | 14  |
| MAIN STRAIN CLAMPS.....                                      | 14  |
| SERVICE CLAMPS.....  | 15  |
| SUSPENSION CLAMP FOR BUNDLED<br>CONDUCTORS (AS SERIES).....  | 16  |
| SUSPENSION CLAMP.....  | 16  |
| SUSPENSION CLAMP FOR BUNDLED<br>CONDUCTORS (ASV SERIES)..... | 17  |
| SUSPENSION CLAMPS AND INTEGRATED<br>STRINGING ROLLER.....    | 18  |
| FAÇADE MOUNTING BRACKETS<br>(CABLE SADDLE).....              | 19  |
| SAFETY SERVICE DISCONNECTOR (SSD).....                       | 20  |
| FUSED SWITCH DISCONNECTS (POLE FUSE).....                    | 21  |
| ACCESSORIES.....   | 21  |
| FUSED SWITCH DISCONNECTS (POLE FUSE).....                    | 22  |
| GANG MOUNTED.....  | 22  |
| FUSED SWITCH DISCONNECTS.....                                | 23  |
| IN LINE OVERHEAD OR PILLAR FUSE.....                         | 23  |
| FUSED SWITCH CONNECTOR (INDEPENDENT<br>TIGHTENING).....      | 24  |
| FUSED SWITCH CONNECTOR.....                                  | 24  |
| PITT FUSED UNDERGROUND (FSD).....                            | 25  |
| RING CONNECTOR.....  | 25  |

## HIGH VOLTAGE FITTINGS

|  |    |
|--|----|
| STRAIN ASSEMBLY AND BUNDLED RESTRAINT..... | 28 |
| HELICAL LINE SPLICE.....                   | 29 |
| COMPRESSION MIDSPAN JOINT.....             | 29 |
| SUSPENSION CLAMP.....                      | 30 |
| POLE SUPPORT CLAMP.....                    | 31 |
| YOKE BAR FOR ABC SUSPENSION.....           | 31 |
| M16 GALVANISED HOOK BOLTS.....             | 32 |
| STRING ROLLER (TYPE LSR23379).....         | 32 |
| POLE BRACKET.....                          | 33 |

## COVERED CONDUCTOR FITTINGS (CCT)

|   |    |
|---|----|
| STRAIN CLAMPS AND COVERS (CCT).....                                 | 36 |
| UNCOVERED STRAIN CONNECTIONS (CCT).....                             | 36 |
| COMPRESSION JOINTS AND COVERS (CCT).....                            | 36 |
| NON METALLIC HELICAL TOP AND<br>SIDE TIES (CCT).....                | 37 |
| INSULATOR TOP CLAMPS (CCT).....                                     | 37 |
| PARALLEL GROOVE CLAMPS FOR LINE<br>TAPS AND NON TENSION JOINTS..... | 38 |
| WORKING EARTH POINT COVERS.....                                     | 38 |
| INSULATION PIERCING CONNECTOR<br>(LIGHTING PROTECTION).....         | 39 |
| MOUNTING BRACKET INSULATORS.....                                    | 39 |
| CABLE STRIPPING TOOLS.....  | 40 |
| STRINGING ROLLER ASSEMBLIES.....                                    | 40 |

## HARDWARE

|                              |    |
|------------------------------|----|
| MECHANICAL WEAK LINK.....    | 42 |
| EYE NUT.....                 | 42 |
| HOOK NUT.....                | 42 |
| HOOK BRACKET.....            | 43 |
| SERVICE SUPPORT BRACKET..... | 43 |














## ASSEMBLY AND STRINGING TOOLS











|  |    |
|--|----|
| CABLE STRIPPING TOOLS.....   | 46 |
| RUNNING SHEAVES.....   | 46 |
| CORE SEPARATING TOOLS.....   | 46 |
| RATCHET SPANNERS.....  | 47 |
| SWIVELS.....   | 47 |
| NYLON (LV CONDUCTORS).....   | 47 |
| COME-ALONGS TENSIONING DEVICES.....  | 48 |
| COME-ALONG CLAMP (AS SERIES).....  | 48 |
| CABLE STRIPPING TOOLS.....   | 48 |
| HEAVY DUTY STEEL CONSTRUCTION ALUMINIUM<br>AND STEEL BASED CONDUCTORS..... | 49 |
| NYLON (HV CONDUCTORS).....   | 49 |
| J HOOK DRIVER.....   | 49 |

## CATALOGUE INDEX





### ■ LOW VOLTAGE FITTINGS

|  |  |          |
|--|--|----------|
|    | Accessories                                    | 21       |
|    | Bare Mains to Service Connectors (R Series)    | 12       |
|    | Facade Mounting Brackets (Cable saddle)        | 19       |
|    | Flexible End Caps                              | 10       |
|    | Fuse Switch Connector                          | 24       |
|   | Fuse Switch Connector (Independent Tightening) | 24       |
|  | Fused Switch Disconnects                       | 23       |
|  | Fused Switch Disconnects (Pole Fuse)           | 21<br>22 |
|  | House Service Connector                        | 11       |
|  | In Line Overhead or Pillar Fuse                | 23       |
|  | Insulation Piercing Connectors                 | 8<br>9   |
|  | Main Strain Clamps                             | 14       |
|  | Mains Connection Box (K Series)                | 11       |







|   |   |    |
|---|---|----|
|    | PITT Fused Underground (FSD)                                | 25 |
|    | Pre-Insulated Compression Lugs                              | 14 |
|    | Pre-Insulated Compression Sleeves                           | 13 |
|    | Ring Connector  | 25 |
|    | Safety Service Disconnect (SSD)                             | 20 |
|   | Service Clamps  | 15 |
|  | Suspension Clamp  | 16 |
|  | Suspension Clamp (AS Series) For Aerial-Bundled Conductors  | 16 |
|  | Suspension Clamp (ASV Series) For Aerial-Bundled Conductors | 17 |
|  | Suspension Clamps and Integrated Stringing Roller           | 18 |

### ■ HIGH VOLTAGE FITTINGS







|   |                           |    |
|---|---------------------------|----|
|  | Compression Midspan Joint | 29 |
|  | Helical Line Splice       | 29 |






## CATALOGUE INDEX









|   |                                      |    |
|---|--------------------------------------|----|
|   | M16 Galvanised Hook Bolts            | 32 |
|   | Pole Support Clamp                   | 31 |
|   | Strain Assembly and Bundle Restraint | 28 |
|   | String Roller (Type LSR23379)        | 32 |
|   | Suspension Clamp                     | 30 |
|  | Yoke Bar for ABC Suspension          | 31 |

### ■ COVERED CONDUCTOR FITTING (CCT)

|  |  |    |
|--|--|----|
|  | Cable Stripping Tools                        | 40 |
|  | Compression Joints and Covers (CCT)          | 36 |
|  | Insulator Top Clamps (CCT)                   | 37 |
|  | Non Metallic Helical Top and Side Ties (CCT) | 37 |
|  | Strain Clamps and Covers (CCT)               | 36 |
|  | Uncovered Strain Connections (CCT)           | 36 |












|   |   |    |
|---|---|----|
|  | Insulation Piercing Connector (Lightning Protection)        | 39 |
|  | Mounting Bracket Insulators                                 | 39 |
|  | Parallel Groove Clamps for Line Taps and Non Tension Joints | 38 |
|  | Stringing Roller Assemblies                                 | 40 |
|  | Working Earth Point Covers                                  | 38 |

### ■ HARDWARE

|   |                         |    |
|---|-------------------------|----|
|  | Eye Nut                 | 42 |
|  | Hook Bracket            | 43 |
|  | Hook Nut                | 42 |
|  | Mechanical Weak Link    | 42 |
|  | Pole Bracket            | 44 |
|  | Service Support Bracket | 43 |

## CATALOGUE INDEX

### ■ ASSEMBLY AND STRINGING TOOLS

|   |  |          |
|---|--|----------|
|     | Cable Stripping Tools  | 46<br>48 |
|     | Come-alongs<br>Tensioning Devices  | 48       |
|     | Come-Along Clamp<br>(AS Series)  | 48       |
|    | Core Separating Tools  | 46       |
|    | Heavy Duty Steel<br>Construction Aluminium and<br>Steel Based Conductors | 49       |
|  | J Hook Driver  | 49       |
|  | Nylon (HV Conductors)  | 49       |
|  | Nylon (LV Conductors)  | 47       |
|  | Ratchet Spanners   | 47       |
|  | Running Sheaves  | 46       |
|   | Swivels  | 47<br>49 |

# ABC

# LOW VOLTAGE FITTINGS

## PAGE

### LOW VOLTAGE FITTINGS

|   |     |
|---|-----|
| INSULATED PIERCING CONNECTORS . . . . .                           | 8-9 |
| FLEXIBLE END CAPS . . . . .                                       | 10  |
| HOUSE SERVICE CONNECTOR . . . . .                                 | 11  |
| MAINS CONNECTION BOX (K SERIES) . . . . .                         | 11  |
| BARE MAINS TO SERVICE CONNCETIONS<br>(R SERIES) . . . . .         | 12  |
| PRE-INSULATED COMPRESSION SLEEVES . . . . .                       | 13  |
| PRE-INSULATED COMPRESSION LUGS . . . . .                          | 14  |
| MAIN STRAIN CLAMPS . . . . .                                      | 14  |
| SERVICE CLAMPS . . . . .  | 15  |
| SUSPENSION CLAMP FOR BUNDLED<br>CONDUCTORS (AS SERIES) . . . . .  | 16  |
| SUSPENSION CLAMP . . . . .  | 16  |
| SUSPENSION CLAMP FOR BUNDLED<br>CONDUCTORS (ASV SERIES) . . . . . | 17  |
| SUSPENSION CLAMPS AND INTEGRATED<br>STRINGING ROLLER . . . . .    | 18  |
| FACADE MOUNTING BRACKETS<br>(CABLE SADDLE) . . . . .              | 19  |
| SAFETY SERVICE DISCONNECTOR (SSD) . . . . .                       | 20  |
| FUSED SWITCH DISCONNECTS (POLE FUSE) . . . . .                    | 21  |
| ACCESSORIES . . . . .   | 21  |
| FUSED SWITCH DISCONNECTS (POLE FUSE) . . . . .                    | 22  |
| GANG MOUNTED . . . . .  | 22  |
| FUSED SWITCH DISCONNECTS . . . . .                                | 23  |
| IN LINE OVERHEAD OR PILLAR FUSE . . . . .                         | 23  |
| FUSED SWITCH CONNECTOR (INDEPENDENT<br>TIGHTENING) . . . . .      | 24  |
| FUSED SWITCH CONNECTOR . . . . .                                  | 24  |
| PITT FUSED UNDERGROUND (FSD) . . . . .                            | 25  |
| RING CONNECTOR . . . . .  | 25  |

“ Comprehensive Range of Low Voltage ABC Fittings ”



# LOW VOLTAGE FITTINGS



## INSULATION PIERCING CONNECTORS



Fig. 1

This I.P.C (Insulation Piercing Connector) is used to establish a tap connection from a low voltage ABC (Aerial Bundled Conductors). Aluminium or copper.

### Insulated cable to insulated cable (Aluminium or Copper)

| Part No. | Fig No. | Cable Range 1 mm <sup>2</sup> | Cable Range 2 mm <sup>2</sup> | No. of Bolts | Shear Head A/F mm |
|----------|---------|-------------------------------|-------------------------------|--------------|-------------------|
| K440     | 1       | 10 - 95                       | 1.5 - 6                       | 1            | 13                |
| K441     | 1       | 25 - 95                       | 6 - 35                        | 1            | 13                |
| K442     | 1       | 35 - 150                      | 1.5 - 25                      | 1            | 13                |
| K443     | 1       | 35 - 150                      | 6 - 35                        | 1            | 13                |
| K445     | 1       | 25 - 95                       | 25 - 95                       | 1            | 17                |
| K446     | 2       | 50 - 150                      | 50 - 150                      | 2            | 17                |



Fig. 2

This I.P.C (Insulation Piercing Connector) is used to establish a tap connection from low voltage ABC (Aerial Bundled Conductors) to a low voltage aluminium alloy or copperbare main conductor.

### Bare cable to insulated (Aluminium or Copper) cable

| Part No. | Fig No. | Bare Cable Material | Bare Cable Size mm <sup>2</sup> | Insulated Cable Size mm <sup>2</sup> | No. of Bolts | Shear Head A/F mm | Type of Piercing Connection |
|----------|---------|---------------------|---------------------------------|--------------------------------------|--------------|-------------------|-----------------------------|
| K470     | 3       | Copper              | 7 - 95                          | 6 - 35                               | 1            | 13                | Standard                    |
| K472     | 4       | Copper              | 7 - 120                         | 25 - 95                              | 1            | 17                | Standard                    |
| K474     | 5       | Copper              | 50 - 240                        | 35 - 150                             | 2            | 17                | Standard                    |
| K471     | 3       | Aluminium           | 7 - 95                          | 35 - 150                             | 1            | 13                | Standard                    |
| K473     | 4       | Aluminium           | 7 - 120                         | 25 - 95                              | 1            | 17                | Standard                    |
| K475     | 5       | Aluminium           | 35 - 240                        | 50 - 150                             | 2            | 17                | Standard                    |
| K235     | 6       | Copper              | 7 - 95                          | 6 - 35                               | 1            | 13                | Two Stage*                  |
| K436     | 6       | Aluminium           | 7 - 95                          | 6 - 35                               | 1            | 13                | Two Stage*                  |

**Installations Notes:** 2 bolt IPC connectors must be tightened alternately to apply uniform pressure until shear head is operated. Implementation can be carried out on live-line but without load on the tap conductor.

**Important:** Two stage IPC's, are able to be installed whilst conductor is under load, up to max of 100A.




Fig. 3

Fig. 4

Fig. 5

Fig. 6



# LOW VOLTAGE FITTINGS



## INSULATION PIERCING CONNECTORS



K394

Fig. 1

This I.P.C (Insulation Piercing Connector) is used to establish a tap connection of 2 insulated conductors to a low voltage ABC (Aerial Bundled Conductors). When the main conductor connection is preformed by insulation piercing, the connection of the tap is preformed either by insulation piercing.

### Insulated cable to multiple insulated cables (Aluminium or Copper)

| Part No. | Fig No. | Cable Range<br>1 mm <sup>2</sup> | Cable Range<br>2 mm <sup>2</sup> | No. of<br>Taps | No. of<br>Bolts | Shear Head<br>A/F mm |
|----------|---------|----------------------------------|----------------------------------|----------------|-----------------|----------------------|
| K394     | 1       | 16 - 96                          | 6 - 35                           | 2              | 1               | 13                   |
| K389     | 1       | 35 - 150                         | 6 - 35                           | 2              | 1               | 13                   |



K363

Fig. 2

This I.P.C (Insulation Piercing Connector) is used for short-circuiting or earthing of low voltage ABC (Aerial Bundled Conductors) networks. It also enables voltage measurements.

### Insulated cables (Aluminium or Copper) - Short circuiting - Test

| Part No. | Fig No. | Cable Range 2 mm <sup>2</sup> | No. of Bolts | Shear Head A/F mm |
|----------|---------|-------------------------------|--------------|-------------------|
| K362     | 1       | 16 - 25                       | 1            | 13                |
| K363     | 2       | 16 - 70                       | 1            | 13                |
| K364     | 2       | 16 - 150                      | 1            | 13                |

# LOW VOLTAGE FITTINGS



## FLEXIBLE END CAPS

Flexible water and UV resistant end caps to fit the end of ABC conductors.



K01



K02



K03



K247

### Flexible End Caps

| Part No. | Length mm <sup>2</sup> | Cable Entry Diameter mm | Application Range mm <sup>2</sup>     |
|----------|------------------------|-------------------------|---------------------------------------|
| K01      | 32                     | 7                       | 10 - 50                               |
| K02      | 40                     | 10.5                    | 35 - 95                               |
| K03      | 50                     | 13                      | 95 - 150                              |
| K247     | 67.2                   | 31                      | Round: 50 - 150<br>Sectoral: 95 - 240 |

# LOW VOLTAGE FITTINGS



## HOUSE SERVICE CONNECTOR



K96BM

The new KBM is a fully overmoulded waterproof connection designed with solid internal chambers. It also includes a new shear cap indicator system. It is used to make electrical connection from an insulated supply cable to an insulated consumer cable.

### Features of K96BM are:

- Bi-metal corrosion resistance accepting both copper and aluminium cables.
- Completely overmoulded design.
- Multiple rib sealing system to ensure integrity of seal on all cable sizes - including fully ribbed ABC.
- Central solid barrier dividing each chamber.
- Fully insulated and water proof.
- Overmoulded shearhead bolt.
- Fits the existing main connection box (MCB).
- Consumers cable can be disconnected and reconnected.
- Tested to AS/NZS4396.
- Connectors is marked with cable sizes and strip requirements.
- Consumers and mains sides are clearly differentiated with markings and bolt colour.

| Part No. | Supply Cable Range mm <sup>2</sup> | Supply Connection Type | Supply Bolt Colour | Customer Cable Range mm <sup>2</sup> | Customer Connection Type | Customer Bolt Colour |
|----------|------------------------------------|------------------------|--------------------|--------------------------------------|--------------------------|----------------------|
| K96BM    | 6 - 35                             | Ins Piercing           | Black              | 4 - 35                               | Strip Cable              | White                |

## MAINS CONNECTION BOX (K SERIES)



K451

These products contain the 'K' Series range of house service connectors and provide an environmentally protective chamber in which to house and mount the connectors. It also provides protection of the consumers mains against UV degradation. The boxes come in single and three phase models with the K96BM.

### Features of K Series are:

- IP66D Rated.
- Suits easy entry of consumers mains through the rear of base.

| Part No. | Single Phase | Three Phase |
|----------|--------------|-------------|
| K451     | Y            | N           |
| K455     | N            | Y           |
| K458*    | Y            | N           |
| K459*    | N            | Y           |

\*Note: Empty boxes, no connectors.



K455

# LOW VOLTAGE FITTINGS



## BARE MAINS TO SERVICE CONNECTORS (R SERIES)



R235

This range of product provides for XPLE or PVC copper or aluminium service cable connection to bare copper and bare aluminium mains in a complete moisture free environment. The service connection is made with insulation piercing technology where there is no need to strip the cable.

### Features R Series are:

- Copper connector has forged body for added strength.
- All tested to applicable requirements of AS/NZS4396.
- Both mains and tap bolts incorporate shearhead technology for use with a standard M8 socket.
- Polycarbonate windows employed on all tap facilities to ensure the operator can see the actual connection.
- Connectors can be disconnected and reconnected from the mains with ease.




R235-4

### Insulated cable to multiple insulated cables (Aluminium or Copper)

| Part No. | Material Type | Bare Mains Range | Area mm <sup>2</sup> | O.D. mm | Tap Range mm <sup>2</sup> | Pack Qty. |
|----------|---------------|------------------|----------------------|---------|---------------------------|-----------|
| R235     | Copper        | 7/1.00 - 19/3.00 | 5.5 - 135            | 3 - 15  | 6 - 35                    | 10        |
| R235-4   | Copper        | 7/1.00 - 19/3.00 | 5.5 - 135            | 3 - 15  | 6 - 35                    | 10        |
| R236     | Aluminium     | 7/1.75 - 19/3.75 | 16 - 210             | 5 - 19  | 6 - 35                    | 10        |
| R236-4   | Aluminium     | 7/1.75 - 19/3.75 | 16 - 210             | 5 - 19  | 6 - 35                    | 10        |



R236



R236-4

# LOW VOLTAGE FITTINGS



## PRE-INSULATED COMPRESSION SLEEVES



K101

Fig. 1



K30

Fig. 2

Pre-Insulated sleeves are used to make an electrical joint, between two aerial bundle insulated conductors. The products are supplied for full tension or non tension applications.

### Features of K101 are:

- Totally insulated and water proof.
- Colour coded to applicable cable size.
- Labelled with cable size, die size, strip length, compression locations.
- Permanently engraved with traceability data.

### Full Tension Sleeves

| Part No. | Fig No. | Cable Size<br>mm <sup>2</sup> | Diameter<br>mm <sup>2</sup> | Length of<br>Sleeve | Die Part<br>No. | End Cap<br>Colour |
|----------|---------|-------------------------------|-----------------------------|---------------------|-----------------|-------------------|
| K101     | 1       | 16                            | 20                          | 104                 | 17.3            | Blue              |
| K103     | 1       | 25                            | 20                          | 104                 | 17.3            | Orange            |
| K106     | 1       | 35                            | 20                          | 104                 | 17.3            | Red               |
| K110     | 1       | 50                            | 20                          | 104                 | 17.3            | Yellow            |
| K170     | 1       | 95                            | 25                          | 137                 | 21.5            | Grey              |
| K185     | 1       | 150                           | 25                          | 178                 | 21.5            | Violet            |

**Note:** Sleeves to connect cables of differing sizes are also available.

### Non Tension Sleeves

| Part No. | Fig No. | Cable Size 1<br>mm <sup>2</sup> | Cable Size 2<br>mm <sup>2</sup> | Diameter<br>mm | Length of<br>Sleeve | Die Size<br>mm |
|----------|---------|---------------------------------|---------------------------------|----------------|---------------------|----------------|
| K30      | 2       | 6                               | 6                               | 16             | 71                  | 14             |
| K31      | 2       | 6                               | 10                              | 16             | 71                  | 14             |
| K32      | 2       | 6                               | 16                              | 16             | 71                  | 14             |
| K33      | 2       | 6                               | 25                              | 16             | 71                  | 14             |
| K35      | 2       | 10                              | 10                              | 16             | 71                  | 14             |
| K36      | 2       | 10                              | 16                              | 16             | 71                  | 14             |
| K37      | 2       | 10                              | 25                              | 16             | 71                  | 14             |
| K39      | 2       | 16                              | 16                              | 16             | 71                  | 14             |
| K40      | 2       | 16                              | 25                              | 16             | 71                  | 14             |
| K53      | 2       | 16                              | 35                              | 16             | 71                  | 14             |
| K42      | 2       | 25                              | 25                              | 16             | 71                  | 14             |
| K54      | 2       | 25                              | 35                              | 16             | 71                  | 14             |
| K55      | 2       | 35                              | 35                              | 16             | 71                  | 14             |

# LOW VOLTAGE FITTINGS



## PRE-INSULATED COMPRESSION LUGS



K159

Fig. 1

Pre-Insulated lugs are used to terminate aerial bundle insulated conductors, onto switchgear, busbars or isolators. The products are available in bi-metallic form.

### Features of K159 are:

- Totally Insulated and water proof.
- Colour coded to applicable cable size.
- Labelled with cable size, die size, strip length, compression locations.
- Permanently engraved with traceability data.

### Bi-Metallic - Aluminium Body - Copper Palm

| Part No. | Fig No. | Cable Size mm <sup>2</sup> | Diameter mm <sup>2</sup> | Length of Sleeve | Palm Size mm | Hole Diameter mm | Die Part No. | Die Size mm | End Cap Colour |
|----------|---------|----------------------------|--------------------------|------------------|--------------|------------------|--------------|-------------|----------------|
| K159     | 1       | 16                         | 16                       | 73               | ø20          | 10.3             | 111-140173AL | 14.0        | Blue           |
| K160     | 1       | 25                         | 16                       | 73               | ø20          | 10.3             | 111-140173AL | 14.0        | Orange         |
| K163     | 1       | 35                         | 20                       | 93               | ø25          | 12.8             | 111-140173AL | 17.3        | Red            |
| K164     | 1       | 50                         | 20                       | 93               | ø25          | 12.8             | 111-140173AL | 17.3        | Yellow         |
| K167     | 1       | 95                         | 20                       | 93               | ø25          | 12.8             | 111-140173AL | 17.3        | Grey           |
| K158     | 1       | 150                        | 25                       | 112              | ø30          | 12.8             | 111-215AL    | 21.5        | Violet         |

## MAIN STRAIN CLAMPS




IBT25095

Strain clamps are available for both mains and service aerial bundled cables, capable of clamping from 1 to 4 cores. If uneven number of cores are clamped, use filler cables in other locations.

### Features of Mains Strain Clamps are:

- Glass reinforced uv stabilised clamping blocks.
- High strength aluminium alloy tensions straps.
- Conforms to requirements of AS3766.
- All hardware is stainless steel - lubricated to eliminate binding.
- Jaws sprung loaded to facilitate easy insertion of cores.

| Part No. | Number of Cores | Cable Range mm <sup>2</sup> |
|----------|-----------------|-----------------------------|
| IBT25095 | 2               | 50 - 95                     |
| IBT5095  | 4               | 50 - 95                     |
| IBT95150 | 4               | 50 - 150                    |



IBT5095

# LOW VOLTAGE FITTINGS



## SERVICE CLAMPS



BCST



BCST

BCST Series are a bolted type service strain and suspension clamp.

**Features of BCST are:**

- Glass reinforced nylon clamping block.
- Blocks are spring loaded for ease of cable insertion.
- Available in galvanised steel or glass reinforced nylon straps.
- Available in open hook or closed eye.
- M10 stainless steel fasteners.
- UV stabilised.

| Part No.       | Conductor Construction mm <sup>2</sup> | Length mm | Standard Pack Quantity |
|----------------|--|-----------|------------------------|
| BCST-2025-3G   | 2 x (10 - 35)                          | 170       | 50                     |
| BCST-2025-3GA  | 2 x (10 - 35)                          | 170       | 50                     |
| BCST-2025-3P   | 2 x (10 - 35)                          | 170       | 50                     |
| BCST-2025-3PA  | 2 x (10 - 35)                          | 170       | 50                     |
| BCST-2025-3GLS | 2 x (10 - 35)                          | 250       | 35                     |
| BCST-2025-3GAL | 2 x (10 - 35)                          | 250       | 50                     |
| BCST-2025-3GL  | 2 x (10 - 35)                          | 250       | 30                     |
| BCST-4035-3G   | 4 x (10 - 35)                          | 170       | 30                     |
| BCST-4035-3GA  | 4 x (10 - 35)                          | 170       | 30                     |
| BCST-4035-3P   | 4 x (10 - 35)                          | 170       | 30                     |
| BCST-4035-3PA  | 4 x (10 - 35)                          | 170       | 30                     |
| BCST-4035-3GLS | 4 x (10 - 35)                          | 250       | 25                     |
| BCST-4035-3GAL | 4 x (10 - 35)                          | 250       | 30                     |
| BCST-4035-3GL  | 4 x (10 - 35)                          | 250       | 20                     |

**Note:**

- G** = Galvanised Strap
- GA** = Galvanised Strap (closed eye)
- GLS** = Galvanised Latching Strap (long)
- GL** = Galvanised Strap (long)
- GAL** = Galvanised Strap (closed eye) long
- P** = Glass-Filled Nylon Strap
- PA** = Glass-Filled Nylon Strap (closed eye)

## SERVICE CLAMPS



IBST435-2

Wedge type strain clamp with sliding jaws. Manufactured from UV stabilised glass reinforced nylon and a stainless steel strap. Designed for 2,3 and 4 core ABC twisted cables.

**Features of IBS are:**

- Stainless steel bail arm - detachable.
- Conforms to requirements of AS3766.
- Wedge action created by sliding jaws.
- No loose components, jaws attached body.

| Part No.  | Number of Cores | Range of Cable mm <sup>2</sup> | Hook or Eye | Min. Failing Load |
|-----------|-----------------|--------------------------------|-------------|-------------------|
| IBST435-2 | 2 up to 4       | 4 - 35                         | detachable  | 2.5kN             |

# LOW VOLTAGE FITTINGS



## SUSPENSION CLAMP (ASSERIES) FOR AERIAL- BUNDLED CONDUCTORS



BCSC

The AS series of LV ABC Suspension Clamps are intended for use on straight runs and for line deviation angles up to 25°. These suspension clamps are suitable for coastal environments and are manufactured from high strength corrosion-resistant aluminium alloy, incorporating neoprene bushes and stainless steel hardware. An optional failure link is built into the fitting.

The clamps are designed as a one-piece format, eliminating the problems of dropping components whilst installing the clamp. The AS suspension clamp greatly assists linesmen by supporting the cable in the open position, and allowing fast installation by simply closing the clamp and tightening the fastener.

### Features of BCSC are:

- Corrosion resistant cast aluminium body.
- Suitable for coastal and highly polluted environment.
- Neoprene bushes.
- Stainless steel hardware.
- Fast and simple installation.
- Optional failure link feature.
- Tested to Australian Standard 3766.

| Part No.       | Conductor Construction mm <sup>2</sup> | Standard Pack Quantity |
|----------------|--|------------------------|
| BCSC-2050-2S   | 2 x 50                                 | 63                     |
| BCSC-2050-2SWL | 2 x 50                                 | 63                     |
| BCSC-2050-2SHD | 2 x 50                                 | 64                     |
| BCSC-2095-2S   | 2 x 95                                 | 63                     |
| BCSC-2095-2SWL | 2 x 95                                 | 63                     |
| BCSC-2095-2SHD | 2 x 95                                 | 64                     |
| BCSC-4050-2S   | 4 x 50                                 | 64                     |
| BCSC-4050-2SWL | 4 x 50                                 | 64                     |
| BCSC-4050-2SHD | 4 x 50                                 | 64                     |
| BCSC-4095-2S   | 4 x 95                                 | 64                     |
| BCSC-4095-2SWL | 4 x 95                                 | 64                     |
| BCSC-4095-2SHD | 4 x 95                                 | 64                     |

### Note:

WL = Weak Link (5kN)

HD = Heavy Duty (stainless wear ring)

## SUSPENSION CLAMP



IBSC425

### Features of IBSC are:

- EPDM UV stabilised rubber insert.
- Galvanised body - with captive bolt slot.
- Galvanised steel hardware - oversize wing nut.
- Suitable for line deviation up to 30 degrees.
- Conforms to requirements of AS3766.

| Part No. | 2 Core mm <sup>2</sup> | 3 Core mm <sup>2</sup> | 4 Core mm <sup>2</sup> |
|----------|------------------------|------------------------|------------------------|
| IBSC425  |                        |                        | 25                     |
| IBSC435  | 50                     | 50                     | 35                     |
| IBSC450  |                        |                        | 50                     |
| IBSC470  | 95                     |                        | 70                     |
| IBSC495  |                        |                        | 95                     |



# LOW VOLTAGE FITTINGS



## SUSPENSION CLAMP (ASV SERIES) FOR AERIAL- BUNDLED CONDUCTORS



The ASV series of LV ABC Suspension clamps have been developed to protect the integrity of the cable insulation by controlling the cable slip during impact loads. The built-in failure link allows the undamaged cable to drop to the ground, thus providing a coordinated failure mechanism. The clamps are intended for use on straight runs and line deviation angles up to 25°.

The installation features of the clamps have been designed following extensive field trials carried out in conjunction with the major electricity distribution authorities.

The ASV series suspension clamps are suited for coastal environments and are manufactured from high strength corrosion-resistant aluminium alloy and incorporate neoprene bushes and stainless steel hardware. A failure link is built into the clamp.

The clamps are designed as a one-piece format, eliminating the common problem of dropping components whilst installing the clamp. The ASV series Suspension Clamp greatly assist linesmen by supporting the cable in the open position and allowing fast installation by simply closing the clamp and tightening the fastener.

### Features of BCSC are:

- Corrosion - resistant cast aluminium alloy body.
- Neoprene bushes.
- Stainless steel hardware.
- Fast and simple installation.
- Built-in failure link for greater system protection.
- Eliminate cable damage during major impacts on the line.
- The PLP AS series suspension clamp complies with Australian Standard 3766.

| Part No.       | Conductor Construction mm <sup>2</sup> | Weak Link Faling Load kN | Standard Pack Quantity |
|----------------|--|--------------------------|------------------------|
| BCSC-4095-3S   | 4 x 95                                 | 6                        | 64                     |
| BCSC-4095-3SHD | 4 x 95                                 | N/A                      | 30                     |
| BCSC-4150-3S   | 4 x 150                                | 8                        | 30                     |
| BCSC-4150-3SHD | 4 x 150                                | N/A                      | 30                     |
| BCSC-4150-3H   | 4 x 150                                | N/A                      | 30                     |

### Note:

**HD** = Heavy Duty (stainless wear ring)

**H** = Heavy Duty (no wear ring)

# LOW VOLTAGE FITTINGS

## SUSPENSION CLAMPS AND INTEGRATED STRINGING ROLLER




IBSRC495

### Features of IBSRC are:

- Type IBSRC.
- Cast aluminium body.
- Conforms to requirements of AS3766.
- Integrated stringing roller design.
- UV Stabilised split elastomer bush.
- Controlled release of conductor.

| Part No. | 2 Core mm <sup>2</sup> | 3 Core mm <sup>2</sup> | 4 Core mm <sup>2</sup> |
|----------|------------------------|------------------------|------------------------|
| IBSRC250 | 50                     |                        |                        |
| IBSRC450 | 95                     |                        | 50                     |
| IBSRC495 |                        |                        | 95                     |



String Roller - IBSRA with IBSRC installed.

| Part No.  | Description                                       |
|-----------|---|
| IBSRA     | Auxiliary stringing roller 50 - 95mm <sup>2</sup> |
| BSRA-4150 | Auxiliary stringing roller 150mm <sup>2</sup>     |

# LOW VOLTAGE FITTINGS



## FACADE MOUNTING BRACKETS (CABLE SADDLE)




BRPF1

### Features of BRPF are:

- Made from UV stabilised glass reinforced polymer.
- Brackets include 6mm drive nail.
- Cables can be supported on bracket during installation.

| Part No. | Drill Size mm | Offset from Structure | Installs Into | Cable Capacity mm  |
|----------|---------------|-----------------------|---------------|--------------------|
| BRPF1    | 12            | 10                    | Masonry       | 2 x $\phi$ 25 - 56 |
| BRPF1T   | None          | 10                    | Timber        | 2 x $\phi$ 25 - 56 |
| BRPF6    | 12            | 60                    | Masonry       | 2 x $\phi$ 25 - 56 |



BRPF6

# LOW VOLTAGE FITTINGS



## SAFETY SERVICE DISCONNECTOR (SSD)



SSD

Designed with safety in mind, Preformed Line Products Safety service disconnect ensures controlled disconnection of service under dynamic impact loading. The product severs the conductor after a high impact load, ensuring the span falling to ground is in an un-energised state.

The energised cable remains at the pole attachment point, insulated and well away from the general public. The PLP safety service disconnect can be installed on existing services with no interruption to the consumers power supply.

| Part No.     | Conductor Size mm <sup>2</sup> |
|--------------|--------------------------------|
| SSD-2X25AL19 | 2 x 25mm AL XLPE               |



### FULLY INSULATED BODY

The PLP SSD™ is manufactured from UV stabilised and fibre reinforced nylon which provides the fitting with complete insulating and mechanically strong features.

### ALL COMPONENTS

All components are held captive within the body so there are no loose parts to fall to ground when installing or upon activation.

### ONLY ACTIVATES ON IMPACT ABOVE A SPECIFIED LOAD

The PLP SSD™ will only activate if a load is applied of approximately 1.9 kN. The SSD™ will not activate simply due to an increase of tension to the cable such as possum walking along the service. Accurate and reliable failure is guaranteed by the shear pin being specifically sized to the failure load.

### CAN BE INSTALLED WITHIN 5 MINUTES

Due to the simple nature of the design of the product, it is easily installed within 5 minutes. Simply place the cable into the clamp and push it into the slots along the body, tighten the nuts on the bolted clamp till secure and bring the bridle around, clip it onto the bollard and snap the cover in place. Installation is now complete! No special equipment is required.

### NO NEED TO DISCONNECT CUSTOMER'S SUPPLY

To install the PLP SSD™, there is no need to disconnect the customer's supply because the conductor is not severed to install plugs or sockets. Therefore, the installation of the SSD™ can be done at any time, night or day, without having to advise customers - there is no disruption at all!

### NO POSSIBILITY OF SERVICE FAILURE DUE TO POOR CONTACT

There are no active electrical components within the SSD™ (such as contacts) which eliminates the possibility of an electrical breakdown or hot joints.

For application procedures, visit the PLP website.  
[www.preformed.com.au](http://www.preformed.com.au)

# LOW VOLTAGE FITTINGS



## FUSED SWITCH DISCONNECTS (POLE FUSE)



K490 (K491)

Fused Switch Disconnects is a single-phase device that is installed on a pole or on a wall. It provides electrical protection to an individual customer. It is designed to receive maximum 100A 22 x 58 size fuse cartridge or neutral tube. It is bi-metallic suiting aluminium or copper insulated cables 6-35mm<sup>2</sup>.

### Features of K490 (K491) and K291 are:

- Accepts 100A barrel type fuse: 58 x 22mm.
- Pig tail type extraction - type **FEHBX**.
- UV stabilised body - fully waterproof seals.
- Torque controlled shear head screws.
- Insulation piercing on all cable sizes and types.
- K291 application range: 6 - 95mm<sup>2</sup> - copper or aluminum.
- K491 application range: 6 - 35mm<sup>2</sup> - copper or aluminum.
- Facility to be gang mounted.
- Self supported whilst being mounted.
- Cable entry ports designed to eliminate moisture ingress.



K291

| Part No. | Description                                | Standard Pack Quantity |
|----------|--|------------------------|
| K490     | 1 Phase FSD 100A G2 + House Number         | 20                     |
| K491     | 1 Phase FSD 100A G2 (Without House Number) | 20                     |
| K492     | Number Plate for FSD K 491 / Cable         | 50                     |
| K291     | Single Phase FSD 100A (Size 22 x 58)       | 1                      |

## ACCESSORIES



K295

**K295** - This adaptor is designed to fix the FSD on bracket type "swan neck". It can also be fixed using a stainless steel strap or 2 screw.

FSDSNAB

**FSDSNAB** - Mounting Bracket, Glass reinforced UV stabilised mounting bracket for K490 / K491 screw mounting option or swan neck adaptor.

# LOW VOLTAGE FITTINGS



## FUSED SWITCH DISCONNECTS (POLE FUSE)




K292

### Features of K292 are:

- 160A Size 00 din fuse links or 250a solid link.
- Hinged fuse carrier, extraction via hot stick - type LOS3.
- UV stabilised body - fully water proof seals.
- Torque controlled shear head screws.
- Insulation piercing on all cable sizes and types.
- Large application range: 6 - 95mm<sup>2</sup> - Copper or Aluminum.
- Facility to be gang mounted.
- Self supported whilst being mounted.
- Angled cable entry ports to eliminate moisture ingress.

| Part No. | Number of Fittings in Assy | Fuse Rating | Fuse Type | Shear Head A/F mm |
|----------|----------------------------|-------------|-----------|-------------------|
| K292     | N/A                        | 160 / 250   | DIN00     | 13                |

## GANG MOUNTED K292



K292GANG

Triple pole FSD

### Gang FSD to suit 160A

| Part No.  | Number of Fittings in Assy | Fuse Rating | Fuse Type | Shear Head A/F mm |
|-----------|----------------------------|-------------|-----------|-------------------|
| K292GANG  | 3                          | 160 / 250   | DIN00     | 13                |
| K292GANG4 | 4                          | 160 / 250   | DIN00     | 13                |

# LOW VOLTAGE FITTINGS



## FUSED SWITCH DISCONNECTS



### Type - NHP Features

- UV stabilised glass reinforced body.
- Double circlip retention of fuse.
- Comes with integral attachment bracket - pattern B.
- Extraction pigtail tool - type - FEHBX.

| Part No. | Cable Range mm <sup>2</sup> | Fuse Rating                        | Fuse Type   |
|----------|-----------------------------|------------------------------------|-------------|
| NHP100AD | 6 - 35                      | 100                                | HRC 58 x 12 |
| IPSNG    |                             | Swan Neck Bracket Pattern B        |             |
| COMBHOOK |                             | Combination Bracket Pattern B      |             |
| PIGTAIL  |                             | Combination Loop Bracket Pattern B |             |



## IN LINE OVERHEAD OR PILLAR FUSE



This sleeve is designed to use a 22 x 58mm AD fuse cartridge or neutral tube. It is used without mechanical load. Mechanical tightening terminals allow implementation in the ABC (Aerial Bundled Conductors) using a simple spanner. Opening and closing of the sleeve can be performed under a load of 63A maximum.

### Features of K221 are:

- Connection is established by insulation piercing technology. Tightening is ensured by shear head screw.
- Terminals suit 6 - 35mm<sup>2</sup> Al/Cu or 16M-50M Al cables.
- Dielectric strength in water is over 6kV.
- Spring holding the fuse cartridge is designed to leave it on the customer side when opening the sleeve (without voltage).
- Seal cap allows to temporary protect access in the network side.
- When the cartridge is implemented, the sleeve the sleeve can be locked by using the sealing ring.

| Part No. | Designation                         | Standard Pack Quantity |
|----------|-------------------------------------|------------------------|
| K221     | Aerial Cutout Sleeve 22 x 58 / 100A | 10                     |

# LOW VOLTAGE FITTINGS



## FUSE SWITCH CONNECTOR (INDEPENDENT TIGHTENING)



K210

### Features of K210 are:

- Insulated piercing of the main line and the tap line is independently carried out.
- Tightening efficiency is ensured by shear head screws.
- Dielectric strength in water is over 6kV.
- Spring holding the fuse cartridge is designed to leave it on the customer side when opening the cutout (without voltage).
- When the cartridge is implemented, the cutout can be locked by using the closing ring.
- 100 Amp fuse capacity with 22 x 58mm barrel type fuse.

### Type Fuse Switch Connector 100A / 6-35mm<sup>2</sup>

| Part No. | Designation             | Main Line mm <sup>2</sup> | Tap Line Insulated Al-Cu mm <sup>2</sup> | Pack Qty. |
|----------|-------------------------|---------------------------|--|-----------|
| K210     | Fuse connector piercing | Insulated Al/Cu 35 - 150  | 6 - 35                                   | 10        |

## FUSE SWITCH CONNECTOR



K223

This fuse is designed to use a 10.3 x 38mm size fuse cartridge or neutral tube. It provides electric protection to insulated service or street light conductors connected to a low voltage ABC (Aerial Bundled Conductors). Maximum rating is 20A.

### Type Fuse Switch Connector 20A / 1.5 - 16mm<sup>2</sup>

| Part No. | Designation                              | Main Line mm <sup>2</sup>  | Tap Line Insulated Al-Cu mm <sup>2</sup> | Pack Qty. |
|----------|--|----------------------------|--|-----------|
| K223     | Fuse connector piercing<br>20A / 95 - 10 | Insulated Al/Cu<br>16 - 95 | 1.5 - 10                                 | 10        |
| K224     | Fuse connector piercing<br>20A / 95 - 16 | Insulated Al/Cu<br>16 - 95 | 6 - 16                                   | 10        |
| K228     | Fuse connector bare<br>20A/Cu 95 - 10    | Bare Cu<br>16 - 95         | 1.5 - 10                                 | 10        |
| K229     | Fuse connector bare 20A/Al<br>95-10      | Bare Al 16-95              | 1.5 - 10                                 | 10        |



K224

K228

K229



# LOW VOLTAGE FITTINGS



## PITT FUSED UNDERGROUND (FSD)



K199


These fully waterproof, insulated connectors are suitable for installation in a pit and enable underground services to be connected quickly and safely by one person using a ratchet spanner. The connectors have been rigorously tested and avoid the need for stripping, compression tooling or heat shrinking.

### Features of K199 are:

- Terminals incorporate insulation piercing technology.
- Simple, quick, fail safe three step installation.
- Terminals accept a wide range of cables from 6 - 50mm<sup>2</sup>.
- The K199 terminal has 2 cable entry points to suit phase connections and 100AMP fuse capacity with a 22 x 58 barrel type.
- The tapered flexible cable seal enables the connector to remain waterproof, even when cables are not in straight alignment with the connector.
- Terminals suit XLPE and PVC insulated single core and multi-core cables.
- Reusable - up to three times with copper cable.
- Connector is able to be separated with the fuse remaining in the dead side.
- Plug provided to cap live side after connector is separated.

| Part No. | Designation                            | Range mm <sup>2</sup> | Standard Pack Quantity |
|----------|--|-----------------------|------------------------|
| K199     | Fuse Insulation Piercing Pit Connector | 6 - 50                | 10                     |

## RING CONNECTOR



K459IPC

The 4 poles ring connector is used to establish 1 or 2 service tap connections from a low voltage underground network.

### Features of K459IPC are:

- Contact is preformed simultaneously with the insulation piercing technology on main and tap sides.
- Earthing device is available as an option
- Connectors is composed of:
  - 2 identical IP2X bipolar tightening parts enabling a non-oriented setting and a symmetric tightening from top.
  - 1 wedge to lock both parts of the connector on the cable.
- Body is made of synthetic materials to ensure safety work under voltage.
- Ergonomics design to meet the particular constraints of the underground work.
- Tightening efficiency is achieved by shear heads screws.
- Underground box and resin kit available on request.

| Part No. | Designation                                | Main Line mm <sup>2</sup> | Tap Line Insulated Al-Cu mm <sup>2</sup> | Pack Qty. |
|----------|--|---------------------------|--|-----------|
| K459     | 4 Poles Service Connector (ring connector) | 50 - 240                  | 2 x 10 - 50                              | 8         |



# ABC

# HIGH VOLTAGE FITTINGS

## PAGE

### HIGH VOLTAGE FITTINGS

|   |    |
|---|----|
| STRAIN ASSEMBLY AND BUNDLED RESTRAINT . . . | 28 |
| HELICAL LINE SPLICE . . . . .               | 29 |
| COMPRESSION MIDSPAN JOINT. . . . .          | 29 |
| SUSPENSION CLAMP. . . . .                   | 30 |
| POLE SUPPORT CLAMP. . . . .                 | 31 |
| YOKE BAR FOR ABC SUSPENSION . . . . .       | 31 |
| M16 GALVANISED HOOK BOLTS . . . . .         | 32 |
| STRING ROLLER (TYPE LSR23379) . . . . .     | 32 |
| POLE BRACKET . . . . .                      | 33 |

**“ Comprehensive Range of High Voltage ABC Fittings ”**




# HIGH VOLTAGE FITTINGS




## STRAIN ASSEMBLY AND BUNDLE RESTRAINT

To secure HVABC conductors at strain or tension points, you must utilise two types of fittings to secure both the catenary, as well as the ABC bundle itself. The Catenary is secured at a strain point using a standard PLP Helical catenary dead-end of applicable size and type - refer table below.



| Part No.  | HVABC Cable Type AS3599.1 or .2 | HVABC Cable Size mm <sup>2</sup> | Catenary Stranding | Catenary Material | Colour Code |
|-----------|---------------------------------|----------------------------------|--------------------|-------------------|-------------|
| GFG-060   | Metallic Screened               | 35                               | 7/2.00             | Gal Steel         | Yellow      |
| GFG-100   | Metallic Screened               | 35 - 185                         | 19/2.00            | Gal Steel         | Yellow      |
| AFG-136CL | Non Metallic Screened           | 35 - 95                          | 7/5.00             | Alum Alloy        | Blue        |
| AFG-175CL | Non Metallic Screened           | 120 - 185                        | 19/3.65            | Alum Alloy        | Black       |

The HVABC bundle assembly, must be secured to the catenary so it does not drift into the middle of the span. This eliminates bird caging, or spreading of the cores. PLP have developed a Helical bundle restraint for this purpose, which is simple to apply and is designed to avoid damage to the phase cores. The assembly is comprised of two Helical dead-ends, which interlock, to tie the catenary to the bundle. The dead-end used to retain the catenary, is designed to be applied over the catenary dead end as above.




| Part No. | HVABC Cable Type AS3599.2 | 11kV Cable mm <sup>2</sup> | 22kV Cable mm <sup>2</sup> |
|----------|---------------------------|----------------------------|----------------------------|
| IBHR1450 | Non Metallic Screened     | 35 - 50                    |                            |
| IBHR1455 | Non Metallic Screened     | 70                         | 35                         |
| IBHR1460 | Non Metallic Screened     | 95                         | 50                         |
| IBHR1465 | Non Metallic Screened     | 120 - 185                  | 70 - 95                    |
| IBHR1765 | Non Metallic Screened     | 120 - 150                  |                            |
| IBHR1770 | Non Metallic Screened     | 185                        |                            |
| IBHR1775 | Non Metallic Screened     |                            | 120 - 150                  |
| IBHR1780 | Non Metallic Screened     |                            | 185                        |

# HIGH VOLTAGE FITTINGS




## HELICAL LINE SPLICE



At locations where joints of the catenary on HVABC cables are required, a Helical line splice or a compression midspan joint can be used. For details of Joints for connecting conductor cores, please refer to the cable accessories CD, and the available range of Raychem medium voltage joints and heat shrink sleeving, together with the Utilux catalogue for details of applicable compression connectors.

| Part No. | HVABC Cable Type<br>AS3599.1 or .2 | Catenary Stranding | Catenary Diameter<br>mm | Catenary Material | 11kV mm <sup>2</sup> or 22kV |
|----------|------------------------------------|--------------------|-------------------------|-------------------|------------------------------|
| GFS-060  | Metallic Screened                  | 7/2.00             | 6.0                     | Gal Steel         | 35                           |
| GFS-100  | Metallic Screened                  | 19/2.00            | 10.0                    | Gal Steel         | 35 - 185                     |
| AFS-143  | Non Metallic Screened              | 7/5.00 Compacted   | 14.3                    | Alum Alloy        | 35 - 95                      |
| AFS-175  | Non Metallic Screened              | 19/3.65 Compacted  | 17.5                    | Alum Alloy        | 120 - 185                    |

## COMPRESSION MIDSPAN JOINT



| Part No. | HVABC Cable Type<br>AS3599.1 or .2 | Catenary Stranding | Catenary Diameter<br>mm | Catenary Material | 11kV mm <sup>2</sup> or 22kV |
|----------|------------------------------------|--------------------|-------------------------|-------------------|------------------------------|
| HM804    | Metallic Screened                  | 7/2.00             | 6.0                     | Gal Steel         | 35                           |
| HM808    | Metallic Screened                  | 19/2.00            | 10.0                    | Gal Steel         | 35 - 185                     |
| HM750    | Non Metallic Screened              | 7/5.00 Compacted   | 14.3                    | Alum Alloy        | 35 - 95                      |
| HM751    | Non Metallic Screened              | 19/3.65 Compacted  | 17.5                    | Alum Alloy        | 120 - 185                    |

# HIGH VOLTAGE FITTINGS



## SUSPENSION CLAMP



The **HVABC** suspension clamp is suitable for use on metallic and non-metallic screened **HVABC** cables, for voltages up to 22kV. It is designed to accommodate line deviations up to 45 degrees. It can be used at both intermediate suspension locations, as well as a secondary means of securing a bundle to the catenary at strain locations. If used in this manner, an **IBHR** bundle restraint, as per the preceding page, is not required.

Incorporates UV stabilised semi-conductive elastomeric insert, aluminium alloy strap, high strength cast aluminium clamp, and stainless steel hardware. Design of clamps, allows for a minimum of lifting of conductor during installation. Minimum failing load of clamp - 40kN.



| Part No. | HVABC Cable Type<br>AS3599.2 | Catenary<br>Diameter mm | 11kV Cable<br>mm <sup>2</sup> | 22kV Cable<br>mm <sup>2</sup> |
|----------|------------------------------|-------------------------|-------------------------------|-------------------------------|
| IBSH1050 | Metallic Screened            | 6 - 10                  | 35                            |                               |
| IBSH1055 | Metallic Screened            | 6 - 10                  | 50                            |                               |
| IBSH1060 | Metallic Screened            | 6 - 10                  | 70                            | 35                            |
| IBSH1065 | Metallic Screened            | 6 - 10                  | 95 - 120                      | 50                            |
| IBSH1070 | Metallic Screened            | 6 - 10                  | 150                           | 70 - 95                       |
| IBSH1075 | Metallic Screened            | 6 - 10                  | 185                           | 120                           |
| IBSH1080 | Metallic Screened            | 6 - 10                  |                               | 150                           |
| IBSH1085 | Metallic Screened            | 6 - 10                  |                               | 185                           |
| IBSH1840 | Non Metallic Screened        | 14 - 18                 | 35 - 50                       |                               |
| IBSH1845 | Non Metallic Screened        | 14 - 18                 | 70                            |                               |
| IBSH1850 | Non Metallic Screened        | 14 - 18                 | 95 - 120                      | 35 - 50                       |
| IBSH1855 | Non Metallic Screened        | 14 - 18                 | 150                           | 70                            |
| IBSH1860 | Non Metallic Screened        | 14 - 18                 | 185                           | 95 - 120                      |
| IBSH1865 | Non Metallic Screened        | 14 - 18                 |                               | 150                           |
| IBSH1870 | Non Metallic Screened        | 14 - 18                 |                               | 185                           |

# HIGH VOLTAGE FITTINGS



## POLE SUPPORT CLAMP



BCHVPC

Used for supporting HVABC conductor bundle down the pole.

### Features of BCHVPC are:

- Stainless M12 fasteners.
- Slot to allow banding to pole or structure.

| Part No.      | Bundle Diameter mm | Mounting Hole Diameter mm | Standard Pack Quantity |
|---------------|--------------------|---------------------------|------------------------|
| BCHVPC-035-3  | 35                 | 5.5                       | 35                     |
| BCHVPC-040-3  | 40                 | 5.5                       | 35                     |
| BCHVPC-050-3  | 45 - 50            | 5.5                       | 35                     |
| BCHVPC-050-3A | 45 - 50            | 12                        | 35                     |
| BCHVPC-060-3  | 55 - 60            | 5.5                       | 35                     |
| BCHVPC-060-3A | 55 - 60            | 12                        | 35                     |
| BCHVPC-070-3  | 65 - 70            | 5.5                       | 35                     |
| BCHVPC-070-3A | 65 - 70            | 12                        | 35                     |

## YOKE BAR FOR ABC SUSPENSION



YABCOF

This double suspension yoke bar provides up to 60° line deviation by using two suspension clamps of 30° each.

| Part No.   | Diameter mm | Length - Hook to hook mm | Standard Pack Quantity |
|------------|-------------|--------------------------|------------------------|
| YABCOF-150 | 16          | 150                      | 25                     |
| YABCOF-300 | 16          | 300                      | 25                     |
| YABCOF-410 | 20          | 410                      | 1                      |

# HIGH VOLTAGE FITTINGS



## M16 GALVANISED HOOK BOLTS



Made of galvanised steel for use with either wood or concrete poles. Straight hook.

| Part No.    | Length mm | Threaded Length mm | Bolt Size mm |
|-------------|-----------|--------------------|--------------|
| GEB-16150-T | 150       | 150                | 16           |
| GEB-16250-T | 250       | 250                | 16           |
| GEB-16350-T | 350       | 350                | 16           |
| GEB-16450-T | 450       | 450                | 16           |


**Note:** Other lengths available on request.

## STRING ROLLER (TYPE LSR23379)

The **LSR23379** stringing roller is a versatile, lightweight and safe product. It is suitable for use on line deviations up to 45 degrees, and accommodates **HVABC** cables up to 185mm<sup>2</sup> - 22kV.

The deep profile design of the rollers, ensure conductors do not stick or jam during stringing, and the frame design ensures that the conductor is guided and retained at all times. Its wide entry design allows for easy application of suspension clamps, and plenty of working space. Its mounting on support hooks allows for vertical height adjustment, which eliminates the dangerous practice of lifting conductors to secure in suspension clamps. With a weight of just 9kg, it is safe for one person to handle.

The standard assembly is used in conjunction with support hooks and associated brackets at suspension clamp locations, but with the addition of the **Yoke Assembly - LSR23857**, it can also be attached to a hook bolt or bracket at the start of a stringing run, where a suspension point is not required. This allows for the cable to be temporarily supported at termination or strain points, until tensile loads are applied and strain clamps fitted.





# HIGH VOLTAGE FITTINGS



## POLE BRACKET



SB10312



HB16200


The two most widely used Pole Brackets are - **SB10312** and **IBHPBV**. These items are manufactured from galvanised steel and can be either bolted or strapped to either concrete or timber poles.

Both brackets incorporate a cylindrical mounting tube, complete with 3 hook mounting holes, which are used for two purposes.

- The middle hole is used to locate and mount a suspension clamp.
- The outer two holes (each side) are used to locate and mount a string roller assembly - Product No **LSR23379**, and to adjust its height whilst stringing.

Both the suspension clamp and stringing roller are attached to the tube, using support hooks - product No **HB16200**. These hooks are manufactured from galvanised steel, have a minimum failing load of 12kN and are supplied with washers and nuts. The two outer hooks that locate the stringing roller, are used to adjust its mounted height for stringing. This adjustment allows the rollers to be located at a height that eliminates any necessity to lift either the conductor bundle or catenary for attachment into the suspension clamp.

The **SB10312** bracket is generally utilised at a point below the top of the pole, whereas the **IBHPBV** is generally installed at the pole top. The **IBHPBV** bracket has the facility to mount an insulator on its top surface to support a bare conductor during retrofit work, so as customer outages are minimised.





# ABC

# COVERED CONDUCTOR FITTINGS

PAGE

|   |    |
|---|----|
| <b>COVERED CONDUCTOR FITTINGS (CCT)</b>                                 |    |
| STRAIN CLAMPS AND COVERS (CCT) . . . . .                                | 36 |
| UNCOVERED STRAIN CONNECTIONS (CCT). . . . .                             | 36 |
| COMPRESSION JOINTS AND COVERS (CCT) . . . . .                           | 36 |
| NON METALLIC HELICAL TOP AND<br>SIDE TIES (CCT) . . . . .               | 37 |
| INSULATOR TOP CLAMPS (CCT) . . . . .                                    | 37 |
| PARALLEL GROOVE CLAMPS FOR LINE<br>TAPS AND NON TENSION JOINTS. . . . . | 38 |
| WORKING EARTH POINT COVERS . . . . .                                    | 38 |
| INSULATION PIERCING CONNECTOR<br>(LIGHTING PROTECTION) . . . . .        | 39 |
| MOUNTING BRACKET INSULATORS. . . . .                                    | 39 |
| CABLE STRIPPING TOOLS. . . . .  | 40 |
| STRINGING ROLLER ASSEMBLIES. . . . .                                    | 40 |

“ Comprehensive Range of CCT  
Covered Fittings ”



# COVERED CONDUCTOR FITTING (CCT)



## STRAIN CLAMPS AND COVERS (CCT)




CCS

To secure CCT conductors at strain or tension points, the most common method is utilising a rack driven wedge assembly. The clamp incorporates a clevis attachment point, and stringing eye, as well as a clamping bar, to lock the conductor in position once tensioned. The contoured design, eliminates stresses on the conductor as it exits the clamp. The UV Stabilised cover, completes the assembly, and makes the strain assembly fully covered. The cover assembly has been designed for assembly over standard insulators. The assembly is suitable for use on conductors voltages from 11kV up to 33kV.

| Part No. | Cover Part No. | Cable Size mm <sup>2</sup> | Cable Stranding |
|----------|----------------|----------------------------|-----------------|
| CCS80    | CCC80120       | 80                         | 7/3.75          |
| CCS120   | CCC80120       | 120                        | 7/4.75          |
| CCS180M  | CCC80120       | 180                        | 19/3.50         |

## UNCOVERED STRAIN CONNECTIONS (CCT)



CCT DEAD-END

In areas where a fully covered system is not required ( for example at termination points where tree proximity is not an issue ), an aluminium Helical Dead-end may be used, over the conductor insulation, to eliminate the need for stripping the conductor. This system is utilised on 11kV networks only.

| Part No.   | Cable Size mm <sup>2</sup> | Cable Outer Diameter mm |
|------------|----------------------------|-------------------------|
| AFG-188-CL | 80                         | 17.9 - 19.4             |
| AFG-210-CL | 120                        | 20.9 - 22.4             |
| AFG-238-CL | 180                        | 24.1 - 25.7             |

## COMPRESSION JOINTS AND COVERS (CCT)



CCT


At locations where CCT conductors must be joined midspan, a series of compression joint kits are available. All kits are supplied complete with Raychem heatshrink mastic lined sleeves, to ensure the joint area is both insulated and sealed. This added sealing slows the onset of corrosion, and decreases resistance in the joint, resulting for otherwise unprotected rapid oxidation of the connection. Compression joints are suitable for all voltages of CCT - 11kV up to 33kV, and are compatible with the material of the conductor.

| Part No. | Cable Size mm <sup>2</sup> | Cable Stranding |
|----------|----------------------------|-----------------|
| HM704CCT | 80                         | 7/3.75          |
| HM704CCT | 120                        | 7/4.75          |
| HM718CCT | 180                        | 19/3.50         |

# COVERED CONDUCTOR FITTING (CCT)




## NON METALLIC HELICAL TOP AND SIDE TIES (CCT)



At suspension locations, whether they be at pin or post type insulators, a series of non-metallic Top and Side ties are available. The ties are installed over the insulation of the conductor, and therefore stripping is not required.

Ties are manufactured from UV Stabilised PVC, and are available for 76mm Insulator neck size. Ties may be supplied in a colour to suit the conductor insulation. Standard colour is Grey. Ties are easily applied by hand, as with other Helical ties. Ties are suitable for angular deviations up to 30 degrees.

| Part No. (Side Ties Dead-end) | Cable Size mm <sup>2</sup> | Cable Outer Diameter mm |
|-------------------------------|----------------------------|-------------------------|
| PST14307G                     | 80                         | 11                      |
| PST18307G                     | 120                        | 11                      |
| PST23407G                     | 180                        | 11                      |




| Part No. (Top Tie) | Cable Size mm <sup>2</sup> | Cable Outer Diameter mm |
|--------------------|----------------------------|-------------------------|
| PTT14307G          | 80                         | 17.9 - 19.4             |
| PTT18307G          | 120                        | 20.9 - 22.4             |
| PTT23407G          | 180                        | 24.1 - 25.7             |

## INSULATOR TOP CLAMPS (CCT)



At suspension locations where stresses at the connection point, or line angle deviations do not allow for installation of plastic ties, a rigid clamp top can be installed to secure the conductor. The clamps are manufactured from aluminium alloy, and have an application range of 7mm up to 32mm. The clamp can be applied over the conductor insulation. Covers can be provided to protect the clamp from accidental contact.



| Part No. | Material Type | Minimum Conductor Diameter mm | Maximum Conductor Diameter mm |
|----------|---------------|-------------------------------|-------------------------------|
| Y11195   | Aluminium     | 7                             | 32                            |

# COVERED CONDUCTOR FITTING (CCT)



## PARALLEL GROOVE CLAMPS FOR LINE TAPS AND NON TENSION JOINTS

Parallel Groove clamps can be utilised in non tension applications as conductor joints, as well as line taps to either insulated or bare conductors. Both aluminium and bi-metallic are available, and both items can be covered using an applicable cover. All clamps are supplied complete with oxide inhibitor and Belleville spring washers, to control forces generated during electrical heat cycling.



| Part No. | Material Type         | CCT Cable Size mm <sup>2</sup> | Line Tap Cable Size mm <sup>2</sup> | Line Tap Cable Size mm | Suitable Cover Part No. |
|----------|-----------------------|--------------------------------|-------------------------------------|------------------------|-------------------------|
| 3594-FS  | Aluminium             | 80 up to 180                   | 35 - 240                            | 7.5 - 20.2             | CCPGC154                |
| 3913-FS  | Bi-Metallic           | 80 up to 180                   | 35 - 185                            | 7.5 - 17.5             | CCPGC154                |
| HDGW15   | Non Metallic Screened | 17.5                           | Alum/Alloy                          | 810                    | 58                      |

## WORKING EARTH POINT COVERS

Working earth point covers are designed to cover a stripped area of conductor which would be used as a local earthing location. The cover is manufactured from UV stabilised material, and is designed such that it can be opened, moved and reapplied using hot sticks. The cover can be easily trimmed to produce a next fit on all sizes of CCT at all voltages.



# COVERED CONDUCTOR FITTINGS (CCT)




## INSULATION PIERCING CONNECTOR (LIGHTNING PROTECTION)

For applications where Surge Arrestors are used for lightning protection, a connection from the arrester to the conductor can be made using an IPC. This connector **CCIPC11120 (11kV 80 / 120mm<sup>2</sup>)** utilises shear head bolts, which remain proud of the connector after shearing. An earth lead, with lug, can be attached to this additional length of bolt on the top of the connector. At the bottom of the connector a stirrup - type 25705F01 can also be attached as a means to attach a temporary earth.



## MOUNTING BRACKET INSULATORS


Brackets are available to mount insulators in either a trident (3 phases per bracket), or single phase format. All brackets are manufactured from galvanised steel. Brackets are not supplied with pole attachment hardware, due to the variety and type of mounting possibilities.



# COVERED CONDUCTOR FITTINGS (CCT)




## CABLE STRIPPING TOOLS



### Features of IBST are:

- Used for removal of core insulation.
- Removes insulation up to 5.5mm thick.
- Cable range from 12mm - 32mm.
- Long life blade.


## STRINGING ROLLER ASSEMBLIES



A unique stringing roller assembly has been designed to allow quick, safe and trouble free installation of all sizes of CCT conductors. The assembly has been designed for attachment to the CCB brackets.

### Features of LSR24570 are:

- Vertical height adjustment and lowering of cables - no lifting required.
- Movable top roller for easy insertion of conductors.
- Top roller locks in position, so as conductor cannot disengage whilst being strung.
- Lightweight design, able to be installed and removed by one person.
- Durable aluminium rollers with bearings.
- Suitable for stringing angles up to 30 degrees.
- Rollers can also be used to string LVABC up to 150mm<sup>2</sup>.
- LSRUNI is a stringing roller only. It does not include attaching bracket.





# ABC HARDWARE

“ Comprehensive Range of  
ABC Hardware ”

## PAGE

### HARDWARE

|                               |    |
|-------------------------------|----|
| MECHANICAL WEAK LINK .....    | 42 |
| EYE NUT .....                 | 42 |
| HOOK NUT .....                | 42 |
| HOOK BRACKET .....            | 43 |
| SERVICE SUPPORT BRACKET ..... | 43 |



# POLE HARDWARE



## MECHANICAL WEAK LINK



### Features of IBW are:

- Installed between suspension fitting on pole support fitting.
- Will withstand normal loading, but will fail under impact loads.
- Eliminates damage to suspension fitting and cables.

| Part No. | Diameter of Material | Total length | Material Type | Min Failing Load kN |
|----------|----------------------|--------------|---------------|---------------------|
| IBWL02   | 6                    | 81           | S/Steel       | 2                   |
| IBWL04   | 10                   | 100          | Gal/Steel     | 4                   |
| IBWL08   | 12                   | 100          | Gal/Steel     | 8                   |

## EYE NUT



### Features of ENG are:

- Screwed onto threaded device to produce eye attachment.

| Part No. | Thread size | Thread Length | Material Type | Diameter of Eye material |
|----------|-------------|---------------|---------------|--------------------------|
| ENG-16   | M16         | 30            | Gal/Steel     | 12                       |
| ENG-20   | M20         | 40            | Gal/Steel     | 20                       |
| EN2020   | M20         | 40            | Gal/Steel     | 20                       |
| ENG-24   | M24         | 45            | Gal/Steel     | 20                       |

## HOOK NUT



### Features of ENGO are:


- Screwed onto threaded device to produce hook attachment.

| Part No. | Thread size | Diameter of Eye material | Material Type | Failing Load kN |
|----------|-------------|--------------------------|---------------|-----------------|
| ENGO-16  | M16         | 16                       | Gal/Steel     | 12              |
| IBHN24   | M20         | 20                       | Gal/Steel     | 24              |

# POLE HARDWARE



## HOOK BRACKET



### Features of IBHB are:

- Designed for façade mounted strain clamps.
- Can be strapped to concrete poles with stainless steel strap.
- Used as temporary hook, for attachment of stringing rollers.


| Part No. | Mounting Centres | Diameter of Eye Material | Material Type | Failing Load kN |
|----------|------------------|--------------------------|---------------|-----------------|
| IBHB12   | 150              | 16                       | Gal/Steel     | 12              |
| IBHB24   | 150              | 20                       | Gal/Steel     | 24              |

## SERVICE SUPPORT BRACKET



### Features of IBSSB are:

- Used as a service strain clamp attachment point.
- Used in conjunction with hook bolts hook bolt or hook brackets.
- Galvanised Steel.





# ABC

# ASSEMBLY AND STRINGING TOOLS

|  | PAGE |
|--|------|
| <b>ASSEMBLY AND STRINGING TOOLS</b>                                      |      |
| CABLE STRIPPING TOOLS .....  | 46   |
| RUNNING SHEAVES .....  | 46   |
| CORE SEPARATING TOOLS .....  | 46   |
| RATCHET SPANNERS.....  | 47   |
| SWIVELS .....  | 47   |
| NYLON (LV CONDUCTORS) .....  | 47   |
| COME-ALONGS TENSIONING DEVICES.....                                      | 48   |
| COME-ALONG CLAMP (AS SERIES) .....                                       | 48   |
| CABLE STRIPPING TOOLS .....  | 48   |
| HEAVY DUTY STEEL CONSTRUCTION ALUMINIUM AND STEEL BASED CONDUCTORS ..... | 49   |
| NYLON (HV CONDUCTORS) .....  | 49   |
| J HOOK DRIVER .....  | 49   |

“ *Comprehensive ABC Assembly and Stringing Tools* ”



# ASSEMBLY AND STRINGING TOOLS



## CABLE STRIPPING TOOLS



The IBLST stripping tool, is designed to remove the tough cross linked polyethylene insulation from low voltage aerial cables. The length of insulation removed is able to be controlled to suit stripping for lugs and sleeves.

| Part No. | Cable Size mm <sup>2</sup> |
|----------|----------------------------|
| IBLST50  | 50                         |
| IBLST95  | 95                         |
| IBLST150 | 150                        |
| IBLSTB   | Spare blade                |

## RUNNING SHEAVES



### Features of 5930 are:

- Attaches to standard hardware, using socket tongue supplied.
- Accommodates cables up to 4 x 150mm<sup>2</sup>.
- Provides clear working space for linesmen.
- Suitable for stringing angles up to 60 degrees - SWL - 10.8kN.
- No lifting of cables required.

## CORE SEPARATING TOOLS

### Features of IBSW95 are:

- Suitable for LVABC.
- Supplied in pair - on metre of rope.
- Impact resistant material.

| Part No. | Cable Size mm <sup>2</sup>                 |
|----------|--|
| IBSW95   | up to 150mm <sup>2</sup>                   |
| K005     | up to 150mm <sup>2</sup>                   |
| K007     | 80 - 240mm <sup>2</sup> (round and sector) |



IBSW95

K005

K007

# ASSEMBLY AND STRINGING TOOLS



## RATCHET SPANNERS



IBLS6

### Features of IBLS are:

- Used on all overhead shear bolt connectors.
- 13mm and 17mm across flats in one spanner.
- Reversible ratchet.
- Fits stainless steel nuts used in strain and suspension clamps.
- Fixed socket that cannot be lost or dropped during installation.

| Part No.   | Size mm <sup>2</sup>               |
|------------|------------------------------------|
| IBLS-6     | over all length 190mm <sup>2</sup> |
| IBLS-6LONG | over all length 260mm <sup>2</sup> |

## SWIVELS



SWIVEL2

### Features of SWIVELS are:

- For use with pulling socks, to eliminate twist.

| Part No. | Length mm | Diameter mm | Maximum Cable Diameter mm | Safe Working Load kN |
|----------|-----------|-------------|---------------------------|----------------------|
| SWIVEL1  | 122       | 28.5        | 10.0                      | 1000                 |
| SWIVEL2  | 178       | 50.0        | 18.5                      | 2000                 |

## NYLON (LV CONDUCTORS)



CSN

Cable Stockings have many uses in the areas of construction, hauling and pulling. As the type of stocking design varies with each type of cable used, PLP can supply a range of stockings to meet your requirements.

| Part No. | Conductor Construction (mm <sup>2</sup> ) | Tension Rating (kN) | Length Total (mm) |
|----------|---|---------------------|-------------------|
| CSN-0225 | 2 x 25                                    | 15                  | 600               |
| CSN-0235 | 2 x 35                                    | 15                  | 600               |
| CSN-0250 | 2 x 50                                    | 15                  | 600               |
| CSN-0295 | 2 x 95                                    | 15                  | 600               |
| CSN-0335 | 3 x 35                                    | 15                  | 600               |
| CSN-0395 | 3 x 95                                    | 25                  | 600               |
| CSN-0425 | 4 x 25                                    | 15                  | 600               |
| CSN-0435 | 4 x 35                                    | 15                  | 600               |
| CSN-0450 | 4 x 50                                    | 15                  | 600               |
| CSN-0470 | 4 x 70                                    | 17                  | 800               |
| CSN-0495 | 4 x 95                                    | 25                  | 800               |
| CSN-4150 | 4 x 150                                   | 25                  | 800               |

# ASSEMBLY AND STRINGING TOOLS



## COME-ALONGS TENSIONING DEVICES



EM5095

### Features of EM and BCCA are:

- Rugged steel plated construction.
- Cast aluminium clamping jaws.

| Part No.      | Cable Application Range mm <sup>2</sup> | Holding Strength kN | Weight kg |
|---------------|---|---------------------|-----------|
| EM35          | 2 x 25 - 35 & 4 x 16 - 50               | 5.9                 | 3.2       |
| EM5095        | 4 x 50 - 95                             | 7.8                 | 5.8       |
| BCCA-495150-3 | 4 x 95 - 150                            | 9.0                 | 6.5       |

## COME-ALONG CLAMP (AS SERIES)



BCCA

The AS series come-along clamps are manufactured in Australia and are intended for use on LV ABC cables of 4 x 95 and 4 x 150mm<sup>2</sup> bundles.

Manufactured with aluminium clamping blocks, the AS series come-along clamps are designed to suit the maximum stringing tensions consistent with these cables.

### Features of BCCA are:

- Aluminium alloy, clamping block.
- Painted steel frame.
- Galvanised steel shackle.

| Part No.      | Conductor Size mm <sup>2</sup> |
|---------------|--------------------------------|
| BCCA-225495   | 2 x 25 - 4 x 95                |
| BCCA-495150-3 | 4 x (95 - 150)                 |

## CABLE STRIPPING TOOLS



IBST1342

### Features OF IBST1342 are:

**Two types of stripping tools are available for use on HVABC cables**

- Used for removal of semi conductive screen.
- Cut depth adjustable in 0.1mm increments.
- Spiral scoring function.
- Durable design.



# ASSEMBLY AND STRINGING TOOLS



HEAVY DUTY STEEL CONSTRUCTION  
ALUMINIUM AND STEEL BASED CONDUCTORS



CSS

| Part No.   | Conductor Diameter Range mm | Tension Rating kN | Length Total mm |
|------------|-----------------------------|-------------------|-----------------|
| CSS-0407HD | 4 - 7mm                     | 5                 | 300             |
| CSS-0611HD | 6 - 11mm                    | 8                 | 350             |
| CSS-1014HD | 10 - 14mm                   | 15                | 350             |
| CSS-1419HD | 14 - 19mm                   | 20                | 400             |
| CSS-1928HD | 19 - 28mm                   | 37                | 500             |
| CSS-2840HD | 28 - 40mm                   | 54                | 600             |
| CSS-4055HD | 40 - 55mm                   | 62                | 800             |

## NYLON (HV CONDUCTORS)



CSN

**Features of CSN are:**

- Mono-filament nylon.
- Double eye.
- Aluminium alloy ferrule.

| Part No.    | Conductor Construction mm <sup>2</sup> | Tension Rating kN | Length Total mm |
|-------------|--|-------------------|-----------------|
| CSN-0335-HV | 3 x 35                                 | 25                | 800             |
| CSN-0350-HV | 3 x 50                                 | 25                | 800             |
| CSN-0370-HV | 3 x 70                                 | 25                | 800             |
| CSN-0395-HV | 3 x 95                                 | 31                | 900             |
| CSN-3120-HV | 3 x 120                                | 31                | 900             |
| CSN-3150-HV | 3 x 150                                | 31                | 900             |
| CSN-3185-HV | 3 x 185                                | 31                | 900             |

## J HOOK DRIVER



TOOL HD-01

Designed with safety in mind, the new PLP J hook driver will make the installation of J hooks into timber poles quicker and easier than ever.

**Features of Tool-HD-01 are:**

- Spring loaded ball so the hook snaps into place with ease.
- Indication mark, showing the alignment of the hook.
- The conical shape allows the user to safely guide the hook.
- Suits 12mm J & Round eye screw hooks.



| Part No.   | Description   | Range                          |
|------------|---------------|--------------------------------|
| Tool-HD-01 | J Hook Driver | 12mm J & Round eye screw hooks |

# ALPHABETICAL INDEX

| Product Description  | Pg       |
|--|----------|
| Accessories  | 21       |
| Bare Mains to Service Connectors (R Series)                        | 12       |
| Cable Stripping Tools (CCT)  | 40       |
| Cable Stripping Tools (IBLST150)                                   | 46       |
| Cable Stripping Tools (IBST1342)                                   | 48       |
| Come-alongs Tensioning Devices                                     | 48       |
| Come-along Clamp (AS Series)                                       | 48       |
| Compression Joints and Covers (CCT)                                | 36       |
| Compression Midspan Joint  | 29       |
| Core Separating Tools  | 46       |
| Eye Nut  | 42       |
| Facade Mounting Brackets (Cable Saddle)                            | 19       |
| Flexible End Caps  | 10       |
| Fuse Switch Connector  | 24       |
| Fuse Switch Connector (Independent Tightening)                     | 24       |
| Fused Switch Disconnects   | 23       |
| Fused Switch Disconnects (Pole Fuse)                               | 21<br>22 |
| Gang Mounted   | 22       |
| Heavy Duty Steel Construction Aluminium and Steel Based Conductors | 49       |
| Helical Line Splice  | 29       |
| Hook Bracket   | 43       |
| Hook Nut   | 42       |
| House Service Connector  | 11       |
| In Line Overhead or Pillar Fuse                                    | 23       |
| Insulation Piercing Connector (Lightning Protection)               | 39       |
| Insulation Piercing Connectors                                     | 8<br>9   |
| Insulator Top Clamps (CCT)   | 37       |
| J Hook Driver  | 49       |
| M16 Galvanised Hook Bolts  | 31       |
| Main Strain Clamps   | 14       |
| Mains Connection Box (K Series)                                    | 11       |
| Mechanical Weak Link   | 42       |
| Mounting Bracket Insulators  | 39       |
| Non Metallic Helical Top and Side Ties (CCT)                       | 37       |
| Nylon (HV Conductors)  | 49       |
| Nylon (LV Conductors)  | 47       |
| Parallel Groove Clamps for Line Taps and Non Tension Joints        | 38       |
| Pitt Fused Underground (FSD)                                       | 25       |
| Pole Bracket   | 32       |
| Pole Support Clamp   | 30       |
| Pre-Insulated Compression Lugs                                     | 14       |
| Pre-Insulated Compression Sleeves                                  | 13       |
| Ratchet Spanners   | 47       |
| Ring Connector   | 25       |
| Running Sheaves  | 46       |
| Safety Service Disconnect (SSD)                                    | 20       |
| Service Clamps   | 15       |
| Service Support Bracket  | 43       |

| Product Description   | Pg |
|---|----|
| Strain Assembly and Bundle Restraint                        | 28 |
| Strain Clamps and Covers (CCT)                              | 36 |
| String Roller (Type LSR23379)                               | 32 |
| Stringing Roller Assemblies                                 | 40 |
| Suspension Clamp (AS Series) For Aerial-Bundled Conductors  | 16 |
| Suspension Clamp (ASV Series) For Aerial-Bundled Conductors | 17 |
| Suspension Clamp (HV)                                       | 30 |
| Suspension Clamp (LV)                                       | 16 |
| Suspension Clamps and Integrated Stringing Roller           | 18 |
| Swivels   | 47 |
| Uncovered Strain Connections (CCT)                          | 34 |
| Working Earth Point Covers                                  | 38 |
| Yoke Bar for ABC Suspension                                 | 31 |

# PART NO. INDEX

| Part No.       | Pg | Part No.      | Pg | Part No.   | Pg | Part No.  | Pg | Part No.     | Pg |
|----------------|----|---------------|----|------------|----|-----------|----|--------------|----|
| 3594-FS        | 38 | BCST-4035-3PA | 15 | GFS-100    | 29 | IBST435-2 | 15 | K39          | 13 |
| 3913-FS        | 38 | BRPF1         | 19 | HB16200    | 33 | IBST5024  | 40 | K42          | 13 |
| 25705F01       | 39 | BRPF1T        | 19 | HDGW15     | 38 | IBSW95    | 46 | K436         | 8  |
| AFG-136CL      | 26 | BRPF6         | 19 | HM704CCT   | 36 | IBT25095  | 14 | K440         | 8  |
| AFG-175CL      | 26 | CCB05         | 39 | HM704CCT   | 36 | IBT5095   | 14 | K441         | 8  |
| AFG-188-CL     | 36 | CCB45         | 39 | HM718CCT   | 36 | IBT95150  | 14 | K442         | 8  |
| AFG-210-CL     | 36 | CCIPC11120    | 39 | HM750      | 29 | IBWL02    | 42 | K443         | 8  |
| AFG-238-CL     | 36 | CCS120        | 36 | HM751      | 29 | IBWL04    | 42 | K445         | 8  |
| AFS-143        | 29 | CCS180M       | 36 | HM804      | 29 | IBWL08    | 42 | K446         | 8  |
| AFS-175        | 29 | CCS80         | 36 | HM808      | 29 | IPSNG     | 23 | K451         | 11 |
| BCCA-225495    | 48 | CCWEPC        | 38 | IBHB12     | 43 | K005      | 46 | K455         | 11 |
| BCCA-495150-3  | 48 | COMBHOOK      | 23 | IBHB24     | 43 | K007      | 46 | K458         | 11 |
| BCCA-495150-3  | 48 | CSN-0225      | 47 | IBHN24     | 42 | K01       | 10 | K459         | 11 |
| BCHVPC-035-3   | 31 | CSN-0235      | 47 | IBHR1450   | 26 | K02       | 10 | K459         | 25 |
| BCHVPC-040-3   | 31 | CSN-0250      | 47 | IBHR1455   | 26 | K03       | 10 | K470         | 8  |
| BCHVPC-050-3   | 31 | CSN-0295      | 47 | IBHR1460   | 26 | K101      | 13 | K471         | 8  |
| BCHVPC-050-3A  | 31 | CSN-0335      | 47 | IBHR1465   | 26 | K103      | 13 | K472         | 8  |
| BCHVPC-060-3   | 31 | CSN-0335-HV   | 49 | IBHR1765   | 26 | K106      | 13 | K473         | 8  |
| BCHVPC-060-3A  | 31 | CSN-0350-HV   | 49 | IBHR1770   | 26 | K110      | 13 | K474         | 8  |
| BCHVPC-070-3   | 31 | CSN-0370-HV   | 49 | IBHR1775   | 26 | K158      | 14 | K475         | 8  |
| BCHVPC-070-3A  | 31 | CSN-0395      | 47 | IBHR1780   | 26 | K159      | 14 | K490         | 21 |
| BCSC-2050-2S   | 16 | CSN-0395-HV   | 49 | IBLS-6LONG | 47 | K160      | 14 | K491         | 21 |
| BCSC-2050-2SHD | 16 | CSN-0425      | 47 | IBLS-6     | 47 | K163      | 14 | K492         | 21 |
| BCSC-2050-2SWL | 16 | CSN-0435      | 47 | IBLST150   | 46 | K164      | 14 | K53          | 13 |
| BCSC-2095-2S   | 16 | CSN-0450      | 47 | IBLST50    | 46 | K167      | 14 | K54          | 13 |
| BCSC-2095-2SHD | 16 | CSN-0470      | 47 | IBLST95    | 46 | K170      | 13 | K55          | 13 |
| BCSC-2095-2SWL | 16 | CSN-0495      | 47 | IBLSTB     | 46 | K185      | 13 | K96BM        | 11 |
| BCSC-4050-2S   | 16 | CSN-3120-HV   | 49 | IBSC425    | 16 | K199      | 25 | LSR23379     | 32 |
| BCSC-4050-2SHD | 16 | CSN-3150-HV   | 49 | IBSC435    | 16 | K210      | 24 | LSR24570     | 40 |
| BCSC-4050-2SWL | 16 | CSN-3185-HV   | 49 | IBSC450    | 16 | K221      | 23 | LSRUNI       | 40 |
| BCSC-4095-2S   | 16 | CSN-4150      | 47 | IBSC470    | 16 | K223      | 24 | NHP100AD     | 23 |
| BCSC-4095-2SHD | 16 | CSS-0407HD    | 48 | IBSC495    | 16 | K224      | 24 | PIGTAIL      | 23 |
| BCSC-4095-2SWL | 16 | CSS-0611HD    | 48 | IBSH1050   | 29 | K228      | 24 | PST14307G    | 37 |
| BCSC-4095-3S   | 17 | CSS-0611HD    | 48 | IBSH1055   | 29 | K229      | 24 | PST18307G    | 37 |
| BCSC-4095-3SHD | 17 | CSS-1014HD    | 48 | IBSH1060   | 29 | K235      | 8  | PST23407G    | 37 |
| BCSC-4150-3H   | 17 | CSS-1419HD    | 48 | IBSH1065   | 29 | K247      | 10 | PTT14307G    | 37 |
| BCSC-4150-3S   | 17 | CSS-1928HD    | 48 | IBSH1070   | 29 | K291      | 21 | PTT18307G    | 37 |
| BCSC-4150-3SHD | 17 | CSS-2840HD    | 48 | IBSH1075   | 29 | K292      | 22 | PTT23407G    | 37 |
| BCSRA-4150     | 18 | CSS-4055HD    | 48 | IBSH1080   | 29 | K292GANG  | 22 | R235         | 12 |
| BCST-2025-3G   | 15 | EM35          | 48 | IBSH1085   | 29 | K292GANG4 | 22 | R235-4       | 12 |
| BCST-2025-3GA  | 15 | EM5095        | 48 | IBSH1840   | 29 | K30       | 13 | R236         | 12 |
| BCST-2025-3GAL | 15 | EN2020        | 42 | IBSH1845   | 29 | K31       | 13 | R236-4       | 12 |
| BCST-2025-3GL  | 15 | ENG-16        | 42 | IBSH1850   | 29 | K32       | 13 | SB10312      | 33 |
| BCST-2025-3GLS | 15 | ENG-20        | 42 | IBSH1855   | 29 | K33       | 13 | SSD-2X25AL19 | 20 |
| BCST-2025-3P   | 15 | ENG-24        | 42 | IBSH1860   | 29 | K35       | 13 | SWIVELS      | 47 |
| BCST-2025-3PA  | 15 | ENGO-16       | 42 | IBSH1865   | 29 | K36       | 13 | TOOL-HD-01   | 49 |
| BCST-4035-3G   | 15 | FSDSNAB       | 21 | IBSH1870   | 29 | K362      | 9  | Y11195       | 37 |
| BCST-4035-3GA  | 15 | GEB-16150-T   | 32 | IBSRA      | 18 | K363      | 9  | YABCOF-150   | 31 |
| BCST-4035-3GAL | 15 | GEB-16250-T   | 32 | IBSRC250   | 18 | K364      | 9  | YABCOF-300   | 31 |
| BCST-4035-3GL  | 15 | GEB-16350-T   | 32 | IBSRC450   | 18 | K37       | 13 | YABCOF-410   | 31 |
| BCST-4035-3GLS | 15 | GEB-16450-T   | 32 | IBSRC495   | 18 | K389      | 9  |              |    |
| BCST-4035-3P   | 15 | GFS-060       | 29 |            |    |           |    |              |    |

---

## **TERMS & CONDITIONS OF SALE**

### **1. APPLICATION**

- 1.1. These Terms apply to all goods sold by the Company.
- 1.2. No amendment, alteration, waiver or cancellation of any of these Terms is binding on the Company unless confirmed by the Company in writing.
- 1.3. The Customer acknowledges that no employee or agent of the Company has any right to make any representation, warranty or promise in relation of the Goods or the sale of the Goods other than as contained in these Terms.

### **2. TERMS OF PAYMENT**

- 2.1. Prices are subject to change on thirty (30) days notice.
- 2.2. Payments are to be made direct to the Company, strictly net, without any deduction or discount other than as stated in these Terms or in the relevant invoice or statement.
- 2.3. Payments are to be made within thirty (30) days of the date of the Company's statement or invoice, whichever is the earlier.
- 2.4. Interest is payable on all overdue accounts calculated on a daily basis at the rate of 2% per month as from the due date for payment until payment is received by the Company.
- 2.5. The Company will charge a handling fee of \$100 or such other greater amount for orders of an invoice value under \$1,000 or such higher amount as the Company determines.

### **3. PROPERTY IN GOODS**

Legal and beneficial ownership of Goods supplied by the Company will not pass to the Customer until such time as the Goods so supplied have been paid in full in cash or cleared funds.

### **4. RE-SALE OF GOODS**

- 4.1. If the Customer is a re-seller then, subject to sub-clause 4.2.4, the Customer has the right to sell the Goods in its own name at full market value and in the ordinary course of business.
- 4.2. Until the amount payable to the Company in respect of the Goods has been paid in full in cash or cleared fund:
  - 4.2.1. the Customer will hold the Goods only as bailee for the Company;
  - 4.2.2. the Goods must be stored in such manner that they are readily distinguishable from other goods owned by the Customer or other persons and so as to clearly show that they are the property of the Company;
  - 4.2.3. the Customer must indemnify the Company from and against any Claim incurred or suffered by the Company arising out of the possession, use or disposal of the Goods by the Customer or repossession or attempted repossession of them by the Company; and
  - 4.2.4. any sale of the Goods under clause 4.1 will only be effected by the Customer as trustee for the Company and the proceeds of such sale and the rights of the Company's Customer against its customer arising from such sale will be held on trust for the Company. The said proceeds must be held in a separate account or otherwise clearly identified in the books and records of the Customer.
- 4.3. The Customer must ensure that the Goods are stored in accordance with any reasonable direction or instructions from the Company and, without the prior written consent of the Company, must not treat, alter, or incorporate the Goods into or with another product of the Company or any third party, or otherwise vary the Goods as supplied by the Company.

- 4.4. If the Customer resells any Goods then, unless the Goods are clearly identifiable by serial numbers or other distinguishing marks, the Customer is deemed to have disposed of the Goods in the chronological order of supply by the Company to the Customer (oldest to most recent).
- 4.5. On the resale of the Goods by the Customer, the Customer must ensure that any contract between the Customer and its customer limits or excludes any liability of the Company to such customer on no less favourable terms than the Company's liability to the Customer under clause 19 or on more limiting terms.
- 4.6. Despite clause 4.5, the Customer must indemnify the Company from and against any Claim incurred or suffered by the Company arising out of the resale of the Goods by the Customer.

## 5. INCORPORATION OF GOODS

- 5.1. If the Customer uses the Goods in some manufacturing or construction process of its own or on behalf of some third party and receives monies from time to time in respect of such use then the Customer must hold a portion of such monies received, calculated in accordance with clause 5.2, in trust for the Company.
- 5.2. The portion referred to in clause 5.1 will be so much of the monies received as equals the amount owing by the Customer to the Company at the time of the receipt of such monies by the Customer.
- 5.3. Money received by the Customer excludes any debts due to other parties by the customer but not yet paid by the Customer.
- 5.4. In the circumstances outlined in clause 5.1, the Customer must not assign or deal with its debts in any way prior to payment of the moneys receivable by the Customer in respect of the Goods as their use as described in clause 5.1 prior to their payment to the Company.

## 6. INSTALLATION OF GOODS

- 6.1. All Goods must be handled, mounted and installed:
  - 6.1.1. by an appropriately licensed technician/tradesman; and
  - 6.1.2. in accordance with:
    - 6.1.2.1. the manufacturer's directions, if any;
    - 6.1.2.2. the relevant Application Procedure found at [http://www.phhttp://www.preformed.com/index.php?option=com\\_phocadownload&view=category&id=29&Itemid=194refor med.com/index.php?option=com\\_phocadownload&view=category&id=29&Itemid=194;](http://www.phhttp://www.preformed.com/index.php?option=com_phocadownload&view=category&id=29&Itemid=194refor med.com/index.php?option=com_phocadownload&view=category&id=29&Itemid=194;) and/or
    - 6.1.2.3. the applicable industry standard, as the case may be.
- 6.2. If any Goods are not handled, mounted or installed in accordance with clause 6.1 then, subject to any statutory provision or other general law obligation to the contrary, the Company will not be liable for any defect or fault in the Goods or for any loss or damage to the Customer caused by the Goods.

## 7. DEFAULT

- If:**
- 7.1. the Goods are not paid for in accordance with these Terms or any other written agreement between the Company and the Customer;
  - 7.2. the Company receives notice of, or reasonably believes that a third party may attempt to levy execution against or attach the Goods; or
  - 7.3. any other event occurs which in the Company's opinion is likely to adversely affect the Customer's ability to pay for the Goods (including but not limited to the appointment of Insolvency Representative to the Customer's undertaking),

then the Company may at any time thereafter, without notice to the Customer and without prejudice to any other rights which it may have against the Customer, terminate any Contract relating to the Goods and the bailment referred to in clause 4.2.1.

## **8. RIGHT TO ENTER PREMISES**

In any of the circumstances referred to in clause 7, the Customer:

- 8.1. authorises the Company by itself, its agents or representatives at all reasonable times, without notice, to enter onto (with force if reasonably necessary) and at all necessary time(s), to remain in and on any premises where the Goods are located in order to collect the Goods, without being guilty of any manner of trespass; and
- 8.2. assigns to the Company all the Customer's rights to enter onto and remain in and on such premises until all the Goods have been collected.

## **9. ADMINISTRATION & RECEIVERSHIP**

In any of the circumstances referred to in clause 7.3:

- 9.1. neither the Customer nor its Insolvency Representative or any other person acting for the Customer and/or its creditors is entitled to sell, charge, remove, dispose of, use or otherwise deal with the Goods in any way inconsistent with the Company's ownership of the Goods, without the Company's prior written approval;
- 9.2. the Customer, its Insolvency Representative and every other person acting for or on behalf of the Customer and/or its creditors is obliged to re-deliver the Goods to the Company immediately or immediately on his appointment, as the case may be, at its or his expense; and
- 9.3. if the Goods are returned to or collected by the Company, the Company will within twenty-eight (28) days, account to the Customer or its Insolvency Representative for all monies received for the Goods from the Customer less the Company's reasonable administration charges, expenses incurred and loss of profits involved.

## **10. CUSTOMER AS TRUSTEE**

If the Customer carries on business as trustee of a trust then the Customer warrants that:

- 10.1. the Customer enters into a Contract or Contracts to purchase the Goods as trustee of a trust;
- 10.2. the Customer has all requisite powers to enter into a Contract under these Terms;
- 10.3. the beneficiary of the trust approves the purchase of the Goods on the terms of the Contract; and
- 10.4. the assets of the trust are available to the Company in satisfaction of any debt incurred by the Customer for the purchase of the Goods.

## **11. GOODS AND SERVICES TAX**

- 11.1. GST is not included in the quoted price.
- 11.2. If GST is imposed on the Company in respect of the Goods then the Customer must pay the amount of such GST to the Company in addition to the quoted price.
- 11.3. The Company must give the Customer written notice of the amount of any GST payable under this clause and provide a tax invoice showing the amount of GST payable.

## **12. CUSTOMS DUTIES, TARIFFS AND LEVIES**

All applicable customs duties, tariffs and levies are payable by the Customer unless the order, order confirmation, invoice or other writing indicates otherwise.

**13. DELIVERY**

- 13.1. Availability dates are estimates only, but the Company will use its best endeavours to maintain these estimates.
- 13.2. If the place of delivery to or collection of the Goods by the Customer is within Australia then the Company will, at the Customer's request, arrange for the delivery of the Goods at the Company's expense.

**14. DELIVERY BY INSTALMENTS**

- 14.1. The Company reserves the right to deliver the Goods in whole or by instalments as well as to deliver prior to the date for delivery and in any such event the Customer must not refuse to take delivery of the Goods.
- 14.2. Where the Goods are delivered by instalments, each instalment is sold under a separate Contract.
- 14.3. Any failure on the part of the Company to deliver instalments within any specified time does not entitle the Customer to repudiate the Contract with regard to the balance of the Goods remaining undelivered.

**15. RISK**

- 15.1. The Goods are entirely at the risk of the Customer from the moment the Goods leave the Company's premises or physical custody.
- 15.2. The Customer must at its own expense, maintain the Goods and insure them for the benefit of the Company for their full replacement value against theft, destructions, fire, water and other risks, as from the moment of delivery to or collection by the Customer until property of and title to the Goods have passed to the Customer.
- 15.3. The Customer must take all reasonable measures to ensure that the Company's title to the Goods is in no way prejudiced. If any of the Goods are lost, destroyed or damaged, any insurance proceeds relating to the Goods in respect of such event that are received by the Customer are held on trust for the Company and must be paid to the Company immediately on receipt but only up to the amount that the Customer owes the Company in respect of those Goods.

**16. INSPECTION**

Unless the Customer has inspected the Goods and given written notice to the Company within seven (7) days after collection or delivery that the Goods do not comply with the relevant specifications or descriptions, the Goods are deemed to have been accepted in good order and condition.

**17. RETURN OF GOODS**

- 17.1. No returns will be accepted unless the Company has previously agreed in writing. If the Company agrees to the return of Goods, they must be unsoiled, undamaged and in a resaleable condition (or Customer pays for all costs of replacement or repair) and delivered at the Customer's expense to the Company's premises unless otherwise agreed by the Company in writing.
- 17.2. Goods imported especially for the Customer or non-standard equipment made to special order cannot under any circumstances be returned and/or credited.

**18. CANCELLATION OF ORDER**

No order may be cancelled, modified or deferred without the prior written consent of the Company (which is at the Company's sole discretion) and if consent is given, then such consent will, at the Company's election, be subject to the Company being reimbursed all losses, including loss of profits, and paid a cancellation and restocking fee (being not less than 10% of the invoice value of the Goods).

**19. COMPANY'S LIABILITY LIMITED**

- 19.1. The Customer acknowledges and agrees that:
  - 19.1.1. the Customer has determined that the Goods are fit for the purpose for which the Customer requires them;
  - 19.1.2. the Customer has the right to inspect the Goods in accordance with clause 19 to satisfy itself that the Goods are fit for purpose and/or are of merchantable and acceptable quality;
  - 19.1.3. the Customer has not relied on the Company's skill and judgment in selecting the Goods; and
  - 19.1.4. the Company is not responsible if the Goods do not comply with any applicable safety standard(s) or similar regulation(s), and that the Company is not liable for any Claim resulting from such non-compliance.
- 19.2. The Company is not subject to, and the Customer releases the Company from any liability (including but not limited to Consequential Loss or Damage, removal costs or re-installation costs or liability for loss of use or profit) arising from any delay in delivery or defect or fault in the Goods or any negligence by the Company in relation to the Goods (including but not limited to their manufacture), to the full extent permitted by law.
- 19.3. If, despite clause 19.2, the statutory provisions under the *Competition and Consumer Act 2010* (Cth), the *Sale of Goods Act 1923* (NSW) or any other act or the general law impose on the Company a liability for a defect or fault in the Goods then, to the extent to which the Company is entitled to do so, the Company's liability under the statutory provisions is limited, at the Company's option, to:
  - 19.3.1. replacement or repair of the Goods;
  - 19.3.2. supply of equivalent Goods; or
  - 19.3.3. payment of the cost of replacing or repairing the Goods or of acquiring equivalent Goods,and in any case:
  - 19.3.4. the Company will not be liable for any Consequential Loss or Damage or any other loss or damage; and
  - 19.3.5. the Company's total liability to the Customer is limited to the invoice value of the Goods.

**20. WARRANTIES AND WARRANTY CLAIMS**

- 20.1. The Company warrants that the Goods are free of substantive defects.
- 20.2. The Company also warrants to the Customer that the Goods will be supplied in an undamaged condition.
- 20.3. Except for any guarantees imposed by the *Competition and Consumer Act 2010* (Cth) and the warranties stated in clauses 20.1 and 20.2, the provision of any other act or law implying terms, conditions, guarantees and/or warranties which might otherwise apply to or arise out of the Contract are hereby expressly negated and excluded to the full extent permitted by law.
- 20.4. On discovery of any defect in the Goods, the Customer must notify the Company in writing of such defect.
- 20.5. All warranty claims must be received by the Company within thirty (30) days of the day of delivery. This warranty extends only to the Customer and to no other person.
- 20.6. The Customer's failure to provide written notice to the Company within the required time of any alleged breach of the above warranty will release and discharge the Company from any obligation or liability for that breach of warranty.
- 20.7. The Customer must not carry out any remedial work to allegedly defective Goods without first obtaining the written consent of the Company to do so



otherwise all of the Company's warranties will be voided to the full extent permitted by law.

- 20.8. The warranties stated in clauses 20.1 and 20.2 do not apply in circumstances where the Customer treats, alters, incorporates the Goods into or with another product of the Company or any third party, or otherwise varies the Goods as supplied by the Company.

## **21. CATALOGUES**

Particulars in leaflets, catalogues, drawings, brochures and other printed material are illustrations only, form no part of the Contract between the Company and the Customer, and are not binding on the Company.

## **22. CUSTOMER'S PROPERTY**

- 22.1. All Customer's property in or under the Company's custody or control will be entirely at the Customer's risk in regard to loss or damage from any cause whatsoever.
- 22.2. The Company will have a first and paramount lien upon all Customer's property (including but not limited to dies provided by or manufactured for the Customer) which is in the Company's possession or control until all accounts due to the Company by the Customer are paid in full.
- 22.3. The Company may sell any of the Customer's property on which the Company has a lien if:
- 22.3.1. a sum in respect of which the lien exists is presently payable;
- 22.3.2. the Company has, not less than fourteen (14) days before the date of the sale, given the Customer a written notice setting out, and demanding payment of such part of the sum in respect of which the lien exists as is presently payable; and
- the Customer has failed to pay the sum referred to in the notice.
- 22.4. The proceeds of the sale will be applied by the Company:
- 22.4.1. firstly to cover the costs of the sale;
- 22.4.2. secondly in payment of such part of the sum in respect of which the lien exists as is presently payable; and
- 22.4.3. by way of accounting to the Customer.

## **23. TOOLING**

- 23.1. If the Company agrees to supply Tooling to the Customer then the Tooling remains the property of the Company and despite the fact that the Customer may have borne or contributed to the cost of the development and manufacture of the Tooling.
- 23.2. The Company reserves the right to recall the Tooling from the Customer at any time.

## **24. PERSONAL PROPERTY SECURITY**

- 24.1. The Customer acknowledges that if the Company has a security interest in:
- 24.1.1. the Goods;
- 24.1.2. the proceeds of the Goods;
- 24.1.3. the Customer's property referred to in clause 22.1; and/or
- 24.1.4. the Tooling,
- for the purposes of the PPSA then the Company may register its security interest in the Goods, proceeds, Customer's property and/or Tooling, as the case may be, on the PPSR.
- 24.2. The Customer undertakes, at its own expense, to promptly do anything (such as supplying information) which the Company requests and reasonably requires the Customer to do for the purposes of ensuring that the security interest is enforceable, perfected or otherwise effective.

- 24.3. The Customer acknowledges that if the Company has a security interest in the Goods, proceeds, Customer's property and/or Tooling, as the case may be, then the Company may register its security interest on the PPSR and the Customer, in accordance with section 157(3)(b) of the PPSA, waives the right to receive notification of the registration.

## **25. COPYRIGHT**

- 25.1. The Customer warrants that:
- 25.1.1. the drawing of any extruded shape submitted by the Customer; and
  - 25.1.2. any Tooling made in accordance with such drawing; and
  - 25.1.3. any article of extruded design made from such Tooling,
- does not infringe the rights of any third party (whether copyright, registered design pattern, trademark, confidential information or otherwise) or breach any applicable law.
- 25.2. In the event of any Claim or order for costs (including legal expenses on a solicitor and client basis) referable to the rights and/or laws referred to in clause 25.1 being made or brought against the Company, the Customer must fully indemnify the Company and keep the Company indemnified from and against same.

## **26. SAMPLES**

Any sample inspected by the Customer is solely for the Customer's convenience and does not constitute a sale by sample. All samples remain the property of the Company.

## **27. SPECIFICATIONS**

- 27.1. Unless otherwise agreed in writing, the Goods are supplied subject to any specification as to weight, quantity, size, dimensions, finishes, chemical composition and physical properties as may be published generally by the Company or as may be set out in any specification issued by the Company in relation to the Goods or, if no such specification has been published or set out, subject to such specification as is normally regarded as being commercially acceptable.
- 27.2. Where any specification for the Goods are to be supplied by the Customer, they must be supplied in a reasonable time to enable the Company to complete delivery by the date for delivery.

## **28. CONTRACT**

- 28.1. The terms of the Contract between the parties are wholly contained in these Terms and any other writing signed by both parties.
- 28.2. The Contract under these Terms is deemed to have been made at the Company's place of business in Sydney, New South Wales and any cause of action is deemed to have arisen there.
- 28.3. The Contract is governed by the law of New South Wales.
- 28.4. The Customer irrevocably and unconditionally submits to the non-exclusive jurisdiction of the courts of New South Wales and any courts which have jurisdiction to hear appeals from those courts about any proceedings in connection with these Terms and waives any right to object to proceedings being brought in those courts for any reason.
- 28.5. The provisions of the United Nations Convention on Contracts for the International Sale of Goods adopted at Vienna, Austria on 10 April 1980 does not apply to any Goods supplied by the Company to the Customer.

## **29. FORCE MAJEURE**

The Company will not be liable for any breach of contract due to any matter or thing beyond the Company's control (including but not limited to transport stoppages,

transport breakdown, fire, flood, earthquake, acts of God, strikes, lock-outs, work stoppages, wars, riots or civil commotion, intervention of public authority, explosion or accident).

### **30. DISPUTE RESOLUTION**

- 30.1. The Company and/or the Customer must not commence any court proceedings in respect of a dispute arising out of these Terms unless it has complied with this clause 30.
- 30.2. Should at any time a party assert that a dispute exists between the parties arising out of or in connection with these Terms, then that party must submit a written notice ("**Notice of Dispute**") to the other party specifying:
  - 30.2.1. the nature of the dispute that has arisen;
  - 30.2.2. the major issues for determination; and
  - 30.2.3. the relief or outcome being sought.
- 30.3. Within seven (7) days from receipt of the Notice of Dispute, the other party must provide a written response ("**Notice of Response**") stating its position in relation to the dispute, including:
  - 30.3.1. any additional issues that should be referred for determination; and
  - 30.3.2. any comment on the relief or outcome referred to in the Notice of Dispute.
- 30.4. During the fourteen (14) day period after the Notice of Response is issued, the parties must take reasonable steps to seek to resolve the dispute.
- 30.5. If the dispute is not resolved within the period referred to in clause 30.4 then the parties must, within an additional fourteen (14) days agree to refer the dispute to a single expert for determination.
- 30.6. If the parties are unable to agree on a expert within the time stipulated in clause 30.5, then either party may refer the dispute to an expert as nominated by Unisearch Expert Opinion Services, for determination.
- 30.7. The determination of the expert:
  - 30.7.1. must be in writing, accompanied by reasons; and
  - 30.7.2. will be final and binding on the parties as to any findings of fact relating to any matter arising from these Terms.
- 30.8. The parties are to bear their own costs of the dispute and the costs of the expert are to be borne by the party found to be at fault by the expert and, in the event that no such finding is made, the costs are to be borne by the parties equally.

### **31. WAIVER OF BREACH**

No failure by the Company to insist on strict performances of any of these Terms is a waiver of any right or remedy which the Company may have, and is not a waiver of any subsequent breach or default by the Customer.

### **32. NO ASSIGNMENT**

Neither the Contract nor any rights arising under the Contract may be assigned by the Customer without the prior written consent of the Company which is at the Company's absolute discretion.

### **33. SEVERABILITY**

If any provision contained in these Terms is held by a court to be unlawful, invalid or unenforceable, the validity and enforceability of the remaining provisions are not affected.

### **34. INTERPRETATION**

In these Terms:

- 34.1. "**Claim**" means a claim, action, suit, demand, proceeding, damage, loss, cost, expense or liability incurred or suffered by the Company.

- 
- 34.2. **“Company”** means Preformed Line Products (Australia) Pty Limited ABN 27 004 533 877 and its successors and assigns.
- 34.3. **“Consequential Loss or Damages”** means all or any of the following:
- 34.3.1. loss of profit;
  - 34.3.2. loss or denial of opportunity;
  - 34.3.3. loss of use;
  - 34.3.4. loss of revenue;
  - 34.3.5. loss of production;
  - 34.3.6. loss of labour;
  - 34.3.7. loss of access to markets;
  - 34.3.8. loss of goodwill;
  - 34.3.9. loss of anticipated savings;
  - 34.3.10. loss of business reputation including future reputation;
  - 34.3.11. loss arising from adverse publicity;
  - 34.3.12. damage to credit rating;
  - 34.3.13. removal costs;
  - 34.3.14. re-installation costs;
  - 34.3.15. commissioning costs;
  - 34.3.16. increase in operating costs;
  - 34.3.17. increase in maintenance costs;
  - 34.3.18. financial costs;
  - 34.3.19. any indirect, remote, abnormal or unforeseeable loss;
  - 34.3.20. any consequential loss or damage not included in the above; and
  - 34.3.21. any similar loss whether or not in the reasonable contemplation of the parties at the time entry into the Contract, and in any case whether arising out of contract or tort (including negligence) or by statute or otherwise, at law or in equity.
- 34.4. **“Contract”** means the contract for the sale of the Goods by the Company to the Customer.
- 34.5. **“Customer”** means the party to whom the Company has agreed to sell the Goods.
- 34.6. **“Goods”** means the goods agreed to be sold by the Company to the Customer.
- 34.7. **“GST”** means the Goods and Services Tax imposed by a *New Tax System (Goods and Services Tax) Act 1999* (Cth) and any related act and/or regulations.
- 34.8. **“Insolvency Representative”** includes but is not limited to a receiver, receiver and manager, administrator, controller, liquidator, provisional liquidator, trustee or similar person.
- 34.9. **“PPSA”** means the *Personal Property Securities Act 2009* (Cth).
- 34.10. **“PPSR”** means the personal property security register created under the PPSA.
- 34.11. **“Terms”** means these terms and conditions of sale as amended from time to time.
- 34.12. **“Tooling”** means any tooling supplied by the Company to the Customer from time to time.

**The Connection You Can Count On**



SCAN QR CODE  
TO DOWNLOAD THIS CATALOGUE



**INSULATED CONDUCTOR FITTINGS**  
FOR LOW & HIGH VOLTAGE ABC, CC & CCT  
CATALOGUE

SCAN QR CODE  
FOR OTHER PLP CATALOGUES



- ▣ Communications
- ▣ Distribution
- ▣ Insulator
- ▣ Substation
- ▣ Transformer
- ▣ Transmission