



PREFORMED LINE PRODUCTS
The connection you can count on.

INSULIGN™ Guy Strain Insulators Fiberglass



COMMUNICATIONS



ENERGY



SPECIAL INDUSTRIES



SOLAR



INSULIGN™





Clevis Roller application



Clevis to Thimble-Eye application

PLP® Distribution Products

INSULIGN™ Guy Strain Insulators – Fiberglass

Rated Strength: 16,000 lbs.

Description

The Preformed Line Products' INSULIGN Guy Strain Insulator series is intended for use with down guys or pole-to-pole guys on overhead lines. The insulative fiberglass rod electrically isolates the guy strand and provides electrical clearance for maintenance crews and the public during normal operation.

Features

Compared to porcelain strain-type insulators, PLP's fiberglass guy strain insulators provide a greater insulative distance which minimizes the potential and severity of dry and wet flashover. Fiberglass guy strain insulators provide a more durable solution compared to conventional porcelain insulators. INSULIGN Guy Strain Insulators utilize a proprietary veiled fiberglass rod that allows for superior performance when exposed to UV conditions.

- Veiled fiberglass rod provides superior UV protection
- Crimped end fittings are designed to assure consistent, high-performance holding strength
- Manufactured, tested, and verified to meet PLP's high-quality standards.



Rated Strength: 16,000 lbs.

INSULIGN GUY STRAIN INSULATORS – FIBERGLASS

Rod Length (in)	Fitting Combination: Clevis/Clevis with Roller	Fitting Combination: Clevis/Thimble-Eye	Fitting Combination: Clevis/Eye
	PLP Catalog Number		
12	GSF16-12CCR	GSF16-12CTE	GSF16-12CE
18	GSF16-18CCR	GSF16-18CTE	GSF16-18CE
24	GSF16-24CCR	GSF16-24CTE	GSF16-24CE
36	GSF16-36CCR	GSF16-36CTE	GSF16-36CE
42	GSF16-42CCR	GSF16-42CTE	GSF16-42CE
54	GSF16-54CCR	GSF16-54CTE	GSF16-54CE
78	GSF16-78CCR	GSF16-78CTE	GSF16-78CE
96	GSF16-96CCR	GSF16-96CTE	GSF16-96CE
120	GSF16-120CCR	GSF16-120CTE	GSF16-120CE
144	GSF16-144CCR	GSF16-144CTE	GSF16-144CE

Custom lengths available, contact PLP® for more information.



Global Headquarters
660 Beta Drive
Cleveland, Ohio 44143

Mailing Address:
P.O. Box 91129
Cleveland, Ohio 44101

Telephone: 440.461.5200
Fax: 440.442.8816
Website: preformed.com
Email: inquiries@preformed.com

© 2018 Preformed Line Products
Printed in U.S.A.
EN-SS-1238
04.18.IH