

**STAYWORK***PREFORMED™ Wrap Guy Link***Application**

The PREFORMED™ Wrap Guy Link is designed to terminate solid or stranded wire used for stays, catenaries/messengers etc. at pole top positions, when the wire or strand is wrapped around the pole.

Suitable for varying pole diameter and for both single and double wrapping, the PREFORMED™ Wrap Guy Link secures the tail to the body of the wire or strand.

The completed application should be inspected for two conditions:

- The Wrap Guy Link itself should be free from any contact with the pole. Only the wire or strand wrapped around the pole top should be in contact.
- The distance between the pole and the cross-over mark on the continued wire or strand should be approximately 1 1/2 pole diameters.

3-2-6/1

The 'J' type hook is an acceptable fitting for use with the PREFORMED™ Wrap Guy Link to retain wire or strand in position. Other types of fittings, with or without rubbing plates may be used, providing they permit secure attachment.

**Construction**

The PREFORMED™ Wrap Guy Link is always manufactured from a material compatible with the strand to which they are applied.

**Lay Direction**

The lay direction must be the same as that of the strand with which it is used.

**Product Referencing and Ordering**

Contact PLP (GB) Ltd with the following information:-

- Quantity
- Catalogue number
- Product name
- Strand: Material
  - Diameter
  - Rated breaking strength
  - Lay direction

**STAYWORK***PREFORMED™ Wrap Guy Link-Galvanised Steel*

CATALOGUE No.	STRAND DIAMETER mm		COLOUR CODE	'O' CLIP SIZE	LENGTH mm	APPROX WEIGHT KGS PER 100	RHS KGS
	MIN	MAX					
WGL1403601	4.83	5.02	RED	11.02	940	13	2167
WGL1403602	5.03	5.25	BLACK	11.02	965	13	2372
WGL1403603	5.26	5.48	WHITE	11.02	991	13	2581
WGL1403604	5.49	5.71	YELLOW	11.02	1016	13	2803
WGL1403605	5.72	5.98	GREEN	11.02	1067	17	3057
WGL1403606	5.99	6.21	BLUE	12.70	1118	18	3325
WGL1403607	6.22	6.47	BLACK	12.70	1143	18	3604
WGL1403608	6.48	6.66	WHITE	12.70	1245	27	3924
WGL1403609	6.67	7.03	YELLOW	12.70	1270	27	4255
WGL1403610	7.04	7.33	GREEN	12.70	1295	27	4631
WGL1403611	7.34	7.63	RED	14.27	1372	37	5026
WGL1403612	7.64	7.97	YELLOW	14.27	1422	39	5470
WGL1403613	7.98	8.30	BLACK	14.27	1473	40	5938
WGL1403614	8.31	8.60	ORANGE	15.87	1549	52	6382
WGL1403615	8.61	8.93	RED	15.87	1600	54	6881
WGL1403616	8.94	9.31	BLACK	15.87	1626	55	7484
WGL1403617	9.32	9.67	GREEN	15.87	1651	52	7802
WGL1403618	9.68	10.05	BLACK	15.87	1702	54	7802
WGL1403619	10.06	10.45	RED	15.87	1753	55	7802
WGL1403620	10.46	10.78	ORANGE	19.05	1880	74	9480
WGL1403621	10.79	11.14	GREEN	19.05	1905	75	9480
WGL1403622	11.15	11.50	BLUE	19.05	1956	77	9480
WGL1403623	11.51	11.83	BLACK	22.14	2032	97	11294
WGL1403624	11.84	12.18	RED	22.14	2083	100	11294
WGL1403625	12.19	12.55	ORANGE	22.14	2134	102	11294

3-2-6/2

For use on Galvanised Steel Strand.

