



PREFORMED LINE PRODUCTS
The connection you can count on.


PROTECTOR TUBING




 COMMUNICATIONS

 ENERGY

 SPECIAL INDUSTRIES

 SOLAR





PLP Distribution Products PROTECTOR TUBING

Description

Protector Tubing protects energized lines from faults due to contact caused by various types of wildlife. The durable EPDM tubing is a minimum of 113 mils thick with a dielectric strength of 500 V/mil and has excellent resistance to ozone and petroleum-based solvents.

Application

- Quick Installation
- Can be cut easily with a knife or wire cutters
- Accommodates wide range of conductors
- Ideal for transformer stinger wires and arrester connections to prevent the electrocution of birds of prey

Features

- Lightweight
- Unobtrusive Appearance
- Excellent resistance to ozone and petroleum based solvents
- Long service life without deterioration of material
- Tubing slit configuration permits easy installation on existing conductor
- Overlapping profile follows bends and turns in the conductor without risk of splitting open to expose energized wire
- New profile provides for large range of conductor sizes
- Not for protection of human contact



World Headquarters
660 Beta Drive
Cleveland, Ohio 44143

Mailing Address:
P.O. Box 91129
Cleveland, Ohio 44101

Telephone: 440.461.5200
Fax: 440.442.8816
Web Site: www.preformed.com
E-mail: inquiries@preformed.com

© 2016 Preformed Line Products
Printed in U.S.A.
EN-SS-1163
04.16.IH

| PROTECTOR TUBING | | | |
|--------------------|-----------------|-----------|-------------|
| PLP Catalog Number | Conductor Range | | Length (ft) |
| | Min. (in) | Max. (in) | L |
| PT-0375 | 0.162 | 0.375 | 8 |
| PT-0625 | 0.376 | 0.625 | 8 |
| PT-0938 | 0.626 | 0.938 | 8 |
| PT-1300 | 0.939 | 1.300 | 8 |

Available in continuous rolls. Contact PLP for more information