

FIBERLIGN® Repair Rods for OPGW

Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

Description

FIBERLIGN Repair Rods are designed as a single-component, outer layer assembly for use on OPGW and are intended for repair of the outer mechanical strand members on an OPGW cable. These Repair Rods will provide varying levels of mechanical and electrical repair depending upon the specific construction, stranding and material of the OPGW.

Features

- Left-hand lay standard. Contact PLP for right-hand lay designs.

Documentation

Application Procedures

[SP-2881 \(Fiberlign Repair Rods for OPGW\)](#)

Catalog Pages

[Fiberlign Repair Rods for OPGW - Catalog](#)

Part Tables

Repair Rods					
Catalog Number	Diameter Range (inch)	Diameter Range (mm)	Color Code	Length	
				in	M
3600100	.354-.385	8.9-9.7	Red	45	1.14
3600101	.386-.422	9.8-10.7	Black	48	1.22
3600102	.423-.460	10.8-11.6	Orange	50	1.27
3600103	.461-.505	11.7-12.8	Green	54	1.37
3600104	.506-.550	12.9-13.9	Blue	61	1.55
3600105	.551-.602	14.0-15.2	Yellow	65	1.65
3600106	.603-.660	15.3-16.7	Brown	70	1.78
3600107	.661-.719	16.8-18.2	Purple	74	1.88
3600108	.720-.785	18.3-19.9	Pink	80	2.03
3600109	.786-.850	20.0-21.5	Red	86	2.18
3600110	.851-.933	21.6-23.6	Black	94	2.39
3600111	.934-1.020	23.7-25.9	Orange	102	2.59

Left-hand lay standard