

FIBERLIGN® Dielectric Damper for ADSS Cable

Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

Description

A special damper, called the **FIBERLIGN Dielectric Damper**, has been developed specifically for application on ADSS cables. It utilizes the same dampening characteristics as the FIBERLIGN Spiral Vibration Damper, plus provides more gentle gripping.

Features

- Lightweight
- Installs by hand or hot stick

Documentation

Application Procedures

[SP-2130 \(FIBERLIGN® Dielectric Damper\)](#)

Catalog Pages

[FIBERLIGN® Dielectric Damper - Catalog](#)

Part Tables

FIBERLIGN Dielectric Damper for ADSS Cable

Catalog Number	Cable Diameter Range (inches)	Cable Diameter Range (mm)	Length inches (m)	Units (per carton)	Carton Weight (lbs.)
50502393	.250-.326	6.3-8.2	49 (1.24)	50	26
50502272	.327-.461	8.3-11.6	51 (1.30)	50	28
50502274	.462-.563	11.7-14.3	53 (1.35)	50	30
50509862	.564-.770	14.3-19.5	65 (1.65)	50	46
50503057	.771-.876	19.5-22.2	71 (1.80)	25	30
50503576	.877-1.00	22.3-25.3	72 (1.91)	25	35
50503909	1.001-1.25	25.4-30.5	75 (2.29)	25	40

Notes:

1. Consult Preformed Line Products for recommendations on the number of dampers required per span.