

FIBERLIGN® ADSS Midspan Drop

Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

Description

FIBERLIGN® ADSS Midspan Drop (FAMD) provides an attachment location for FTTH drop cables between utility poles anywhere along the span of an ADSS distribution feeder cable. In cases when local codes or obstructions prevent aerial connection directly from the utility pole to the home, the FMD is a convenient, economical solution that can avoid the cost of adding an intermediate pole or structure.

Features

- Attach to Backbone ADSS up to 1.007” (25.58 mm) diameter
- Perpendicular load up to 500 lbs (226.8 kg)
- Connect up to two Cable Drops
- Supports FIBERLIGN® Drop Cable Dead-ends
- Maximum Perpendicular Load 500#
- Easy installation - No Tools Required
- Compact size - Easy to Handle
- Includes three components: Structural Reinforcing rods (SRR), Midspan Connector, and PVC Round thimble.
- SRR's limit bending and protect the cable from extreme side loads.
- Midspan Connector provides a loop interface after applied to the SRR.
- The PVC thimble fits in the loop of the Midspan Connector and provides a curved surface to properly support interconnecting drop cable dead-end loops.

Documentation

Application Procedures

[SP-3001 \(FIBERLIGN ADSS Midspan Drop\)](#)

Catalog Pages

[FIBERLIGN ADSS Midspan Drop - Catalog](#)

Sales Materials

[FIBERLIGN ADSS Drop Cable DE & Midspan Drop - Sell Sheet](#)

Part Tables

ADSS Midspan Drop			
Catalog Number	Cable Range		Color Code
	Inches	mm	
3800005	.350-.399	8.9-10.1	White
3800006	.400-.450	10.2-11.4	Red
3800007	.451-.509	11.5-12.9	Black
3800008	.510-.575	13.0-14.6	Blue
3800009	.576-.649	14.7-16.5	Orange
3800010	.650-.730	16.6-18.5	Green
3800011	.731-.820	18.6-20.8	Brown
3800012	.821-.920	20.9-23.4	Yellow
3800013	.921-1.007	23.5-25.6	Purple

Overall Length = 27 inches, 685 mm.
Thimble Catalog Number 00070253