

FIBERLIGN® Lite Support for ADSS Drop Cables

Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

Description

The **FIBERLIGN Lite Support (FLS)** for ADSS Drop Cables is the perfect product for distribution of multiple drop cables in an FTTP system as each FLS can support two cables and the FLS has stackable housings. One 5/8" double arming bolt or through bolt can securely stack FLS units within the same pole space. This keeps cables neatly secured to the pole.

Features

- Accepts round and flat profile ADSS drop cables
- Span Lengths up to 300' (91 m) NESCYP heavy
- Line Angles up to 20 Degrees
- Multi-cable Options
- Two Cables per Housing and Stackable Housing for 4 or more cables
- Stringing Block
 - String-in Cable for line angles up to 10 Degrees
 - Accepts 1-1/4" (31.8 mm) diameter Pulling-in Hardware
- Mounting Options
 - Accepts 5/8" (15.8 mm) Through Bolt for Wood Pole
 - Accepts 3/4" (19.1 mm) Wide Band for Steel/Concrete Pole

Documentation

Application Procedures

[SP-2902 \(Fiberlign Lite Support ADSS Drop\)](#)

Catalog Pages

[Fiberlign Lite Support ADSS Drop - Catalog](#)

Sales Materials

[Fiberlign Lite & Tangent Support Drop Cable - Sell Sheet](#)

Part Tables

Catalog Number	Insert Size	Cable Diameter Range ¹			
		Min. (in)	Max. (in)	Min. (mm)	Max. (mm)
4800107	SMALL	0.250	0.280	6.35	7.12
4800109		0.305	0.375	7.74	9.53
480011817	LARGE	0.250	0.280	6.35	7.12
480011818		0.281	0.304	7.13	7.73
480011819		0.305	0.375	7.74	9.53
480011820	DUAL (Small & Large)	0.250	0.280	6.35	7.12
480011821		0.281	0.304	7.13	7.73
480011822		0.305	0.375	7.74	9.53

¹ Round Profile Cable Diameter Range. Flat cables use Catalog No. 4800107.

Sizes up to .700" for the Small Insert and 1.029" for the Large Insert can be found in the earlier section.

Add Suffix Code H2 for banding hardware kit that includes Retaining bolt, washer and lock washer.