

# FIBERLIGN® Figure 8 Drop Cable Dead-end

**Weight:** 0.00kg

**Dimensions:** 0.00cm x 0.00cm x 0.00cm

## Description

The **FIBERLIGN® FIGURE 8 Drop Cable Dead-end** has high strength in a light-weight package. Simple to install, the Dead-end is applied on the messenger component of the Figure 8 cable after separating the fiber component at the web. Depending on the jacket adherence, the Dead-end may be applied over the jacket or onto the bare messenger after the jacket is removed.

## Features

- Made from corrosion resistant materials that match the messenger strand material
- The loop of the Dead-end will fit over a minimum diameter of 1.0" (25 mm) and a maximum diameter of 1-5/8" (41 mm)
- Designed to fit over common guy wire Dead-end pole fittings

## Documentation

### Catalog Pages

[Fiberlign Figure 8 Drop DE - Catalog](#)

## Part Tables

| FIBERLIGN® Figure 8 Drop Cable Dead-ends |                                          |         |            |               |
|------------------------------------------|------------------------------------------|---------|------------|---------------|
| Catalog Number <sup>1</sup>              | Cable Information <sup>2</sup>           |         | Color Code | Length Inches |
|                                          | Dimension <sup>3</sup><br>L x W in. (mm) | Mfg.    |            |               |
| 699911619 <sup>4</sup>                   | .380 x .160<br>(9.6 x 4.1)               | Corning | Yellow     | 13"           |
| 200811230                                | .300 x .170<br>(7.6 x 4.3)               | Pirelli | Red        | 8"            |

1 Add suffix code "T" to dead-end catalog number to receive P/N 00065474 Thimble. P/N 00065474 is a 1/2" standard thimble – weight is 0.12 lbs. each.

2 Contact PLP for cable applications not shown

3 Dimensions L x W represent Length x Width of the Figure 8.

4 Apply over jacket