

GUY-GRIP® Dead-end

Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

Description

The PREFORMED™ **Guy-Grip Dead End** is recommended for stay termination on wood pole construction. They are suitable for stay rod, stay insulator and pole top attachment, single, multiple and flying stays can be terminated.

PREFORMED™ **Guy-Grip Dead Ends** are designed for the termination of stays up to 27m in length. **Big Grip Dead Ends** are recommended for stays exceeding 27m in length. PREFORMED™ **Big Grip Dead Ends** are available for a wide range of strand sizes.

Guy-Grip Dead Ends are intended for strand termination. For termination of wire rope, **Big Grip Wire Rope Dead Ends** are specified.

Features

PREFORMED™ **Guy-Grip Dead Ends** are made of material compatible with the strand to which they are applied.

Lay direction must be the same as that of the outer layer of the strand with which it is used.

The loop of the **Guy-Grip Dead End** is designed for use with thimbles and stay rod eyes having smooth contours, diameters and groove widths which will adequately support the loop of the fitting.

For detailed method of installation refer to application instructions.

Documentation

Application Procedures

[SP-2045 \(GUY-GRIP Dead-End\)](#)

[SP-3263 \(GUY-GRIP Dead-End - Multiple Down Guys\)](#)

Preformed Line Products (GB) Ltd. Catalogue Pages

[Guy-Grip Dead End - Transmission and Distribution Catalogue](#)

Corporate Catalogue Pages

[GUY-GRIP Dead-End - Catalogue](#)

Part Tables

Preformed Line Products (GB) Ltd. Part Tables:

STAYWORK

PREFORMED™ Guy Grip Dead End-Galvanised Steel

CATALOGUE No.	STRAND DIAMETER mm		COLOUR CODE	LENGTH mm	APPROX WEIGHT KGS PER 100	RHS KGS
	MIN	MAX				
GDE1303401	2.54	2.65	RED	254	4	1964
GDE1303402	2.66	2.78	ORANGE	279	4	1964
GDE1303403	2.79	2.91	GREEN	279	4	1964
GDE1303404	2.92	3.06	BLUE	305	4	1964
GDE1303405	3.07	3.22	BLACK	305	4	1964
GDE1303406	3.23	3.37	RED	330	4	1964
GDE1303407	3.38	3.52	ORANGE	356	5	1964
GDE1303408	3.53	3.67	GREEN	381	5	1964
GDE1303409	3.68	3.85	BLUE	406	7	2619
GDE1303410	3.86	4.03	YELLOW	432	8	2619
GDE1303411	4.04	4.21	BLACK	457	9	2619
GDE1303412	4.22	4.41	ORANGE	483	10	3175
GDE1303413	4.42	4.61	RED	483	10	3175
GDE1303414	4.62	4.82	GREEN	508	11	3175
GDE1303415	4.83	5.02	RED	508	11	3175
GDE1303416	5.03	5.25	BLACK	533	12	3274
GDE1303417	5.26	5.48	RED	559	12	3274
GDE1303418	5.49	5.70	GREEN	559	12	3274
GDE1303419	5.71	5.96	YELLOW	584	15	3969
GDE1303420	5.97	6.21	BLUE	584	16	3969
GDE1303421	6.22	6.47	BLACK	610	16	3969
GDE1303422	6.48	6.75	WHITE	635	22	5180
GDE1303423	6.76	7.03	YELLOW	635	23	5180
GDE1303424	7.04	7.33	GREEN	660	23	5180
GDE1303425	7.34	7.63	RED	686	31	6500
GDE1303426	7.64	7.97	YELLOW	711	32	6500
GDE1303427	7.98	8.30	BLACK	737	34	6500
GDE1303428	8.31	8.60	ORANGE	762	43	7902
GDE1303429	8.61	8.93	RED	787	44	7902
GDE1303430	8.94	9.31	BLACK	813	46	7902
GDE1303431	9.32	9.67	GREEN	838	45	7802
GDE1303432	9.68	10.05	BLACK	914	47	7802
GDE1303433	10.06	10.45	RED	864	47	7802
GDE1303434	10.46	10.78	ORANGE	889	59	9468
GDE1303435	10.79	11.14	GREEN	889	60	9468
GDE1303436	11.15	11.50	BLUE	914	61	9468
GDE1303437	11.51	11.83	BLACK	914	76	11280
GDE1303438	11.84	12.18	RED	1016	78	11280

For use on Galvanised Steel Strand

PREFORMED™ Guy Grip Dead End-Aluminium Covered Steel

CATALOGUE No.	STRAND DIAMETER mm		COLOUR CODE	LENGTH mm	APPROX WEIGHT KGS PER 100	RHS KGS
	MIN	MAX				
GDE1504801	4.14	4.23	RED	432	8	2268
GDE1504802	4.24	4.41	BLUE	432	10	3025
GDE1504803	4.42	4.61	GREEN	457	10	3025
GDE1504804	4.62	4.79	YELLOW	406	10	3025
GDE1504805	4.80	4.97	ORANGE	432	10	3815
GDE1504806	4.98	5.17	BLACK	483	11	3815
GDE1504807	5.18	5.37	WHITE	457	11	3815
GDE1504808	5.38	5.55	RED	483	14	4808
GDE1504809	5.56	5.86	BLUE	533	15	4808
GDE1504810	5.87	6.01	GREEN	533	15	4808
GDE1504811	6.02	6.29	ORANGE	559	16	4808
GDE1504812	6.30	6.57	YELLOW	559	16	4808
GDE1504813	6.58	6.85	BLACK	559	16	4808
GDE1504814	6.86	7.13	BLUE	610	18	4808
GDE1504815	7.14	7.41	WHITE	610	22	6010
GDE1504816	7.42	7.69	RED	610	22	6010
GDE1504817	7.70	7.97	BLACK	660	24	6010
GDE1504818	7.98	8.24	GREEN	660	24	6010
GDE1504819	8.25	8.55	BLUE	660	24	6010
GDE1504820	8.56	8.88	WHITE	737	34	7580
GDE1504821	8.89	9.26	ORANGE	787	45	9619
GDE1504822	9.27	9.64	BLACK	762	44	9619
GDE1504823	9.65	10.02	RED	813	47	9619
GDE1504824	10.03	10.40	BLUE	838	62	11435
GDE1504825	10.41	10.84	ORANGE	864	63	11435
GDE1504826	10.85	11.24	GREEN	914	66	11435
GDE1504827	11.25	11.67	YELLOW	940	87	13640
GDE1504828	11.68	12.05	BLACK	965	88	13640
GDE1504829	12.06	12.56	RED	991	91	13640

For use on Aluminium Covered Steel Strand.

PREFORMED™ Guy Grip Dead End-Copper Covered Steel

CATALOGUE No.	STRAND DIAMETER mm		COLOUR CODE	LENGTH mm	APPROX WEIGHT KGS PER 100	RHS KGS
	MIN	MAX				
GDE1605001	4.14	4.23	RED	432	7	1524
GDE1605002	4.24	4.41	BLUE	432	10	2032
GDE1605003	4.42	4.61	ORANGE	432	10	2032
GDE1605004	4.62	4.79	GREEN	406	9	2032
GDE1605005	4.80	4.97	WHITE	432	13	2327
GDE1605006	4.98	5.17	BLACK	457	13	2327
GDE1605007	5.18	5.37	BLUE	457	14	2327
GDE1605008	5.38	5.55	YELLOW	483	18	3806
GDE1605009	5.56	5.86	GREEN	508	19	3806
GDE1605010	5.87	6.01	WHITE	533	20	3806
GDE1605011	6.02	6.29	RED	533	20	3806
GDE1605012	6.30	6.57	ORANGE	559	21	3806
GDE1605013	6.58	6.85	BLACK	559	21	3806
GDE1605014	6.86	7.13	BLUE	584	22	3806
GDE1605015	7.14	7.41	GREEN	610	28	4758
GDE1605016	7.42	7.69	YELLOW	610	29	4758
GDE1605017	7.70	7.97	WHITE	635	30	4758
GDE1605018	7.98	8.24	BLACK	660	31	4758
GDE1605019	8.25	8.55	ORANGE	660	31	4758
GDE1605020	8.56	8.88	RED	686	40	5833
GDE1605021	8.89	9.26	BLUE	762	55	7189
GDE1605022	9.27	9.64	BLACK	762	55	7189
GDE1605023	9.65	10.02	GREEN	787	56	7257
GDE1605024	10.03	10.40	ORANGE	838	76	8736
GDE1605025	10.41	10.84	BLACK	864	77	8736
GDE1605026	10.85	11.24	YELLOW	890	79	9072
GDE1605027	11.25	11.67	GREEN	940	105	10587
GDE1605028	11.68	12.05	WHITE	965	107	10587
GDE1605029	12.06	12.56	RIUF	990	110	10587

For use on Copper Covered Steel Strand.