

Wrap Guy Link

Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

Description

The PREFORMED™ **Wrap Guy Link** is designed to terminate solid or stranded wire used for stays, catenaries/messengers etc. at pole top positions, when the wire or strand is wrapped around the pole.

Suitable for varying pole diameter and for both single and double wrapping, the PREFORMED™ **Wrap Guy Link** secures the tail to the body of the wire or strand.

The 'J' type hook is an acceptable fitting for use with the PREFORMED™ **Wrap Guy Link** to retain wire or strand position. Other types of fittings, with or without rubbing plates may be used, providing they permit secure attachment.

Features

Intended for single use but can be reinstalled twice within 90 days.

The PREFORMED™ **Wrap Guy Link** is always manufactured from a material compatible with the strand to which they are applied.

The lay direction must be the same as that of the strand with which it is used.

Documentation

Application Procedures

[SP-2030 \(Wrap Guy Link\)](#)

Preformed Line Products (GB) Ltd. Catalogue Pages

[Wrap Guy Link - Transmission and Distribution Catalogue](#)

Corporae Catalogue Pages

[Wrap Guy Link - Catalogue](#)

Part Tables

Preformed Line Products (GB) Ltd. Part Tables:

STAYWORK

PREFORMED™ Wrap Guy Link-Galvanised Steel

| CATALOGUE No. | STRAND DIAMETER mm | | COLOUR CODE | 'O' CLIP SIZE | LENGTH mm | APPROX WEIGHT KGS PER 100 | RHS KGS |
|------------------|-----------------------|-------|----------------|------------------|--------------|------------------------------|------------|
| | MIN | MAX | | | | | |
| WGL1403601 | 4.83 | 5.02 | RED | 11.02 | 940 | 13 | 2167 |
| WGL1403602 | 5.03 | 5.25 | BLACK | 11.02 | 965 | 13 | 2372 |
| WGL1403603 | 5.26 | 5.48 | WHITE | 11.02 | 991 | 13 | 2581 |
| WGL1403604 | 5.49 | 5.71 | YELLOW | 11.02 | 1016 | 13 | 2803 |
| WGL1403605 | 5.72 | 5.98 | GREEN | 11.02 | 1067 | 17 | 3057 |
| WGL1403606 | 5.99 | 6.21 | BLUE | 12.70 | 1118 | 18 | 3325 |
| WGL1403607 | 6.22 | 6.47 | BLACK | 12.70 | 1143 | 18 | 3604 |
| WGL1403608 | 6.48 | 6.66 | WHITE | 12.70 | 1245 | 27 | 3924 |
| WGL1403609 | 6.67 | 7.03 | YELLOW | 12.70 | 1270 | 27 | 4255 |
| WGL1403610 | 7.04 | 7.33 | GREEN | 12.70 | 1295 | 27 | 4631 |
| WGL1403611 | 7.34 | 7.63 | RED | 14.27 | 1372 | 37 | 5026 |
| WGL1403612 | 7.64 | 7.97 | YELLOW | 14.27 | 1422 | 39 | 5470 |
| WGL1403613 | 7.98 | 8.30 | BLACK | 14.27 | 1473 | 40 | 5938 |
| WGL1403614 | 8.31 | 8.60 | ORANGE | 15.87 | 1549 | 52 | 6382 |
| WGL1403615 | 8.61 | 8.93 | RED | 15.87 | 1600 | 54 | 6881 |
| WGL1403616 | 8.94 | 9.31 | BLACK | 15.87 | 1626 | 55 | 7484 |
| WGL1403617 | 9.32 | 9.67 | GREEN | 15.87 | 1651 | 52 | 7802 |
| WGL1403618 | 9.68 | 10.05 | BLACK | 15.87 | 1702 | 54 | 7802 |
| WGL1403619 | 10.06 | 10.45 | RED | 15.87 | 1753 | 55 | 7802 |
| WGL1403620 | 10.46 | 10.78 | ORANGE | 19.05 | 1880 | 74 | 9480 |
| WGL1403621 | 10.79 | 11.14 | GREEN | 19.05 | 1905 | 75 | 9480 |
| WGL1403622 | 11.15 | 11.50 | BLUE | 19.05 | 1956 | 77 | 9480 |
| WGL1403623 | 11.51 | 11.83 | BLACK | 22.14 | 2032 | 97 | 11294 |
| WGL1403624 | 11.84 | 12.18 | RED | 22.14 | 2083 | 100 | 11294 |
| WGL1403625 | 12.19 | 12.55 | ORANGE | 22.14 | 2134 | 102 | 11294 |

For use on Galvanised Steel Strand.

