

Spool Tie

Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

Description

The **PREFORMED™ Spool Tie** is intended to secure bare or jacketed conductors in the side groove of vertically and horizontally mounted spool/bobbin insulators used in low voltage distribution construction. **Spool Ties** with pads, are recommended for use with bare conductors.

Features

Spool Ties provide superior abrasion protection for the conductor under all types of motion including aeolian vibration, galloping and sway.

The pad component surrounds the conductor with a resilient cushion which eliminates abrasion at the conductor-insulator interface.

Documentation

Application Procedures

[SP-2066 \(Spool Tie\)](#)

[SP-2711 \(Spool Tie-Secondary Application\)](#)

Preformed Line Products (GB) Ltd. Catalogue Pages

[Spool Ties - Transmission and Distribution Catalogue](#)

Corporate Catalogue Pages

[Spool Tie - Catalogue](#)

Part Tables

Preformed Line Products (GB) Ltd. Part Tables:

CATALOGUE No.	CONDUCTOR DIAMETER RANGE mm		COLOUR CODE	APPROX WEIGHT KGS PER 100
	MIN	MAX		
SPT5011001	4.83	5.05	BROWN	4.18
SPT5011002	5.06	5.28	ORANGE	4.18
SPT5011003	5.29	5.53	GREEN	4.18
SPT5011004	5.54	5.79	YELLOW	4.18
SPT5011005	5.80	6.04	PURPLE	4.18
SPT5011006	6.05	6.30	BLACK	4.18
SPT5011007	6.31	6.59	BLUE	5.28
SPT5011008	6.60	6.85	WHITE	5.28
SPT5011009	6.86	7.13	BLACK	5.28
SPT5011010	7.14	7.42	BROWN	5.28
SPT5011011	7.43	7.72	ORANGE	5.28
SPT5011012	7.73	8.00	GREEN	8.96
SPT5011013	8.01	8.33	YELLOW	8.96
SPT5011014	8.34	8.66	PURPLE	8.96
SPT5011015	8.67	8.99	BLACK	8.96
SPT5011016	9.00	9.34	BLUE	12.39
SPT5011017	9.35	9.70	WHITE	12.83
SPT5011018	9.71	10.01	RED	12.83

For use on Aluminium Based Conductors

The fittings listed are designed to fit spool/bobbin insulators with a groove radius of 9.5mm and a neck diameter of 44.5mm.

CATALOGUE No.	CONDUCTOR DIAMETER RANGE mm		COLOUR CODE	APPROX WEIGHT KGS PER 100
	MIN	MAX		
SPT4011201	4.83	5.05	BROWN	44
SPT4011202	5.06	5.28	ORANGE	4
SPT4011203	5.29	5.53	GREEN	4
SPT4011204	5.54	5.79	YELLOW	4
SPT4011205	5.80	6.04	PURPLE	4
SPT4011206	6.05	6.30	BLACK	4
SPT4011207	6.31	6.59	BLUE	4
SPT4011208	6.60	6.85	WHITE	4
SPT4011209	6.86	7.13	BLACK	4
SPT4011210	7.14	7.42	BROWN	4
SPT4011211	7.43	7.72	ORANGE	4
SPT4011212	7.73	8.00	GREEN	10
SPT4011213	8.01	8.33	YELLOW	10
SPT4011214	8.34	8.66	PURPLE	10
SPT4011215	8.67	8.99	BLACK	10
SPT4011216	9.00	9.34	BLUE	13
SPT4011217	9.35	9.70	WHITE	13
SPT4011218	9.71	10.01	RED	13

For use on Copper Based Conductors

The fittings listed are designed to fit spool/bobbin insulators with a groove radius of 9.5mm and a neck diameter of 44.5mm.

Videos