

# Plastic Line Tie

**Weight:** 0.00kg

**Dimensions:** 0.00cm x 0.00cm x 0.00cm

**IMAGE  
COMING  
SOON**

## Description

**Plastic Line Ties** are intended for use on “tangent” construction with jacketed conductors and vertically mounted tie top insulators on cross-arms, pole-top mounted insulators, or Spacer Cable brackets. Line angles of up to 15° are recommended.

## Features

- Suitable for use with any plastic covered conducton such as Tree Wire of Spacer Cable
- Two versions availabe: Standard "PVC" and "Semi-Con" for higher voltage applications

## Documentation

### Application Procedures

[SP-2618 \(Plastic Line Tie\)](#)

## Catalog Pages

[Plastic Line Tie - Catalog](#)

## Part Tables

## C-Neck

PVC Plastic Ties Catalog Number	Semi-Con Plastic Ties Catalog Number	OD Range (in.)		Nominal Conductor Size	Units per carton	Approx. Wt./Lbs.	Approx. Applied Length (in.)	Insulator Color ID Mark (PVC/SC)	Conductor Color Code (PVC/SC)
		Min.	Max.						
TTC-1104	TTC-1104SC	0.296	0.400	#4, 6/1, 2/64s	50	15	20	Black/None	White
TTC-1100	TTC-1100SC	0.401	0.540	#2, 6/1, 3/64s #4, 7W, 8/64s	50	15	19	Black/None	Green
TTC-1101	TTC-1101SC	0.541	0.730	1/0, 6/1, 10/64s 3/0, 6/1, 4/64s	50	16	19	Black/None	Blue
TTC-1102	TTC-1102SC	0.731	0.920	4/0, 6/1, 10/64s 336.4, 18/1, 6/64s	50	17	20	Black/None	Orange
TTC-1103	TTC-1103SC	0.921	1.100	336.4, 18/1, 10/64s 447, 19W, 8/64s	50	18	22	Black/None	Red
TTC-1105	TTC-1105SC	1.101	1.300	477, 37W, 10/64s 795, 61W, 6/64s	50	20	24	Black/None	Black/None

## F-Neck

PVC Plastic Ties Catalog Number	Semi-Con Plastic Ties Catalog Number	OD Range (in.)		Nominal Conductor Size	Units per carton	Approx. Wt./Lbs.	Approx. Applied Length (in.)	Insulator Color ID Mark (PVC/SC)	Conductor Color Code (PVC/SC)
		Min.	Max.						
TTF-1205	TTF-1205SC	0.296	0.400	#4, 6/1, 2/64s	50	15	20	Yellow	White
TTF-1200	TTF-1200SC	0.401	0.540	#2, 6/1, 3/64s #4, 7W, 8/64s	50	15	19	Yellow	Green
TTF-1201	TTF-1201SC	0.541	0.730	1/0, 6/1, 10/64s 3/0, 6/1, 4/64s	50	16	19	Yellow	Blue
TTF-1202	TTF-1202SC	0.731	0.920	4/0, 6/1, 10/64s 336.4, 18/1, 6/64s	50	17	20	Yellow	Orange
TTF-1203	TTF-1203SC	0.921	1.100	336.4, 18/1, 10/64s 447, 19W, 8/64s	50	19	22	Yellow	Red
TTF-1204	TTF-1204SC	1.101	1.300	477, 37W, 10/64s 397.5, 19W, 12/64s	50	21	24	Yellow	Black/None