

# Alloy Spool Tie

**Weight:** 0.00kg

**Dimensions:** 0.00cm x 0.00cm x 0.00cm

## Description

Preformed Line Products **Alloy Ties** are intended for use in corrosive environments on aluminum based conductors. They are suitable for use on ANSI C29 compliant insulators. Alloy Ties are designed for use in coastal areas. They have been performance-matched to aluminum conductors and are much more corrosive-resistant than standard aluminized steel ties.

## Features

- Easily applied by hand or with hot sticks
- Performance matched materials
- Will not damage the conductor during installation
- Conductor application up to 1.24"
- Accommodates line angles 0-40° depending on application
- Resiliency built in to protect the conductor
- Reacts like the conductor under loading
- Adheres to NESC Standards
- Will hold a minimum of 700 lbs. of unbalanced load (According to rigorous PLP testing)
- Suitable for use with either ANSI compliant polymer or porcelain insulators
- Made in the USA

## Documentation

### Application Procedures

[SP-2762 \(Alloy Spool Tie\)](#)

## Sales Materials

[Alloy Ties - Sell Sheet](#)

## Part Tables

Alloy Spool Ties			
Spool Ties	Dia. Range (in) Min.	Dia. Range (in) Max.	Color Code
ASP-4304	0.316	0.357	Red
ASP-4305	0.358	0.405	Yellow
ASP-4306	0.406	0.459	Blue
ASP-4307	0.460	0.520	Orange
ASP-4308	0.521	0.588	Red
ASP-4309	0.589	0.665	Purple
ASP-4310	0.666	0.755	Brown
ASP-4311	0.756	0.858	Red

## Videos