

Service-Grip Dead-end

Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

Description

Service-Grip Dead-end, manufactured of aluminum-covered steel, is designed for bare neutral messengers of self-supporting cable used in making service drops. The Dead-end is recommended for service drops by reason of minimum length, economy, and neatness of appearance. Mechanical strength meets the requirements for NESC Grade "N", Rule 263-E, Supply Services, Spans not exceeding 150 feet.

Features

- Manufactured of aluminum-covered steel
- Designed for bare neutral messengers or self-supporting cable used in making service drops

Documentation

Application Procedures

[SP-2019 \(Service-Grip Dead-end\)](#)

Catalog Pages

[Service-Grip Dead-end - Catalog](#)

Part Tables

| Catalog Number | Diameter Range (In.) | | Nominal Conductor Sizes | | | | Units | Wt./Lbs. | Length (In.) | Color Code | Max. Neck Dia. (In.) |
|----------------|----------------------|------|-------------------------|---------------------|-------------|---------------------|------------|----------|--------------|------------|----------------------|
| | Min. | Max. | ACSR | All-Alum. | Alum. Alloy | Comp. | Per Carton | | | | |
| SG-4500 | .169 | .198 | #6, 6/1 | #6, 7W | #6, 7W | #6, 6/1 #6, 7W | 300 | 24 | 11 | Blue | 2-3/8 |
| SG-4501 | .199 | .224 | #5, 6/1 | #4, Solid | #5, 7W | #4, 7W | 300 | 27 | 12 | White | 2-3/8 |
| SG-4502 | .225 | .257 | #4, 6/1 #4, 7/1 | #4, 7W | #4, 7W | #4, 6/1 #4, 7/1 | 300 | 29 | 13 | Orange | 2-3/8 |
| SG-4503 | .258 | .289 | #3, 6/1 | #3, 7W #2, Solid | #3, 7W | #3, 6/1 #2, 7W | 200 | 27 | 14 | Black | 2-5/8 |
| SG-4504 | .290 | .325 | #2, 6/1 #2, 7/1 | #2, 7W | #2, 7W | #2, 6/1 #1, 7W | 200 | 28 | 15 | Red | 2-5/8 |
| SG-4505 | .326 | .360 | #1, 6/1 | #1, 7W | #1, 7W | #1, 6/1 1/0, 7W | 200 | 31 | 17 | Green | 2-5/8 |
| SG-4506 | .361 | .400 | 1/0, 6/1 | 1/0, 7W | 1/0, 7W | 1/0, 6/1 2/0, 7W | 100 | 28 | 19 | Yellow | 2-7/8 |
| SG-4507 | .401 | .450 | 2/0, 6/1 | 2/0, 7W | 2/0, 7W | 2/0, 6/1 3/0, 7W | 100 | 31 | 21 | Blue | 2-7/8 |
| SG-4508 | .451 | .510 | 3/0, 6/1 | 3/0, 7W | 3/0, 7W | 4/0, 7W | 100 | 33 | 23 | Orange | 2-7/8 |
| SG-4509 | .511 | .580 | 4/0, 6/1 4/0, 18/1 | 4/0, 7W | 4/0, 7W | 4/0, 6/1 | 100 | 37 | 26 | Red | 3 |