

# Bushing Covers for Wildlife Protection



**Weight:** 0.00kg

**Dimensions:** 0.00cm x 0.00cm x 0.00cm

## Description

Preformed Line Products **Bushing Covers for Wildlife Protection** are designed to reduce the number of outages experienced on the utility's distribution system by insulating transformer bushings, lighting arrestors, capacitors and switching equipment from incidental contact by animals. This is achieved by covering energized components sufficiently so that an animal can not contact the component and ground potential simultaneously.

## Features

- Made from a light gray, high voltage, plasticol compound that is a minimum of 100 mills thick.

## Documentation

### Application Procedures

[SP-2759 \(WP-11S;WP-CSP;WP-10T;WP-17T\)](#)

[SP-2959 \(WP-2.25F\)](#)

## Catalog Pages

[Bushing Covers for Wildlife Protection - Catalog](#)

**Sales Materials**

[Bushing Covers for Wildlife Protection - Sell Sheet](#)

**Part Tables**

BUSHING COVERS						
PLP Catalog Number	Description	Carton Quantity	Height (inches)	Width (inches)	Length (inches)	Tap Wire Opening (inches)
WP-10T	Single bushing transformer and capacitor. Will cover a maximum of 7.5" of tap wire. Locking tabs hold the guard on the first skirt of the insulator.	25	11.75	3.75	3.75	up to 0.75
WP-11T	Single bushing transformer and capacitor. Will cover a maximum of 12.5" of tap wire. Locking tabs hold the guard on the first skirt of the insulator.	25	17.00	3.75	3.75	up to 0.75
WP-11S	Existing tap retrofit. Apply through slit edge and hold guard in place with the fasteners provided.	25	11.00	3.50	3.50	0.40
WP-CSP	Completely Self-Protected (CSP) transformers. Designed as retrofit. Designed to protect both primary bushing and lightning arrester.	25	3.75	3.50	12.25	0.40
WP-2.25F	Single bushing transformer. Covers 2.25" OD current limiting fuse bolted to bushing. Bottom of the double dipped tip indicates point of install for fuse. Locking tabs hold guard on first skirt of the insulator.	25	12.75	3.75	3.75	cut as needed