

# FIBERLIGN<sup>®</sup> Lite Support for Figure 8 Drop Cables

**Weight:** 0.00kg

**Dimensions:** 0.00cm x 0.00cm x 0.00cm

## Description

The **FIBERLIGN Lite Support (FLS) for FIGURE 8 Drop Cables** is the perfect product for distribution of multiple drop cables in an FTTP system as each FLS can support two cables and the FLS has stackable housings. One 5/8" double arming bolt or through bolt can securely stack FLS units within the same pole space. This keeps cables neatly secured to the pole.

## Features

- Secures most figure 8 cable in soft one-piece insert.
- Span lengths up to 300' NESC heavy.
- Line angles up to 20 degrees.
- Two cables per housing.
- Stackable housings for 4 or more cables.
- Small and Large inserts are offered. A dual insert kit is available as well.

## Documentation

### Application Procedures

[SP-2902 \(Fiberlign Lite Support Figure 8\)](#)

## Catalog Pages

[Fiberlign Lite Support Figure 8 - Catalog](#)

## Sales Materials

### [Fiberlign Lite & Tangent Support Drop Cable - Sell Sheet](#)

#### Part Tables

Catalog Number	Insert Size	Cable Dimension			
		Min. L X W (in)	Max. L X W (in)	Min. L X W (mm)	Max. L X W (mm)
4800107	SMALL	.3 x .16	.44 x .18	7.6 x 4.1	11.2 x 4.6
480011817	LARGE	.3 x .16	.44 x .18	7.6 x 4.1	11.2 x 4.6
480011820	DUAL (Small & Large)	.3 x .16	.44 x .18	7.6 x 4.1	11.2 x 4.6

Add Suffix Code H2 for banding hardware kit that includes retaining bolt, washer and lock washer.