Reeving Splice

Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

Phone: 123456789 - Email: name@yourdomain.com

Description

PLP Reeving Splices were designed in conjunction with Otis Elevator Company as an aid to simplify marrying wire ropes during elevator repairs. Reeving splices hold galvanized steel cables in place, allowing old elevator wire ropes to be removed and replaced.

Features

- Designed to hold working loads from zero to 2,000 lbs
- Saves repair time
- Applies quickly without need of special tools
- Designed to maintain a constant, positive grip, even when ropes go slack
- For use on Galvanized Steel Elevator wire rope
- Multiple sizes available
- Patented

Documentation Application Procedures

SP2260 (Reeving Splice)

Sales Materials

Reeving Splice - Sell Sheet

Part Tables

Catalog Number	Wire Rope Size		Overall Diameter
	in	mm	
			in (mm)
RS-2102	5/16	8	.415 (10.54)
RS-2103	3/8	9	.477 (12.11)
RS-2104	7/16	11	.539 (13.71)

RS-2105	1/2	12	.640 (16.25)
RS-2106	9/16	14	.702 (17.83)
RS-2107	5/8	15	.797 (20.24)
RS-2108	11/16	17	.887 (22.52)
RS-2109	3/4	19	.950 (24.13)
RS-2110	13/16	20	1.036 (26.31)
RS-2111	7/8	22	1.113 (28.27)
RS-2112	1	25	1.238 (31.44)