

Drop Wire Dead-end

Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

Description

PREFORMED Drop Wire Dead-ends provide an easy, low-cost way to support service drop wire without bail failures or stripping the insulation.

Features

- Applied by hand in seconds
- No tools required
- Wrap-on design prevents potentially damaging stress points
- Trim and modern appearance
- Manufactured of neoprene-coated, stainless steel for added protection against the elements

Documentation

Application Procedures

[SP-2152 \(Drop Wire Dead-end\)](#)

Catalog Pages

[Drop Wire Dead-end - Catalog](#)

Part Tables

Stainless Steel Neoprene Coated

Catalog Number	Manufacturer	Manufacturer's Designation	Color Code	Units Per Carton	Wt./Lbs. Per Carton
NDE-9500	Alphaduct	PDCW Parallel (N-182)	Black	100	9
	Alphaduct	PDCW Parallel Dumbbell (NE-182)	Black	100	9
	Alphaduct	PDCW Parallel Reinforced (NR-182)	Black	100	9
	Whitney-Blake	TCWP Parallel (2#18)	Black	100	9
	Whitney-Blake	TBP Parallel Reinforced (2#17)	Black	100	9
NDE-9501	AT&T	Bell Reinforced (2#18)	Green	100	9
	Whitney-Blake	TBP-R Parallel Reinforced (2#17)	Green	100	9