

TAP™ Protector Rod



Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

Description

TAP™ Protector Rods are intended to protect the conductor from potential damage due to bolted or compression type hot line clamp and stirrup installation. These rods provide reinforcement to the conductor, designed to reduce the possibility of conductor damage due to bending stress, clamping stress, or abrasion.

Features

- Reduces clamping stress on the conductor
- Manufactured from strong, fatigue resistant aluminum alloy
- RUS-approved product for standard construction methods
- Easily installed by hand or hot sticks
- Limited conductor preparation required for installation

Documentation

Application Procedures

[SP-2685 \(TAP™ Protector Rod\)](#)

Catalog Pages

[TAP™ Protector Rod - Catalog](#)

Sales Materials

[TAP™ Protector Rod - Sell Sheet](#)

Part Tables

TAP Protector Rods						
PLP Catalog Number	TAP Rod Conductor Ranges	Nominal Conductor Sizes	Total Overall Diameter	Applied Length	Qty. per Carton	Color
TAP-0175	.244" - .259"	#4 ACSR, AAC, AAAC	.486" - .501"	10"	100	Orange
TAP-0179	.309" - .326"	#2 ACSR, AAC, AAAC	.551" - .568"	10"	100	Red
TAP-0183	.390" - .413"	1/0 ACSR, AAC, AAAC	.632" - .655"	12"	100	Yellow
TAP-0185	.437" - .463"	2/0 ACSR, AAC, AAAC	.679" - .705"	13"	50	Blue
TAP-0187	.491" - .521"	3/0 ACSR, AAC, AAAC	.733" - .763"	14"	50	Orange
TAP-0189	.552" - .585"	4/0 ACSR, AAC, AAAC	.764" - .827"	15"	100	Red
TAP-0191	.607" - .630"	266.8 ACSR, AAC, AAAC	.849" - .872"	16"	100	White
TAP-0192	.632" - .655"	266.8 ACSR, AAC, AAAC	.874" - .897"	16"	50	Yellow
TAP-0194	.680" - .703"	336.4 ACSR, AAC, AAAC	.922" - .945"	17"	50	Blue
TAP-0195	.704" - .740"	336.4 ACSR, AAC, AAAC	.946" - .982"	18"	50	Green
TAP-0197	.793" - .840"	477 ACSR, AAC, AAAC	1.035" - 1.082"	20"	50	Purple
TAP-0198	.841" - .898"	477 ACSR, AAC, AAAC	1.083" - 1.140"	21"	25	Blue