

I-String Assembly - Tangent Suspension, Twin-Bundle Conductor, 50K



Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

Description

PLP **Tangent Suspension String Assemblies** support the conductor as it runs tangent to the structure. I-String or V-String configurations can be designed to accommodate specified insulator strength, bundling configuration, bundle spacing, and other features.

Features

- All items will arrive in one weather-resistant crate, so all string parts will be delivered at the same time.
- String Assemblies are packaged and marked by string or tower for easy field identification, to minimize handling, and to expedite string installation.
- The number of assemblies per crate can be modified based on customer requirements.
- The catalog numbers provided represent commonly used string configurations. Please contact a PLP sales representative if you are interested in design modifications, or creation of an assembly to your specification.

Notes:

- All galvanizing has been performed per ASTM A153

- Parts with length “L” are variable length and dependent on the string design and line parameters.
- Suspension Clamp and associated attachment hardware sold separately. See the Suspension and Support section of the website for AGS / CGS / Bolted Clamp and Armor Rods options.
- Compression Dead-end Assemblies are sold separately. Please see the Compression Hardware section of the website for ACSR / ACSS / ACCC configurations.
- Corona rings are packaged separately.
- Please see the individual component drawings for detailed dimensions and material properties of parts.

Documentation
Sales Materials

[S-IH-21-50 - Catalog Pages](#)

Part Tables

Catalog Number
S-IH-21-50

Bill of Materials					
Part Number	Description	QTY	Material	Weight (Ea) lbs. (Kg)	UBS lbs.
AS-50BNK	Anchor Shackle	1	Galv. Steel	1.7 (0.8)	50,000
Supplied By Other	Insulator String	1	-	-	-
SYC-50	Socket Y-Clevis	1	Ductile Iron	5.4 (2.4)	50,000
YPD-65607	Yoke Plate,	1	Ductile Iron	20.8 (9.4)	50,000

	Delta, 50K (APEX Hole)				
See Note 3 in Features section	Attachment Hardware	2	Ductile Iron	-	-
See Note 3 in Features section	Suspension Hardware	2	Aluminum	-	-