

EZ-WRAP[®] Spool Tie

Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

Description

The **EZ-WRAP Spool Tie** is intended for use on aluminum based conductors with diameters from .190" to .968".

Features

- An EZ-WRAP Spool Tie Assembly consists of one metal tie component plus tie tube
- The elastomeric tie tube is designed for abrasion protection with bare conductors

Documentation

Application Procedures

[SP-2762 \(EZ-WRAP[®] Spool Tie\)](#)

Catalog Pages

[EZ-WRAP[®] Spool Tie - Catalog](#)

Part Tables

| Catalog Number | Diameter Range (Inches) | | Nominal Conductor Size | | Units | Wt./Lbs. | Applied Length (Inches) | Color Code |
|----------------|-------------------------|-------|--|--|------------|----------|-------------------------|------------|
| | Min. | Max. | Bare Conductor | Plastic Jacketed Conductor | Per Carton | | | |
| EZSP-4372 | .245 | .277 | #4 (6/1, 7/1) #4 (7W Alum. Alloy) | #6 (7W, 2/64s) #6 (Solid, 3/64s) #6 (6/1, 2/64s) | 100 | 16 | 19 | Orange |
| EZSP-4374 | .316 | .357 | #2 (6/1, 7/1) #2 (7W Alum. Alloy) #1 (6/1) | #4 (7W, 3/64s) #4 (6/1, 7/1, 3/64s) | 100 | 16 | 24 | Red |
| EZSP-4375 | .358 | .405 | 1/0 (7W All Alum.) 1/0 (6/1) 1/0,7(W Alum. Alloy) | #3 (7W, 4/64s) #2 (7W, 3/64s) #4 (7W, 5/64s) | 100 | 17 | 26 | Yellow |
| EZSP-4376 | .406 | .459 | 2/0 (7W All Alum.) 2/0 (6/1) 2/0 (7W Alum. Alloy) | #2 (6/1, 3/64s) #2 (7W, 4/64s) #1 (7W, 4/64s) | 100 | 21 | 28 | Blue |
| EZSP-4377 | .460 | .520 | 3/0 (7W All Alum.) 3/0 (6/1) 3/0 (7W Alum. Alloy) | #4 (7W, 8/64s) #1 (6/1, 4/64s) #1 (7W-19W, 5/64s) 1/0 (7W, 4/64s) | 100 | 21 | 31 | Orange |
| EZSP-4378 | .521 | .588 | 4/0 (7W All Alum.) 4/0 (6/1) 4/0 (7W Alum. Alloy) | 1/0 (6/1, 4/64s) 1/0 (7W, 5/64s) 2/0 (7W, 4/64s) 1/0 (6/1, 5/64s) | 100 | 27 | 32 | Red |
| EZSP-4379 | .589 | .665 | 266.8 (37W All Alum.) 266.8 (18/1) 336.4 (19W All Alum.) | 3/0 (7W-19W, 4/64s) 3/0 (6/1, 4/64s) 4/0 (7W 19W, 4/64s) 3/0 (6/1, 5/64s) | 100 | 28 | 23 | Purple |
| EZSP-4380 | .666 | .755 | 336.4 (18/1) 397.5 (19W All Alum.) 400 (19W, 37W All Alum.) | 4/0 (7W, 5/64s) 3/0 (6/1, 6/64s) 4/0 (6/1, 5/64s) 266.8 (19W, 5/64s) | 100 | 30 | 25 | Brown |
| EZSP-4381 | .756 | .858 | 477 (19W, 37W All Alum.) 477 (18/1, 24/7), 26/7 | 266.8 (18/1, 5/64s) 336.4 (19W, 4/64s) 336.4 (37W, 6/64s) | 100 | 35 | 26 | Red |
| EZSP-4382 | .859 | .968 | 556.5 (26/7) 636 (18/1) 700 (37W, 61W All Alum.) | 350 (37W, 6/64s) 336.4 (19W, 8/64s) 450 (37W, 5/64s) 477(37W, 5/64s) | 100 | 40 | 28 | Blue |
| EZ-MS-10279 | .969 | 1.096 | 636 (24/7, 26/7, 54/7) 795 (37W, 61W) 795 (36/1, 24/7, 54/7) | 500 (37W, 5/64s) 477 (37W, 8/64s) 500 (37W, 8/64s) | 100 | 66 | 38 | Green |

Videos

Product Gallery