

# Overhead Dead-end

**Weight:** 0.00kg

**Dimensions:** 0.00cm x 0.00cm x 0.00cm

## Description

The **Overhead Dead-end**, intended for use on aluminum based conductor, with a diameter range of .229" to .577", is designed to terminate primary, secondary and neutral wire conductors.

## Features

- Tools are not required nor recommended to install Overhead Dead-ends, except for hot stick applications.
- Designed to grip the conductor uniformly to prevent distortion of the conductor.
- Unique design that eliminates bolts, nuts, washers and other component parts that may become lost or damaged during installation or in service.

## Documentation

### Application Procedures

[SP-2071 \(Overhead Dead-end\)](#)

## Catalog Pages

[Overhead Dead-end - Catalog](#)

## Part Tables

Catalog Number	Conductor (Inches)		Units	Wt./Lbs.	Length (Inches)	Color Code
	Range	Nominal Size	Per Carton			
OHDE-9534	.229-.257	#4	100	31	24	Orange
OHDE-9536	.290-.325	#2	100	59	30	Red
<del>OHDE-9537*</del>	<del>.326-.364</del>	<del>#1</del>	<b>Obsolete</b>	<del>60</del>	<del>34</del>	<del>Green</del>
OHDE-9538	.365-.409	1/0	50	47	38	Yellow
OHDE-9539	.410-.460	2/0	50	60	38	Blue
<del>OHDE-9540*</del>	<del>.461-.516</del>	<del>3/0</del>	<b>Obsolete</b>	<del>71</del>	<del>45</del>	<del>Orange</del>
<del>OHDE-4577*</del>	<del>.517-.577</del>	<del>4/0</del>	<b>Obsolete</b>	<del>57</del>	<del>52</del>	<del>Red</del>