



COYOTE® DTC4 AND DTC6

The **COYOTE DTC4 and DTC6 (Drop Termination Closure)** offer a durable, compact solution with multiple internal fiber organizers to support your current and future needs. Network evolution is unpredictable so why not choose a closure system developed to adapt. The DTC4 can be used as a transition unit for interior duct applications. Both the COYOTE DTC4 and DTC6 can equip an adapter bulkhead tray that hinges to allow access to the underlying fiber slack storage area.

FEATURES AND BENEFITS

- Dimensions: 10.8" x 7.8" x 3.2" (274 x 198 x 82 mm)
- Max Splice Capacity: 24 Single Fusion
- Max Adapter Quantity: 4 Dual SC or 4 Quad LC
- Grommet Quantity: 4 or 6 (Multi-Hole Grommets Available)
- Grommet Cable Diameter Range: Large Grommets = 0.118" – 0.60" (3 – 15 mm)
Small Grommets = 0.093" – 0.420" (2.4 – 10.7 mm) and Flat Drop
- Applications: Direct Bury, Below Grade, Pole/Wall Mount, Pedestal, Aerial, or Interior Applications
- Designed and tested in accordance with Telcordia® GR-771-CORE Buried, Underground, IP-68 Rated Requirements
- Constructed out of rugged UV-stabilized, flame-retardant material (UL94-5VA Rated)
- Hinged cover with integrated over-mold creates a secure seal and provides quick re-entry and re-use

ORDERING INFORMATION

COYOTE® DTC4 Catalog Number

DTC4- XX - XX - X - X - X - X

(Section 1) (Section 2) (Section 3) (Section 4) (Section 5) (Section 6)

Must be in alphabetical order Must be in alphabetical order

Catalog Number Example: DTC4-AA-DD-2-1-2-N

COYOTE® DTC6 Catalog Number

DTC6- XXXXXX - X - X - X - X

(Section 2) (Section 3) (Section 4) (Section 5) (Section 6)

Must be in alphabetical order

Catalog Number Example: DTC6-AABBDD-2-2-2-Y

Section 1

DTC4 Large Grommet Selection (Select 2)		Cable Diameter Range
A		5-Hole Design 1 Hole: 0.55" – 0.60" (14 - 15 mm) 4 Holes: 0.275" (7 mm)
B		7-Hole Design 1 Hole: 0.55" – 0.60" (14 - 15 mm) 6 Holes: 0.197" (5 mm)
C		7-Hole Design 1 Hole: 0.335" (8.5 mm) 6 Holes: 0.197" (5 mm)
D		8-Hole Design 8 Holes: 0.197" (5 mm)
E		8-Hole Design 8 Holes: 0.118" (3 mm)

Section 2

DTC4 Small Grommet Selection (Select 2)		Cable Diameter Range
DTC6 Small Grommet Selection (Select 6)		
A		SOLID / PLUG
B		0.170" – 0.250" (4.3 - 6.4 mm) ROUND CABLES
C		0.250" – 0.350" (6.4 - 8.9 mm) ROUND CABLES
D		0.156" – 0.170" (4.0 - 4.3 mm) ROUND CABLES
E		0.093" – 0.125" (2.4 - 3.2 mm) ROUND CABLES
F		FOR FLAT DROP CABLES
G		0.350" – 0.420" (8.9 - 10.7 mm) ROUND CABLES

Section 3

Organizer Options (Select 1)	
1	 Splice Only
2	 Splice & Adapters

Section 4

Adapter Type (Select 1)	
N	NONE
1	 Duplex SC/APC
2	 Duplex SC/UPC
3	 Quad LC/APC
4	 Quad LC/UPC

Section 5

Adapter Quantity
0 to 4

Section 6

Pigtails Required (Select 1) (Matches adapter type and quantity)	
N	NONE
Y	 900 µm

Accessories

Catalog Number	Description
8004109	COYOTE DTC4/6 Pole/Wall Mounting Bracket
8004110	COYOTE DTC4/6 Cable Storage Bracket
8004111	COYOTE DTC4/6 Aerial Mounting Bracket – Strand Applications
8004112	COYOTE DTC4/6 Aerial Mounting Bracket – ADSS Applications
8004172	COYOTE DTC4/6 Mounting Bracket – For use with FIBERLIGN® ADSS Cable Storage Bracket