











SPECIAL INDUSTRIES



SOLAR











Global Headquarters 660 Beta Drive Cleveland, Ohio 44143

Mailing Address: P.O. Box 91129 Cleveland, Ohio 44101

Telephone: 440.461.5200 Fax: 440.442.8816 Website: preformed.com Email: inquiries@preformed.com

© 2018 Preformed Line Products Printed in U.S.A. NU-SS-1249 11.18.IH

PLP® Arborist Products Eye-Bolt with Nut

General Information

PLP Forged Steel Eye-Bolts for tree cabling are designed to be used in traditional methods. PLP thimbles are hot-dipped galvanized to ASTM A153 standards for the best corrosion resistance. Correctly sized nut included to aid in getting the job done right.

Each size is laboratory tested to ensure proper performance at the advertised working loads. TREE-GRIP™ Dead-end and Thimbles make cabling installation easy, all you need is the strand. Available in nine sizes to work in a wide range of applications.

PLP now offers a wide range of tree cabling/ bracing products to fit arborists' needs. For information on the entire line of tree care products, please visit preformed.com or contact your local PLP representative.

Features

- Available in 9 different sizes for a widevariety of applications
- Use with PLP TREE-GRIP Dead-ends and thimbles for quicker tree cabling
- Working loads of 1,500 lbs., 2,600 lbs., and 5,200 lbs. for best performance

PLP Reliability

Preformed Line Products has been a dependable manufacturer of high-quality products since 1947.



Product Data

Eye-Bolts				
PLP Catalog Number	Description	Weight (lbs)	Working Load Limit (lbs)	Carton Qty.
EBN-9061	Eye-Bolt with Nut - 3/8" x 4-1/2"	0.29	1500	75
EBN-9062	Eye-Bolt with Nut - 3/8" x 6"	0.35	1500	50
EBN-9063	Eye-Bolt with Nut - 1/2" x 6"	0.66	2600	100
EBN-9064	Eye-Bolt with Nut - 1/2" x 8"	0.82	2600	40
EBN-9065	Eye-Bolt with Nut - 1/2" x 12"	1.14	2600	40
EBN-9066	Eye-Bolt with Nut - 1/2" x 18"	1.30	2600	25
EBN-9067	Eye-Bolt with Nut - 5/8" x 8"	1.35	5200	30
EBN-9068	Eye-Bolt with Nut - 5/8" x 12"	1.67	5200	25
EBN-9070	Eye-Bolt with Nut - 5/8" x 18"	2.05	5200	25