

COYOTE[®] Drop Cable Closure

Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

Description

The **COYOTE Drop Cable Closure** is a re-enterable (not re-usable), encapsulant filled closure for splicing buried fiber optic drop cables (up to 6-fiber). The COYOTE Drop Cable Closure will accept either dielectric or shielded fiber optic drop cables with an outside diameter of up to 0.5" (13 mm).

Features

- Each Closure body is factory filled with field proven POLY-BEE[™] Sealant to provide a protective barrier around the sealed splice tray assembly.
- The sealed splice tray assembly has an integral bond clamp which provides both conductivity between the cable shields and cable restraint.
- The splice block on the splice tray assembly holds up to six heat-shrink fusion splice protectors. Six 40 mm long protectors are provided.
- Unfilled version for aerial fiber optic drop cables (up to 6-fiber) are available.
- Meets required elements of TELCORDIA GR -771- CORE and Bellcore TR-NWT-000251, Issue 2.

Documentation

Application Procedures

[SP-2953 \(COYOTE[®] Drop Cable Closure\)](#)

Catalog Pages

[COYOTE[®] Drop Cable Closure - Catalog](#)

Sales Materials

[COYOTE® Drop Cable Closure - Sell Sheet](#)

MSDS Sheets

[C-Cement Tube - MSDS](#)

[C-Cement Can - MSDS](#)

[Poly-Bee Sealant - MSDS](#)

Part Tables

Catalog Number	Description
8006876	COYOTE Drop Cable Closure, includes sealed splice tray assembly and six (6) heat shrink splice protectors.
8006914	COYOTE Drop Cable Closure unfilled includes splice tray assembly & six (6) heat shrink splice protectors.