

# FIBERLIGN<sup>®</sup> Suspension for OPGW

**Weight:** 0.00kg

**Dimensions:** 0.00cm x 0.00cm x 0.00cm

## Description

The **FIBERLIGN Suspension** provides superior cable and fiber protection at the support point. The combination of Structural Reinforcing Rods, Outer Rods, boltless housing and resilient inserts reduces compression, clamping, and bending stresses on cable. Negative weather related cable motion, such as aeolian vibration, galloping, and wind sway are also minimized.

## Features

- Elastomer Insert is specifically formulated for resistance to ozone attack, weathering, extreme high and low temperatures variations, and compression set.
- Housing is a high-strength aluminum alloy casting.
- Applications for Single or Double Suspensions
- Consult PLP for trunnion or bracket type mounting, right-hand lay, and larger units for special applications.
- Fittings and grounding accessories available and can be included in the same container with the suspension.

## Documentation

### Application Procedures

[SP-2704 \(FIBERLIGN<sup>®</sup> Suspension for OPGW\)](#)

[SP-3049 \(FIBERLIGN<sup>®</sup> Suspension for OPGW - Enhanced Corrosion\)](#)

[SP-2968 \(FIBERLIGN<sup>®</sup> Suspension for OPGW - Double\)](#)

## Catalog Pages

## Part Tables

Catalog Number		Diameter Range				Structural Reinforcement Rods					Outer Rods				
Single	Double	Min. (in)	Max. (in)	Min. (mm)	Max. (mm)	Single Length (in)	Double Length (in)	Rod Dia. (in)	Rods per set	Color Code	Single Length (in)	Double Length (in)	Rod Dia. (in)	Rods per set	Color Code
4300100	4300200	.354	.381	8.9	9.6	66	84	.146	9	Blue	42	60	.204	11	Blue
4300101	4300201	.382	.398	9.7	10.1	66	84	.146	9	Green	42	60	.204	11	Green
4300102	4300202	.399	.418	10.2	10.6	66	84	.146	10	Yellow	42	60	.204	11	Yellow
4300103	4300203	.419	.439	10.7	11.1	67	84	.146	10	Black	42	60	.204	11	Black
4300104	4300204	.440	.458	11.2	11.6	68	84	.146	11	White	43	61	.204	11	White
4300105	4300205	.459	.461	11.7	11.7	72	90	.167	10	Purple	46	64	.250	10	Orange
4300106	4300206	.462	.476	11.8	12.0	72	90	.167	10	Purple	46	64	.250	10	Purple
4300107	4300207	.477	.503	12.1	12.7	73	90	.146	11	Orange	46	64	.250	10	Orange
4300108	4300208	.504	.511	12.8	12.9	76	90	.146	12	Red	46	64	.250	10	Purple
4300109	4300209	.512	.536	13.0	13.6	76	94	.167	11	Blue	49	67	.250	11	Blue
4300110	4300210	.537	.559	13.7	14.1	77	94	.167	11	Green	49	67	.250	11	Green
4300111	4300211	.560	.565	14.2	14.3	77	94	.167	11	Green	49	67	.250	11	Green
4300112	4300212	.566	.573	14.4	14.5	79	102	.182	11	Black	54	76	.250	12	Black
4300113	4300213	.574	.598	14.6	15.1	79	102	.182	11	Black	54	76	.250	12	White
4300114	4300214	.599	.625	15.2	15.8	81	102	.182	11	Brown	54	76	.250	12	Brown
4300116	4300216	.626	.632	15.9	16.0	94	120	.204	11	Red	63	89	.310	11	Red
4300117	4300217	.633	.666	16.1	16.9	94	120	.204	11	Red	63	89	.310	11	Blue
4300118	4300218	.667	.682	17.0	17.3	94	120	.204	11	Yellow	63	89	.310	11	Green
4300119	4300219	.683	.710	17.4	18.0	94	120	.204	11	Yellow	63	89	.310	11	Yellow
4300120	4300220	.711	.728	18.1	18.4	94	120	.204	12	White	63	89	.310	12	Black
4300121	4300221	.729	.744	18.5	18.8	94	120	.204	12	White	63	89	.310	12	White
4300122	4300222	.745	.750	18.9	18.9	94	120	.204	12	White	63	89	.310	12	White
4300123	4300223	.751	.786	19.0	19.9	94	120	.204	12	Brown	63	89	.310	12	Brown
4300124	4300224	.787	.814	20.0	20.6	100	129	.250	11	Green	72	101	.365	11	Green
4300125	4300225	.815	.845	20.7	21.4	100	129	.250	11	Yellow	72	101	.365	11	Yellow
4300126	4300226	.846	.855	21.5	21.6	100	129	.250	11	Blue	72	101	.365	12	Blue
4300127	4300227	.856	.894	21.7	22.6	100	132	.250	12	Black	80	112	.365	12	Black
4300128	4300228	.895	.907	22.7	22.9	100	132	.250	12	White	80	112	.365	12	White
4300129	4300229	.908	.916	23.0	23.2	100	132	.250	12	Purple	80	112	.365	12	Purple
4300153	4300253	.917	.929	23.3	23.5	100	132	.250	12	Brown	80	112	.365	12	Brown
4300154	4300254	.930	.942	23.6	23.9	100	132	.250	12	Red	80	112	.365	12	Red
4300155	4300255	.943	.977	24.0	24.7	100	132	.250	13	Orange	80	112	.365	13	Orange

Left-hand lay standard

## Videos

### Installation Video

## Accessories

Ground Wire assemblies and fittings may be included in the same container with the suspension by adding the appropriate SUFFIX CODE from the below table.

**Note:** the suffix sequence is grounding wire first and fittings second.

**Ex. 4300100GYC** includes a 4300100 single suspension with copper ground wire

## assembly (G) and Y-clevis eye (YC).

Suffix Code	Description
G	4' (1.2 m) long #4 (7W) Copper with terminal on one end. Catalog #710010015
GA	4' (1.2 m) long 4/0 (19W) Aluminum conductor with terminal on one end. Catalog #710010293
GA2	5' (1.5 m) long 95 mm <sup>2</sup> (7w) Aluminum Ground wire with terminals at both ends

**CAUTION:** Determine appropriate material and size wire necessary to provide adequate grounding for your system before ordering the ground wire assemblies. For proper performance and personal safety be sure to select the proper ground wire before application.

S2	Anchor Shackle (Catalog no 72905002), 25,000#
YC	One (1) Y-clevis to fit selected suspension. Single suspension applications.
CE	One (1) clevis-eye to fit selected suspension. Single suspension applications.
CEYP	Two (2) clevis-eyes with yoke plate to fit selected suspension. Double suspension applications.