

# Strand Splice

**Weight:** 0.00kg

**Dimensions:** 0.00cm x 0.00cm x 0.00cm

## Description

Strand Splices are intended for use on guys or messengers.

## Features

- Rated for 100% of the strands published rated breaking strength unless otherwise noted.
- Made of the same basic material as the strand to which they are applied.

## Documentation

### Application Procedures

[SP-2033 \(Strand Splice\)](#)

## Catalog Pages

[Strand Splice - Catalog](#)

## Part Tables

**For use on:  
Extra High Strength, High Strength,  
Siemens Martin, Utilities Grade<sup>2</sup>**

Catalog Number	Strand			Units	Wt./Lbs.	Length (In.)	No. of Subsets	Rod Diameter (In.)	Color Code
	Size (In.)	Construction	Actual Diameter (In.)	Per Carton					
GLS-2102	3/16	7W 7W	.195 .186	100	30	27	2	.070	Red
GLS-2103	7/32	7W	.216	100	36	29	2	.070	Green
GLS-2104	1/4	3W 7W	.259 .240	50	34	35	2	.086	Yellow
GLS-2105	9/32	7W	.279	50	36	38	2	.086	Blue
GLS-2106	5/16	3W 7W	.312 .327	50	46	42	3	.086	Black
GLS-2107	3/8	3W 7W	.356 .360	25	38	50	3	.100	Orange
GLS-2108	7/16	7W	.435	25	58	56	3	.119	Green
GLS-2109	1/2	7W 19W	.495 .500	10	36	63	3	.138	Blue
GLS-2110	9/16	7W 19W	.564 .565	10	52	70	4	.159	Yellow

**For use on:  
Bezinal Strand<sup>2</sup>**

Catalog Number	Strand			Per Carton		Length (Inches)	Number of Subsets	Rod Diameter (Inches)	Color Code
	Size (Inches)	Construction	Mean Diameter (Inches)	Units	Weight (Lbs)				
BLS-9102	3/16	7W	.186	100	30	27	2	.070	Red
BLS-9104	1/4	3W 7W	.240	50	34	35	2	.086	Yellow
BLS-9106	5/16	3W 7W	.312	50	46	42	3	.086	Black
BLS-9107	3/8	3W 7W	.360	25	38	50	3	.100	Orange
BLS-9108	7/16	7W	.435	25	57	56	3	.119	Green
BLS-9109	1/2	7W 19W	.495	10	34	63	3	.138	Blue

**For use on:  
Aluminum Clad Steel<sup>2</sup>**

Catalog Number	Strand		Units	Wt./Lbs.	Length (Inches)	No. of Subsets	Rod Diameter (Inches)	Color Code
	Construction	Mean Diameter (Inches)	Per Carton					
AWLS-4102	3#12	.174	50	12	19	2	.081	Orange
AWLS-4108	4M 3#10	.220 .220	50	22	24	2	.102	Green
AWLS-4110	3#9 6M 1/4"	.247 .242 .242	50	24	25	2	.102	Yellow
AWLS-4113	3#8 9/32" 8M	.277 .272 .272	50	30	28	3	.102	Blue
AWLS-4116	3#7 10M 5/16"-7#10	.311 .306 .306	50	34	30	3	.102	Black
AWLS-4119	3#6 12.5M 11/32"-7#9	.349 .343 .343	50	46	33	3	.114	Yellow
AWLS-4120	14M	.363	25	32	36	3	.128	Blue
AWLS-4122	3#5 3/8"-7#8 16M	.392 .385 .386	25	34	38	3	.128	Orange
AWLS-4124	18M	.417	25	45	41	3	.144	Black
AWLS-4125	7/16"-7#7	.433	25	55	50	3	.144	Green
AWLS-4126	20M	.444	10	30	53	3	.162	Yellow

**For use on:  
Copperweld Strand<sup>2</sup>**

Catalog Number	Strand		Units	Wt./Lbs.	Length (Inches)	No. of Subsets	Rod Diameter (Inches)	Color Code
	Size	Mean Diameter (Inches)	Per Carton					
CLS-8100	2.2M	.164	50	12	18	2	.081	Orange
CLS-8102	3#12	.174	50	14	19	2	.081	Red
CLS-8106	4M	.209	50	20	22	2	.091	White
CLS-3101	3#10	.220	50	28	24	2	.102	Green
CLS-3103	3#9 6M	.247 .237	50	28	25	2	.102	Yellow
CLS-3104	6M3	.258	50	32	26	3	.102	White
CLS-3106	8M 3#8	.276 .277	50	36	28	3	.102	Blue
CLS-3109	10M 7#10, 5/16" 3#7	.303 .306 .311	50	40	30	3	.102	Red
CLS-3112	7#9, 11/32" 12.5M 3#6	.343 .345 .349	50	58	33	3	.114	Green
CLS-3113	14M	.360	25	38	36	3	.128	Blue
CLS-3115	7#8, 3/8" 16M 3#5	.385 .386 .392	25	40	38	3	.128	White
CLS-3117	18M	.414	25	56	41	3	.144	Orange
CLS-3118	20M 7#7, 7/16"	.438 .433	10	28	50	3	.144	Yellow
CLS-3121	7#6, 1/2"	.486	10	38	55	3	.162	Blue
CLS-3123	25M	.525	10	52	61	3	.182	Green
CLS-3124	7#5, 9/16"	.546	10	54	63	3	.182	Yellow

**For use on:  
Type 302, 430 or 316 Stainless Steel Strand.**

Catalog Number	Strand		Units	Wt./Lbs.	Rod Diameter (Inches)	Color Code
	Size (Inches)	Mean Diameter (Inches)	Per Carton			
<b>For Use On: Type 302 and 430 Strand</b>						
SLS-5101	7/32,-3W -7W	.224 .216	50	24	.071	Blue
SLS-5102	1/4,-3W -7W	.259 .249	50	36	.085	Yellow
SLS-5103	9/32,-7W	.279	50	40	.085	Black
SLS-5104	5/16,-7W	.312	50	34	.101	Orange
SLS-5105	3/8,-3W 7W	.356 .360	25	50	.120	Green
<b>For Use On: Type 430 Strand</b>						
SLS-5106	7/16,-7W	.435	10	38	.139	Red
SLS-5107	1/2,-7W	.495	10	58	.161	Blue
<b>For Use: Type 316 Strand</b>						
SLS-6101	7/32,-3W 7W	.224 .216	50	24	.071	Blue
SLS-6102	1/4,-3W -7W	.259 .249	50	36	.085	Yellow
SLS-6103	9/32,-7W	.279	50	40	.085	Black
SLS-6104	5/16,7W	.312	50	64	.101	Orange
SLS-6105	3/8,-3W -7W	.356 .360	25	50	.120	Green