

Reeving Splice

Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

Description

PLP Reeving Splices were designed in conjunction with Otis Elevator Company as an aid to simplify marrying wire ropes during elevator repairs. Reeving splices hold galvanized steel cables in place, allowing old elevator wire ropes to be removed and replaced.

Features

- Designed to hold working loads from zero to 2,000 lbs
- Saves repair time
- Applies quickly without need of special tools
- Designed to maintain a constant, positive grip, even when ropes go slack
- For use on Galvanized Steel Elevator wire rope
- Multiple sizes available
- Patented

Documentation

Application Procedures

[SP2260 \(Reeving Splice\)](#)

Sales Materials

[Reeving Splice - Sell Sheet](#)

Part Tables

Overall Diameter of Spliced Wire Rope

Size		Reeving Splice	Overall Diameter in. (mm)
in.	mm		
5/16	8	RS-2102	.415 (10.54)
3/8	9	RS-2103	.477 (12.11)
7/16	11	RS-2104	.539 (13.71)
1/2	12	RS-2105	.640 (16.25)
9/16	14	RS-2106	.702 (17.83)
5/8	15	RS-2107	.797 (20.24)
11/16	17	RS-2108	.887 (22.52)
3/4	19	RS-2109	.950 (24.13)
13/16	20	RS-2110	1.036 (26.31)
7/8	22	RS-2111	1.113 (28.27)
1	25	RS-2112	1.238 (31.44)

Catalog Number	Wire Rope				Units	Wt/ Lb	Length		No. of Subsets	Overall Diameter		Color Code
	Size		Mean Diameter				Per Carton	in.		(mm)	in.	
	in.	(mm)	in.	(mm)								
RS-2102	5/16	8	.312	8.0	50	30	19	483	3	.415	10.54	Green
RS-2103	3/8	9	.375	9.5	50	30	22	558	3	.477	12.11	Yellow
RS-2104	7/16	11	.4375	11	50	30	25	635	4	.539	13.71	Red
RS-2105	1/2	12	.500	12.7	10	8	29	736	3	.640	16.25	Orange
RS-2106	9/16	14	.5625	14.2	10	9	32	812	4	.702	17.83	Yellow
RS-2107	5/8	15	.625	15.8	10	13	36	914	3	.797	20.24	Black
RS-2108	11/16	17	.6875	17.4	10	17	40	1016	3	.887	22.52	Red
RS-2109	3/4	19	.750	19.0	10	18	42	1066	3	.950	24.13	Green
RS-2110	13/16	20	.8125	20.6	10	24	46	1168	3	1.036	26.31	Yellow
RS-2111	7/8	22	.875	22.2	10	28	50	1270	3	1.113	28.27	Blue
RS-2112	1	25	1.00	25.4	10	41	56	1422	4	1.238	31.44	Orange