

GUY-GRIP® Dead-end

Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

Description

GUY-GRIP Dead-ends are intended for use on single wood poles associated with distribution construction. They are made of the same material as to which they are applied.

Features

- Rated at 100% of the strand's published rated breaking strength.
- Intended for single use but can be reinstalled twice within 90 days.

Documentation

Application Procedures

[SP-2045 \(GUY-GRIP® Dead-End\)](#)

[SP-3253 \(GUY-GRIP Dead-End - Multiple Down Guys\)](#)

Catalog Pages

[Guy-Grip Catalogue](#)

[GUY-GRIP Dead-End - Catalog](#)

Part Tables

RIGHT HAND LAY STANDARD.

CATALOGUE NO. GSDE	CONDUCTOR DIAMETER (mm)	COLOUR CODE	RODS PER SET	SETS PER PACK	APPROX PACK MASS (kg)	APPROX. LENGTH OF FITTING (mm)
108	2.74	ORANGE	4	20	2.5	270
144	3.66	BROWN	4	20	3	380
175	4.44	BLUE	4	20	3	480
192	4.88	YELLOW	4	20	3	520
227	5.77	RED	5	20	4	560
240	6.10	ORANGE	5	20	4	580
284	7.2	BLACK	5	30	5	600
312	7.93	BROWN	5	15	7	710
320	8.13	GREEN	5	15	8	740
345	8.76	RED	5	15	10	790
384	9.75	BLACK	6	20	10	850
396	10.05	BLUE	6	20	10	860
400	10.16	YELLOW	6	20	10	860
432	10.97	BROWN	6	20	13	890
472	12.19	GREEN	6	15	12	960
520	13.21	ORANGE	5	5	7	1300
640	16.26	BROWN	6	5	10	1660

ON REQUEST LEFT HAND LAY

372 LH	9.45	BLACK	6	20	10	850
502 LH	12.75	GREEN	6	15	12	980