

VARI-GRIP™ Dead-end

Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

Description

The unique housing, wedge and rod design of the **VARI-GRIP Dead-end** is designed to provide a holding strength of 100% of the strand's rated breaking load. The high strength U-Bolt allows for adjusting the guy strand tension without the need for a turnbuckle.

Features

- Retaining rods are made from a material that is compatible with the guy strand material
 - (e.g., aluminum-clad steel rods for aluminum-clad steel guy strand)
- Available for strand sizes of 7/16" to 1.78" (20,800 - 295,500 lbs)
- Take-up U-Bolts in sizes 0" and 18" are available for most strand sizes

Documentation

Application Procedures

[VARI-GRIP DEAD-END User Instructions](#)

Catalog Pages

[VARI- GRIP Catalogue](#)

Sales Materials

[VARI-GRIP Dead-End - Sell Sheet](#)

Part Tables

ADJUSTABLE VARI - GRIP

PART NO.	GUY	A	B (SEE NOTE 3)	C	D	E (MINIMUM) (mm)	NUTS (kN) (SEE NOTE 1)	ROD DIAM (mm)	RODS PER SET
	DIAM. (mm)								
VG 13 AC	13	0 – 457	16	M16	80	>13	(E) 150	3.25	12
VG 16 AC	16	0 – 457	16	M20	90.50	>16	189	4.47	12
VG 19 AC	19	0 – 457	16	M24	120	>19	300	4.47	12
VG 22 AC	22	0 – 457	16	M24	120	>19	355	5.2	12
VG 24 AC	24	0 – 457	18	M27	136	>22	427	5.2	14
VG 26 AC	26	0 – 457	18	M27	136	>22	484	5.2	14
VG 28 AC	28	0 – 457	45	M33	165	>26	596	6.4	14
VG 32 AC	32	0 – 457	45	M33	165	>26	775	6.4	16

NON- ADJUSTABLE VARI- GRIP

PART NO.	GUY	A	B (SEE NOTE 3)	C	D	E (MINIMUM) (mm)	UTS (kN) (SEE NOTE 1)	ROD DIAM. (mm)	RODS PER SET
	DIAM. (MM)								
VG 13 N	13	NON- ADJUSTABLE	(E)16	M16	80	>13	150	3.25	12
VG 16 N	16		16	M20	90.50	>16	189	4.47	12
VG 19 N	19		16	M24	120	>19	300	4.47	12
VG 22 N	22		16	M24	120	>19	355	5.2	12
VG 24 N	24		18	M27	136	>22	427	5.2	14
VG 26 N	26		18	M27	136	>22	484	5.2	14
VG 28 N	28		45	M33	165	>26	596	6.4	14
VG 32 N	32		45	M33	165	>26	775	6.4	16