

EY



Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

Description

These clamps are of the bolted type clamps and are designed for making a connection onto a single solid terminal stem for a pair of stranded conductors. They can be use as a single tap off from a twin conductor bundle. They should only be used for non-current carrying purposes e.g. through connections on support post insulators, voltage transformers and surge arresters as applicable.

Features

- Fasteners M12 GR. 8.8 HDG torque to 45Nm
- Cat no. to be stamped on the substation body
- All bolted clamp and conductor surfaces to be cleaned with stainless steel wire brush and a suitable conductive grease applied before use.
- Material: Cast aluminium.
- Supplied in clear, sealed, heavy duty, UV stabilised plastic bag.

Documentation

Catalog Pages

[EY Catalogue](#)

Part Tables

NEW TYPE DESIGNATION	OLD TYPE DESIGNATION	CONNECTION TO CONDUCTOR		STEM DIAMETER		RATED CURRENT [IN]	MAXIMUM VOLTAGE [UM]
		ANGLE	DIAMETER (A) (mm)	(B) (mm)	(A RMS)	(KV RMS)	
EY – A	Y 1	0°	26.5	38	1300	300	
EY – B	Y 2	0°	38.3	38	1300	420	
EY – C	Y 3	90°	26.5	38	1300	300	
EY – D	Y 4	90°	38.3	38	1300	420	
EY – E	Y 5	0°	26.5	26	833	300	
EY – F	Y 6	90°	26.5	26	833	300	
EY – G	Y 7	90°	38.3	26	833	420	
EY – H	Y 8	0°	38.3	26	833	420	
EY – J	Y 9	0°/90°	38.3	60	2400	420	

• All clamps supplied with M12 HDG bolts, nuts and washers

• Recommended Torque: 45 Nm