

# WRAPLOCK® Tie

**Weight:** 0.00kg

**Dimensions:** 0.00cm x 0.00cm x 0.00cm

## Description

**WRAPLOCK Ties** secure conductors in the top groove of interchangeable head-style insulators. They provide an improved method of securing conductor compared to clamp-top insulators or hand ties over Armor Rods.

## Features

- Superior abrasion protection for the conductor under all types of motion
- Provides superior protection by eliminating abrasion
- Elastomer component surrounds the bare conductor with a resilient cushion

## Documentation

### Application Procedures

[SP-2020 \(Wraplock Tie\)](#)

### Catalog Pages

[Wraplock Tie](#)

[Insulator/Tie Fit Information Sheet](#)

## Part Tables

# Aluminium Alloy WRAPLOCK® TIES

RIGHT HAND LAY STANDARD. ALWAYS QUOTE INSULATOR TYPE AND NECK DIAMETER.

CATALOGUE NO. AWT	CONDUCTOR DIAMETER (mm)	COLOUR CODE	SETS PER PACK	APPROX PACK MASS (kg)
192 – 201	4.88 – 5.10	BLUE	15	1.5
202 – 212	5.11 – 5.38	GREEN	15	1.5
213 – 223	5.39 – 5.66	WHITE	15	1.5
224 – 235	5.67 – 5.97	GREY	15	1.5
236 – 247	5.98 – 6.27	RED	15	1.5
248 – 259	6.28 – 6.57	ORANGE	15	1.5
260 – 269	6.58 – 6.83	GREEN	15	1.5
270 – 280	6.84 – 7.11	YELLOW	15	1.5
281 – 291	7.12 – 7.39	BLUE	15	1.5
292 – 303	7.40 – 7.70	RED	15	1.5
304 – 314	7.71 – 7.97	BROWN	15	1.5
315 – 327	7.98 – 8.30	GREY	15	1.5
328 – 340	8.31 – 8.63	BLUE	15	1.5
341 – 353	8.64 – 8.97	ORANGE	15	1.5
354 – 367	8.98 – 9.32	GREEN	15	1.5
368 – 381	9.33 – 9.67	BROWN	15	1.5
382 – 394	9.68 – 10.00	GREY	15	2.0
395 – 411	10.01 – 10.44	YELLOW	10	2.0
412 – 437	10.45 – 11.10	RED	10	2.0
438 – 463	11.11 – 11.76	BLUE	10	2.0
464 – 492	11.77 – 12.50	GREEN	10	2.0
493 – 522	12.51 – 13.27	BLACK	10	2.0
523 – 554	13.28 – 14.07	GREY	10	2.0
555 – 594	14.08 – 15.09	BROWN	10	2.0
595 – 630	15.10 – 16.00	ORANGE	10	2.0
631 – 664	16.01 – 16.86	BROWN	10	2.0
665 – 705	16.87 – 17.91	GREEN	10	2.0
706 – 747	17.92 – 18.97	WHITE	5	1.5
748 – 795	18.98 – 20.19	BLACK	5	1.5
796 – 846	20.20 – 21.49	BROWN	5	1.5
847 – 900	21.50 – 22.86	RED	5	1.5
901 – 958	22.87 – 24.33	ORANGE	5	1.5
959 – 1018	24.34 – 25.86	WHITE	5	1.5
1019 – 1083	25.87 – 27.50	BLACK	5	1.5
1084 – 1151	27.51 – 29.23	YELLOW	5	1.5
1152 – 1223	29.24 – 31.06	BROWN	5	1.5
1224 – 1240	31.07 – 31.50	RED	5	1.5



# Copper Alloy WRAPLOCK® TIES

RIGHT HAND LAY STANDARD. ALWAYS QUOTE INSULATOR TYPE AND NECK DIAMETER.

CATALOGUE NO. CWT	CONDUCTOR DIAMETER (MM)	COLOUR CODE	SETS PER PACK	APPROX PACK MASS(KG)
192 – 201	4.88 – 5.10	RED	15	5.0
202 – 212	5.11 – 5.38	YELLOW	15	5.0
213 – 223	5.39 – 5.66	GREEN	15	5.0
224 – 235	5.67 – 5.97	BLUE	15	5.0
236 – 247	5.98 – 6.27	WHITE	15	5.0
248 – 259	6.28 – 6.57	BROWN	15	5.0
260 – 269	6.58 – 6.83	RED	15	5.0
270 – 280	6.84 – 7.11	GREEN	15	5.0
281 – 291	7.12 – 7.39	ORANGE	15	5.0
292 – 303	7.40 – 7.70	YELLOW	15	5.0
304 – 314	7.71 – 7.97	BLUE	15	5.0
315 – 327	7.98 – 8.30	BLACK	15	5.0
328 – 340	8.31 – 8.63	RED	15	5.0
341 – 353	8.64 – 8.97	WHITE	15	5.0
354 – 367	8.98 – 9.32	BROWN	15	5.0
368 – 381	9.33 – 9.67	BLACK	15	5.0
382 – 394	9.68 – 10.00	RED	15	5.0
395 – 411	10.01 – 10.44	ORANGE	10	6.5
412 – 437	10.45 – 11.10	GREEN	10	6.5
438 – 463	11.11 – 11.76	BLUE	10	6.5
464 – 492	11.77 – 12.50	WHITE	10	6.5
493 – 522	12.51 – 13.27	BROWN	10	6.5
523 – 554	13.28 – 14.07	RED	10	6.5
555 – 594	14.08 – 15.09	BLACK	10	6.5
595 – 630	15.10 – 16.00	ORANGE	10	6.5
631 – 664	16.01 – 16.86	GREEN	10	6.5
665 – 705	16.87 – 17.91	YELLOW	10	6.5
706 – 747	17.92 – 18.97	WHITE	5	5.0
748 – 795	18.98 – 20.19	BLUE	5	5.0
796 – 846	20.20 – 21.49	BROWN	5	5.0
847 – 900	21.50 – 22.86	RED	5	5.0
901 – 958	22.87 – 24.33	BLACK	5	5.0
959 – 1018	24.34 – 25.86	ORANGE	5	5.0
1019 – 1083	25.87 – 27.50	GREEN	5	5.0
1084 – 1151	27.51 – 29.23	YELLOW	5	5.0
1152 – 1223	29.24 – 31.06	WHITE	5	5.0
1224 – 1240	31.07 – 31.50	BLUE	5	5.0

**Videos**

**Product Gallery**

