

EPT 2



Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

Description

These bolted-type clamps shall be used mainly for connecting twin stranded conductors to earth switches with 8-hole pad terminals.

Features

- To connect a flat terminal to a stranded conductor by bolting palm to terminal and crimping conductor in compression tube.
- Recommended fasteners M12 GR. 8.8 HDG torque to 45Nm.
- Compression die and size stamped on tube . All terminal, palm and conductor surfaces to be cleaned with stainless steel wire brush and a suitable conductive grease applied before use.
- Material: Cast aluminium .
- Supplied in clear, sealed, heavy duty, UV stabilized plastic bag.
- Cat. no. to be stamped as shown.

Documentation

Catalog Pages

[EPT 2 Catalogue](#)

Part Tables

| NEW TYPE DESIGNATION | CONDUCTOR DIAMETER (mm) (A) | CONDUCTOR SPACING (mm) | EQUIPMENT TERMINAL | RATED CURRENT [IN] (A RMS) | MAXIMUM VOLTAGE [UM] (KV RMS) |
|---------------------------------|--|---------------------------------------|-------------------------------|---|--|
| EPT2 – A | 2 x 26.5 | 150 | 8 Bolt Pad | 1700 | 145 |
| EPT2 – B | 2 x 38.3 | 150 | 8 Bolt Pad | 2700 | 420 |

- All clamps supplied with M12 HDG bolts, nuts and washers
- Recommended Torque: 45 Nm