

TBTC-C2

Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

Documentation Catalogue Page

[TBTC-C2 Catalogue](#)

Part Tables

ESKOM CODE	PLP CATALOGUE NO.	TUBE	CONDUCTOR			AFTER	ALCAN DIE	MINIMUM	MAXIMUM	WEIGHT kg
		DIAM. (A) mm	DIAM. (B) mm	(C) mm	ANGLE OFFSET	COMP. (A.F.) mm		RATED CURRENT @ 90°C	VOLTAGE kV rms	
ETP-IL-2-A	TBTC-80-26-C2-0	80	2x26.5	155	0	36	DA-10	1700	145	3.5
ETP-IL-2-B	TBTC-80-26-C2-45	80	2X26.5	155	45	36	DA-10	1700	145	3.5
ETP-IL-2-C	TBTC-80-26-C2-90	80	2X26.5	155	90	36	DA-10	1700	145	3.5
ETP-IL-2-D	TBTC-80-38-C2-0	80	2X38.3	155	0	49	DA-13	2000	145	3.9
ETP-IL-2-E	TBTC-80-38-C2-45	80	2X38.3	155	45	49	DA-13	2000	145	3.9
ETP-IL-2-F	TBTC-80-38-C2-90	80	2X38.3	155	90	49	DA-13	2000	145	3.9
ETP-IL-2-N	TBTC-120-26-C2-0	120	2X26.5	180	0	36	DA-10	1700	145	4.9
ETP-IL-2-P	TBTC-120-26-C2-45	120	2X26.5	180	45	36	DA-10	1700	145	4.9
ETP-IL-2-Q	TBTC-120-26-C2-90	120	2X26.5	180	90	36	DA-10	1700	145	4.9
ETP-IL-2-R	TBTC-120-38-C2-0	120	2X38.3	180	0	49	DA-13	2700	145	5.4
ETP-IL-2-S	TBTC-120-38-C2-45	120	2X38.3	180	45	49	DA-13	2700	145	5.4
ETP-IL-2-T	TBTC-120-38-C2-90	120	2X38.3	180	90	49	DA-13	2700	145	5.4
ETP-IL-2-AA	TBTC-200-38-C2-0	200	2x38.3	220	0	49	DA-13	2700	420	13.7
ETP-IL-2-AB	TBTC-200-38-C2-45	200	2X38.3	220	45	49	DA-13	2700	420	13.7
ETP-IL-2-AC	TBTC-200-38-C2-90	200	2X38.3	220	90	49	DA-13	2700	420	13.7
ETP-IL-2-AD	TBTC-250-38-C2-0	250	2X38.3	245	0	49	DA-13	2700	420	14.9
ETP-IL-2-AE	TBTC-250-38-C2-45	250	2X38.3	245	45	49	DA-13	2700	420	14.9
ETP-IL-2-AF	TBTC-250-38-C2-90	250	2X38.3	245	90	49	DA-13	2700	420	14.9