

Twin- Ties

Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

Description

Twin Ties, Provide an improved method of securing conductors when compared to hand-binding or insulator clamps. Protection is provided against conductor abrasion, as occurs with hand-binding, and they provide better RIV characteristics. The pad provides protection for the conductor against abrasion from the insulator.

Features

- One design will accommodate most C-neck to F-neck insulators while another will accommodate most F-neck to J-neck insulators.

Documentation

Application Procedures

[SP-2825-1 \(EZ-WRAP[®] Twin Tie\)](#)

Catalog Pages

[Aluminium Twin Ties-Catalogue](#)

[Insulator/Tie Fit Information Sheet](#)

Part Tables

Aluminium Alloy TWIN-TIES

RIGHT HAND LAY STANDARD. ALWAYS QUOTE INSULATOR TYPE AND NECK DIAMETER.

CATALOGUE NO. ATT	CONDUCTOR DIAMETER (mm)	COLOUR CODE	SETS PER PACK	APPRO. PACK MASS (kg)
192 – 201	4.88 – 5.10	BLUE	60	0.12
202 – 212	5.11 – 5.38	GREEN	60	0.12
213 – 223	5.39 – 5.66	WHITE	60	0.12
224 – 235	5.67 – 5.97	GREY	60	0.12
236 – 247	5.98 – 6.27	RED	60	0.12
248 – 259	6.28 – 6.57	ORANGE	60	0.12
260 – 269	6.58 – 6.83	GREEN	60	0.12
270 – 280	6.84 – 7.11	YELLOW	60	0.12
281 – 291	7.12 – 7.39	BLUE	40	0.16
292 – 303	7.40 – 7.70	RED	40	0.16
304 – 314	7.71 – 7.97	BROWN	40	0.16
315 – 327	7.98 – 8.30	GREY	40	0.16
328 – 340	8.31 – 8.63	BLUE	40	0.16
341 – 353	8.64 – 8.97	ORANGE	40	0.16
354 – 367	8.98 – 9.32	GREEN	40	0.16
368 – 381	9.33 – 9.67	BROWN	40	0.16
382 – 394	9.68 – 10.00	GREY	40	0.16
395 – 411	10.01 – 10.44	YELLOW	40	0.16
412 – 437	10.45 – 11.10	RED	40	0.16
438 – 463	11.11 – 11.76	BLUE	40	0.26
464 – 492	11.77 – 12.50	GREEN	40	0.26
493 – 522	12.51 – 13.27	BLACK	40	0.26
523 – 554	13.28 – 14.07	GREY	40	0.26
555 – 594	14.08 – 15.09	BROWN	40	0.26
595 – 630	15.10 – 16.00	ORANGE	30	0.327
631 – 664	16.01 – 16.86	BROWN	30	0.327
665 – 705	16.87 – 17.91	GREEN	30	0.327
706 – 747	17.92 – 18.97	WHITE	30	0.327
748 – 795	18.98 – 20.19	BLACK	30	0.327
796 – 846	20.20 – 21.49	BROWN	30	0.327
847 – 900	21.50 – 22.86	RED	30	0.327
901 – 958	22.87 – 24.33	ORANGE	30	0.327
959 – 1018	24.34 – 25.86	WHITE	30	0.4
1019 – 1083	25.87 – 27.50	BLACK	30	0.4
1084 – 1151	27.51 – 29.23	YELLOW	30	0.4
1152 – 1223	29.24 – 31.06	BROWN	30	0.4
1224 – 1240	31.07 – 31.50	RED	30	0.4

Copper Alloy TWIN-TIES

RIGHT HAND LAY STANDARD. ALWAYS QUOTE INSULATOR TYPE AND NECK DIAMETER.

CATALOGUE NO. CTT	CONDUCTOR DIAMETER (mm)	COLOUR CODE	SETS PER PACK	APPRO. PACK MASS (kg)
192 – 201	4.88 – 5.10	RED	60	0.35
202 – 212	5.11 – 5.38	YELLOW	60	0.35
213 – 223	5.39 – 5.66	GREEN	60	0.35
224 – 235	5.67 – 5.97	BLUE	60	0.35
236 – 247	5.98 – 6.27	WHITE	60	0.35
248 – 259	6.28 – 6.57	BROWN	60	0.35
260 – 269	6.58 – 6.83	RED	60	0.35
270 – 280	6.84 – 7.11	GREEN	60	0.35
281 – 291	7.12 – 7.39	ORANGE	40	0.45
292 – 303	7.40 – 7.70	YELLOW	40	0.45
304 – 314	7.71 – 7.97	BLUE	40	0.45
315 – 327	7.98 – 8.30	BLACK	40	0.45
328 – 340	8.31 – 8.63	RED	40	0.45
341 – 353	8.64 – 8.97	WHITE	40	0.45
354 – 367	8.98 – 9.32	BROWN	40	0.45
368 – 381	9.33 – 9.67	BLACK	40	0.45
382 – 394	9.68 – 10.00	RED	40	0.45
395 – 411	10.01 – 10.44	ORANGE	40	0.45
412 – 437	10.45 – 11.10	GREEN	40	0.45
438 – 463	11.11 – 11.76	BLUE	40	0.45
464 – 492	11.77 – 12.50	WHITE	40	0.45
493 – 522	12.51 – 13.27	BROWN	40	0.45
523 – 554	13.28 – 14.07	RED	40	0.45
555 – 594	14.08 – 15.09	BLACK	40	0.45
595 – 630	15.10 – 16.00	ORANGE	30	0.60
631 – 664	16.01 – 16.86	GREEN	30	0.60
665 – 705	16.87 – 17.91	YELLOW	30	0.60
706 – 747	17.92 – 18.97	WHITE	30	0.60
748 – 795	18.98 – 20.19	BLUE	30	0.60
796 – 846	20.20 – 21.49	BROWN	30	0.60
847 – 900	21.50 – 22.86	RED	30	0.60
901 – 958	22.87 – 24.33	BLACK	30	0.60
959 – 1018	24.34 – 25.86	ORANGE	30	0.60
1019 – 1083	25.87 – 27.50	GREEN	30	0.60
1084 – 1151	27.51 – 29.23	YELLOW	30	0.60
1152 – 1223	29.24 – 31.06	WHITE	30	0.60
1224 – 1240	31.07 – 31.50	BLUE	30	0.60

Videos

Product Gallery

