

TBHXS

Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

Documentation Catalog Page

[TBHXS Catalogue](#)

[TBHXS -2 Catalogue](#)

Part Tables

ESKOM CODE	PLP CATALOGUE NO.	TUBE DIAM. (A) mm	STEM DIAM. (B) mm	(C) mm	(D) mm	MINIMUM	MAXIMUM	WEIGHT kg
						RATED CURRENT @ 90°C	VOLTAGE kV rms	
EEC-H/VS-F-E	TBHXS-200-38	200	38	820	520	2500	800	27.6
EEC-H/VS-F-F	TBHXS-200-60	200	60	880	520	3150	800	28.9
EEC-H/VS-F-G	TBHXS-250-38	250	38	870	550	2500	800	28.9
EEC-H/VS-F-H	TBHXS-250-60	250	60	930	550	3150	800	30.1

ESKOM CODE	PLP CATALOGUE NO.	TUBE DIAM. (A) mm	STEM DIAM. (B) mm	(C) mm	(D) mm	MINIMUM	MAXIMUM	WEIGHT kg
						RATED CURRENT @ 90°C	VOLTAGE kV rms	
EEC-H/VS-TB-A	TBHXS-80-26	80	26	625		900	145	6.9
EEC-H/VS-TB-B	TBHXS-80-38	80	38	625		1350	145	6.8
EEC-H/VS-TB-C	TBHXS-80-60	80	60	645		2000	145	8.2
EEC-H/VS-TB-G	TBHXS-120-26	120	26	645		900	145	8.9
EEC-H/VS-TB-H	TBHXS-120-38	120	38	645		1350	145	8.8
EEC-H/VS-TB-J	TBHXS-120-60	120	60	645		2000	145	9.6