

Spool Tie

Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

Description

The **Spool Tie** is intended for use on aluminum based conductors with diameters from .190" to .968". Each Spool Tie is supplied with an elastomeric tie tube designed to minimize abrasion to bare conductors and insulators. For application on jacketed conductors, the tube may be discarded. Spool Ties can also be applied to bare conductor without the tube where desired, although consideration of abrasion should be given.

Features

- Each Spool Tie is supplied with an elastomeric tie tube designed for abrasion protection with bare conductors

Documentation

Application Procedures

[SP-2066 \(Spool Tie\)](#)

[SP-2711 \(Spool Tie-Secondary Application\)](#)

Catalog Pages

[Spool and Side Tie Catalogue](#)

Part Tables

Galvanised Steel Side and Spool Ties for Copper Conductors

RIGHT HAND LAY STANDARD. ALWAYS QUOTE INSULATOR TYPE AND NECK DIAMETER.

CATALOGUE NO. CST	CONDUCTOR DIAMETER (mm)	COLOUR CODE	SETS PER PACK	APPROX PACK MASS (kg)
192 – 201	4.88 – 5.10	RED	100	7.5
202 – 212	5.11 – 5.38	YELLOW	100	7.5
213 – 223	5.39 – 5.66	GREEN	100	7.5
224 – 235	5.67 – 5.97	BLUE	100	7.5
236 – 247	5.98 – 6.27	WHITE	100	8
248 – 259	6.28 – 6.57	BROWN	100	8
260 – 269	6.58 – 6.83	RED	100	8
270 – 280	6.84 – 7.11	GREEN	100	8
281 – 291	7.12 – 7.39	ORANGE	50	6
292 – 303	7.40 – 7.70	YELLOW	50	6
304 – 314	7.71 – 7.97	BLUE	50	6
315 – 327	7.98 – 8.30	BLACK	50	6
328 – 340	8.31 – 8.63	RED	50	7
341 – 353	8.64 – 8.97	WHITE	50	7
354 – 367	8.98 – 9.32	BROWN	50	7
368 – 381	9.33 – 9.67	BLACK	50	7.5
382 – 394	9.68 – 10.00	RED	50	7.5
395 – 411	10.01 – 10.44	ORANGE	50	7.5
412 – 437	10.45 – 11.10	GREEN	50	8
438 – 463	11.11 – 11.76	BLUE	50	8

Videos

Product Gallery