

Alloy Top Tie

Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

Description

Preformed Line Products **Alloy Ties** are intended for use in corrosive environments on aluminum based conductors. They are suitable for use on ANSI C29 compliant insulators. Alloy Ties are designed for use in coastal areas. They have been performance-matched to aluminum conductors and are much more corrosive-resistant than standard aluminized steel ties.

Features

- Easily applied by hand or with hot sticks
- Performance matched materials
- Will not damage the conductor during installation
- Conductor application up to 1.24"
- Accommodates line angles 0-40° depending on application
- Resiliency built in to protect the conductor
- Reacts like the conductor under loading
- Adheres to NESC Standards
- Will hold a minimum of 700 lbs. of unbalanced load (According to rigorous PLP testing)
- Suitable for use with either ANSI compliant polymer or porcelain insulators
- Made in the USA

Documentation

Application Procedures

[SP-2668 \(Alloy Top Tie\)](#)

Sales Materials

[Alloy Ties - Sell Sheet](#)

Part Tables

Alloy Top Ties				
C-Neck	F-Neck	Dia. Range (in) Min.	Dia. Range (in) Max.	Color Code
ALC-1104	ALF-1204	0.316	0.357	Red
ALC-1105	ALF-1205	0.358	0.405	Yellow
ALC-1106	ALF-1206	0.406	0.459	Blue
ALC-1107	ALF-1207	0.460	0.520	Orange
ALC-1108	ALF-1208	0.521	0.588	Red
ALC-1109	ALF-1209	0.589	0.665	Purple
ALC-1110	ALF-1210	0.666	0.755	Brown
ALC-1111	ALF-1211	0.756	0.858	Red

Videos

Alloy Top Tie - Installation Video