

# Lashing Rod

**Weight:** 0.00kg

**Dimensions:** 0.00cm x 0.00cm x 0.00cm

## Description

**PREFORMED Lashing Rods** can be used on all types of messengered overhead cables. They are particularly adaptable to spans obstructed by trees, short spans over traffic intersections and support of power cable into and out of substations.

## Features

- Made of the same basic material as the messenger to which they are applied. This pertains to Galvanized, Copperweld, Aluminum-clad Steel, Stainless Type 302, and Stainless Type 316.
- For use in highly corrosive environment, or on extra heavy cables, a neoprene coating can be applied to the Galvanized, Copperweld®, Aluminum-clad Steel or Stainless Steel Lashing Rods.

## Documentation

### Application Procedures

[SP-2085 \(Lashing Rod\)](#)

## Catalog Pages

[Lashing Rods-SLR Catalogue](#)

## Part Tables

### Galvanized Steel

**(For use on: Galvanized Messengered Cable)**

Catalog Number	C-Coat Diameter Range		Units	Wt/Lbs	Length (Feet)	Rod Diameter (Inches)	Color Code
	Min.	Max.	Per Carton				
LR-6100	.400	.439	100	13	5 ft	.086	Red
LR-6101	.440	.489	100	13	5 ft	.086	White
LR-6102	.490	.539	100	13	5 ft	.086	Orange
LR-6103	.540	.599	100	13	5 ft	.086	Green
LR-6104	.600	.669	100	17	5 ft	.100	Yellow
LR-6105	.670	.749	100	17	5 ft	.100	White
LR-6106	.750	.839	100	17	5 ft	.100	Red
LR-6107	.840	.939	100	17	5 ft	.100	White
LR-6108	.940	1.049	100	17	5 ft	.100	Orange
LR-6109	1.050	1.169	100	24	5 ft	.119	Green
LR-6110	1.170	1.309	100	24	5 ft	.119	Yellow
LR-6111	1.310	1.459	100	24	5 ft	.119	White
LR-6112	1.460	1.629	100	37	6 ft	.138	Red
LR-6113	1.630	1.819	100	37	6 ft	.138	White
LR-6114	1.820	2.039	100	37	6 ft	.138	Orange
LR-6115	2.040	2.279	100	52	6 ft	.159	Green
LR-6116	2.280	2.539	100	54	6 ft	.159	Yellow
LR-6117	2.540	2.839	100	56	6 ft	.159	White
LR-6118	2.840	3.179	100	58	6 ft	.159	Red
LR-6119	3.180	3.559	50	34	6 ft	.172	White
LR-6120	3.560	3.999	50	35	6 ft	.172	Orange
LR-6121	4.000	4.479	50	36	6 ft	.172	Green
LR-6122	4.480	4.999	50	37	6 ft	.172	Yellow
LR-6123	5.000	5.599	50	38	6 ft	.172	White
LR-6124	5.600	6.299	50	39	6 ft	.172	Red

## **Aluminum-Clad Steel**

**(For use on: Aluminum-Clad Steel or Aluminum-Clad Steel Messengered Cable)**

Catalog Number	Diameter Range		Units	Wt/Lbs	Length (Feet)	Rod Diameter (Inches)	Color Code
	Min.	Max.	Per Carton				
LR-2100	.400	.439	100	14	5 ft	.102	Red
LR-2101	.440	.489	100	14	5 ft	.102	White
LR-2102	.490	.539	100	14	5 ft	.102	Orange
LR-2103	.540	.599	100	14	5 ft	.102	Green
LR-2104	.600	.669	100	18	5 ft	.114	Yellow
LR-2105	.670	.749	100	18	5 ft	.114	White
LR-2106	.750	.839	100	18	5 ft	.114	Red
LR-2107	.840	.939	100	18	5 ft	.114	White
LR-2108	.940	1.049	100	18	5 ft	.114	Orange
LR-2109	1.050	1.169	100	24	5 ft	.128	Green
LR-2110	1.170	1.309	100	24	5 ft	.128	Yellow
LR-2111	1.310	1.459	100	24	5 ft	.128	White
LR-2112	1.460	1.629	100	36	6 ft	.144	Red
LR-2113	1.630	1.819	100	36	6 ft	.144	White
LR-2114	1.820	2.039	100	36	6 ft	.144	Orange
LR-2115	2.040	2.279	100	46	6 ft	.162	Green
LR-2116	2.280	2.539	100	47	6 ft	.162	Yellow
LR-2117	2.540	2.839	100	48	6 ft	.162	White
LR-2118	2.840	3.179	100	49	6 ft	.162	Red
LR-2119	3.180	3.559	50	32	6 ft	.182	White
LR-2120	3.560	3.999	50	33	6 ft	.182	Orange
LR-2121	4.000	4.479	50	34	6 ft	.182	Green
LR-2122	4.480	4.999	50	35	6 ft	.182	Yellow
LR-2123	5.000	5.599	50	36	6 ft.	.182	White
LR-2124	5.600	6.299	50	37	6 ft	.182	Red

## Copperweld®

(For use on: Copperweld Messengered Cable)

Catalog Number	Diameter Range		Units	Wt/Lbs	Length (Feet)	Rod Diameter (Inches)	Color Code
	Min.	Max.	Per Carton				
LR-3100	.400	.439	100	18	5 ft	.102	Red
LR-3101	.440	.489	100	18	5 ft	.102	White
LR-3102	.490	.539	100	18	5 ft	.102	Orange
LR-3103	.540	.599	100	18	5 ft	.102	Green
LR-3104	.600	.669	100	23	5 ft	.114	Yellow
LR-3105	.670	.749	100	23	5 ft	.114	White
LR-3106	.750	.839	100	23	5 ft	.114	Red
LR-3107	.840	.939	100	23	5 ft	.114	White
LR-3108	.940	1.049	100	23	5 ft	.114	Orange
LR-3109	1.050	1.169	100	29	5 ft	.128	Green
LR-3110	1.170	1.309	100	29	5 ft	.128	Yellow
LR-3111	1.310	1.459	100	29	5 ft	.128	White
LR-3112	1.460	1.629	100	45	6 ft	.144	Red
LR-3113	1.630	1.819	100	45	6 ft	.144	White
LR-3114	1.820	2.039	100	45	6 ft	.144	Orange
LR-3115	2.040	2.279	100	56	6 ft	.162	Green
LR-3116	2.280	2.539	100	58	6 ft	.162	Yellow
LR-3117	2.540	2.839	100	58	6 ft	.162	White
LR-3118	2.840	3.179	100	60	6 ft	.162	Red
LR-3119	3.180	3.559	50	40	6 ft	.182	White
LR-3120	3.560	3.999	50	41	6 ft	.182	Orange
LR-3121	4.000	4.479	50	42	6 ft	.182	Green
LR-3122	4.480	4.999	50	43	6 ft	.182	Yellow
LR-3123	5.000	5.599	50	44	6 ft	.182	White
LR-3124	5.600	6.299	50	45	6 ft	.182	Red

## **Stainless Steel, Type 302**

**(For use on: Type 302 Stainless Steel Messengered Cable)**

Catalog Number	Diameter Range		Units	Wt/Lbs	Length (Feet)	Rod Diameter (Inches)	Color Code
	Min.	Max.	Per Carton				
LR-4100	.400	.439	100	13	5 ft	.085	Red
LR-4101	.440	.489	100	13	5 ft	.085	White
LR-4102	.490	.539	100	13	5 ft	.085	Orange
LR-4103	.540	.599	100	13	5 ft	.085	Green
LR-4104	.600	.669	100	18	5 ft	.101	Yellow
LR-4105	.670	.749	100	18	5 ft	.101	White
LR-4106	.750	.839	100	18	5 ft	.101	Red
LR-4107	.840	.939	100	18	5 ft	.101	White
LR-4108	.940	1.049	100	18	5 ft	.101	Orange
LR-4109	1.050	1.169	100	25	5 ft	.120	Green
LR-4110	1.170	1.309	100	25	5 ft	.120	Yellow
LR-4111	1.310	1.459	100	25	5 ft	.120	White
LR-4112	1.460	1.629	100	40	6 ft	.139	Red
LR-4113	1.630	1.819	100	40	6 ft	.139	White
LR-4114	1.820	2.039	100	40	6 ft	.139	Orange
LR-4115	2.040	2.279	100	54	6 ft	.161	Green
LR-4116	2.280	2.539	100	56	6 ft	.161	Yellow
LR-4117	2.540	2.839	100	56	6 ft	.161	White
LR-4118	2.840	3.179	100	58	6 ft	.161	Red
LR-4119	3.180	3.559	50	36	6 ft	.175	White
LR-4120	3.560	3.999	50	37	6 ft	.175	Orange
LR-4121	4.000	4.479	50	38	6 ft	.175	Green
LR-4122	4.480	4.999	50	39	6 ft	.175	Yellow
LR-4123	5.000	5.599	50	40	6 ft	.175	White
LR-4124	5.600	6.299	50	41	6 ft	.175	Red

## **Stainless Steel, Type 316**

**(For use on: Type 316 Stainless Steel Messengered Cable)**

Catalog Number	Diameter Range		Units	Wt/Lbs	Length (Feet)	Rod Diameter (Inches)	Color Code
	Min.	Max.	Per Carton				
LR-5100	.400	.439	100	13	5 ft	.085	Red
LR-5101	.440	.489	100	13	5 ft	.085	White
LR-5102	.490	.539	100	13	5 ft	.085	Orange
LR-5103	.540	.599	100	13	5 ft	.085	Green
LR-5104	.600	.669	100	18	5 ft	.101	Yellow
LR-5105	.670	.749	100	18	5 ft	.101	White
LR-5106	.750	.839	100	18	5 ft	.101	Red
LR-5107	.840	.939	100	18	5 ft	.101	White
LR-5108	.940	1.049	100	18	5 ft	.101	Orange
LR-5109	1.050	1.169	100	25	5 ft	.120	Green
LR-5110	1.170	1.309	100	25	5 ft	.120	Yellow
LR-5111	1.310	1.459	100	25	5 ft	.120	White
LR-5112	1.460	1.629	100	40	6 ft	.139	Red
LR-5113	1.630	1.819	100	40	6 ft	.139	White
LR-5114	1.820	2.039	100	40	6 ft	.139	Orange
LR-5115	2.040	2.279	100	54	6 ft	.161	Green
LR-5116	2.280	2.539	100	56	6 ft	.161	Yellow
LR-5117	2.540	2.839	100	56	6 ft	.161	White
LR-5118	2.840	3.179	100	58	6 ft	.161	Red
LR-5119	3.180	3.559	50	36	6 ft	.175	White
LR-5120	3.560	3.999	50	37	6 ft	.175	Orange
LR-5121	4.000	4.479	50	38	6 ft	.175	Green
LR-5122	4.480	4.999	50	39	6 ft	.175	Yellow
LR-5123	5.000	5.599	50	40	6 ft	.175	White
LR-5124	5.600	6.299	50	41	6 ft	.175	Red